YAMAHA

RX-A1000

AV Receiver

Owner's Manual

English for Oceania



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

About this manual

- Some features are not available in certain regions.
- This manual is created prior to production. Design and specifications are subject to change in part as a result of improvements, etc. In case of differences between the manual and product, the product has priority.
- "10 ON SCREEN" (example) indicates the name of the parts on the remote control. Refer to the "Remote control" (☞p. 12) for the information about each position of the parts.
- 1 indicates that the reference is in the footnote. Refer to the corresponding numbers on the bottom of the page.
- ☞ indicates the page describing the related information.
- Click on the " " at the bottom of the page to display the corresponding page in "Part names and functions."
  - Front panel
  - Rear panel
  - Front panel display
  - Remote control

Supplied accessories

Check that you received all of the following parts.

- Remote control
- Batteries (AAA, R03, UM-4) x 2
- Power cable
- YPAO microphone
- AM loop antenna
- Indoor FM antenna

Language selection

This procedure allows you to select the language of menus and messages on the TV screen.

1 **Press 10 ON SCREEN to display the ON SCREEN menu.**

2 **Press 11 Cursor △ / ▽ to select "Setup" and press 11 ENTER.**



3 **Press 11 Cursor ◁ / ▷ to select the "Language" and press 11 ENTER.**



4 **Press 11 Cursor △ / ▽ to select the favorite language from the following options.**

English (English), 日本語 (Japanese), Français (French), Deutsch (German), Español (Spanish), Русский (Russian)

5 **Press 10 ON SCREEN to close the ON SCREEN menu.**

CONTENTS

INTRODUCTION

Features and capabilities 5

Using the TV OSD to operate the unit 6

Basic operation of OSD menu 6
Viewing or modifying content for the current input source <Content window> 6
Configuring settings for this unit <ON SCREEN menu> 6
Adjust settings for each input source <Option menu> 7

Part names and functions 8

Front panel 8
Front panel with the cover opened 9
Rear panel 10
Front panel display 11
Remote control 12
Remote control (sequel) 13
On-screen display 14

CONNECTIONS

Connecting speakers 15

Speaker channels and functions 15
Speaker layout 16
Connecting speakers and subwoofers 19

Advanced speaker configuration 22

Speaker layout utilizing an external power amplifier 22
Connecting an external amplifier 22

Connecting external components 23

Jacks and cables 23
Connecting a TV monitor 24
Connecting BD/DVD players and other devices 27
Connecting game consoles or video camcorders 32
Connecting a multi-format player or an external decoder 32
Connecting a SCENE link playback-compatible device 33
Using the Trigger function to link external component power 33
Connecting audio/video recording devices 34
Connecting to the network 34
Connecting a USB storage device 35

Connecting the FM/AM antennas 36

Setting up the speaker parameters automatically (YPAO) 37

PLAYBACK

Basic playback procedure 44

Changing input settings with a single key (SCENE function) 46

Selecting the SCENE suitable for the external component 46

Enjoying favorite sound field effect 47

Selecting sound programs and sound decoders 47
Enjoying spatial sound with the CINEMA DSP function 47
Enjoying unprocessed playback (Straight decoding mode) 48
Enjoying Hi-Fi Sound Quality (Pure Direct Mode) 49
Enjoying stereo playback 49
Enjoying compressed music source with better sound quality (Compressed Music Enhancer) 49
Sound programs 50

Controlling this unit while viewing the TV screen 52

Basic operations via the TV screen display 52

Configuring settings specific to an individual input source (Option menu) 54

Option menu display and setup 54
Option menu 55

Confirming and operating input sources from the content window 58

Displaying the content window on the TV screen 58
Switching the display between the Now Playing view and the Browse view 58

FM/AM tuning 59

Selecting a frequency for reception (Normal tuning) 59
Navigating the FM/AM tuner from the content window 60

Playing back tunes on the PC 62

Windows Media Player setup 62
Playback of PC music contents 62

Playing back tunes on the USB storage devices 64

Playback of the USB storage device 64

Listening to the Internet Radio 66

Listening to Internet Radio 66

Using shortcut function 68

Playing back tunes from your iPod™/iPhone™ 69

Connecting the Universal Dock for iPod 69
Controlling an iPod™/iPhone™ 69
Playing iPod™/iPhone™ from the menu screen (Menu browse control) 70
Operating basic playback functions via the remote control (Simple remote control) 71
Playing iPod™/iPhone™ with wireless connection 71

Playing back tunes from Bluetooth™ components 73

Connecting a Yamaha Bluetooth Wireless Audio Receiver 73
Pairing Bluetooth™ components 73
Using Bluetooth™ components 74

Controlling this unit by using the Web browser (Web Control Center) 75

Displaying and Operating Web Control Center 75

SETUP

Configuring input sources (Input menu) 77
Configuring input sources 77
Input menu 78

Editing the SCENE function (Scene menu) 80
Editing a scene 80
Scene menu 81
Simple registering as the SCENE 82

Setting sound program parameters (Sound Program menu) 83
Editing sound programs 83
CINEMA DSP parameters 84
Parameters usable in certain sound programs 86
Parameters usable in surround decoder 87

Setting various functions (Setup menu) 88
Operating the Setup menu 88
Setup menu 89
Manages settings for speakers 89
Setting the audio output function of this unit 93
Setting this unit's video output function 95
Setting HDMI functions 96
Adjusting this unit's network parameters 98
Setting this unit's multi-zone function 99
Making the receiver easier to use 100
Language 103

Confirming information of this unit (Information menu) 104
Selecting information 104

Controlling the remote control to operate various functions 106
Keys connecting external components 106
Default remote control code settings 106
Registering remote control codes for external component operations 107
Resetting all remote control codes 108

Extended functionality that can be configured as needed (Advanced Setup menu) 109
Displaying/Setting the Advanced Setup menu 109
Setting the impedance of speakers 109
Remote sensor 110
Avoiding crossing remote control signals when using multiple Yamaha receivers 110
Changing TV format 111
Removing HDMI video output up-scaling limits 111
Recovery and backup of the system settings 111
Initializing various settings for this unit 111
Firmware update 112
Firmware version 112

Using the HDMI Control function 113

Enjoying the contents in another room 117
Connecting Zone2 117
Controlling Zone2 119
Enjoying the music in all rooms 119

APPENDIX

Troubleshooting 120
General 120
HDMI™ 122
Tuner (FM/AM) 123
USB and Network 124
iPod™/iPhone™ 125
Bluetooth™ 126
Remote control 126

Glossary 127
Audio information 127
Sound program information 128
Video information 129
Compatibility of the input and output video signals 129

Information on HDMI™ 130

About trademarks 131

Specifications 132

Index 134

INTRODUCTION

Features and capabilities

■ **Built-in high-quality, high-power 7-channel amplifier**

■ **Multi-channel speaker configuration capability**
- 2- to 7.1-channel speaker configurations 16
- Presence speaker connections for playback with a richer sound field effect 19
- Bi-amplification connections for high-quality playback 20
- External amplifier connections for high-quality playback and expansion of channels 22
- Speaker impedance configuration 20

■ **HDMI compatibility**
- 8 HDMI input jacks (7 on the rear, 1 on the front) supporting 3D video signal input 27
- 2 selectable HDMI output jacks supporting Audio Return Channel and 3D video signal 25

■ **Automatic setup for speaker acoustic parameters (YPAO - Yamaha Parametric Room Acoustic Optimizer) 37**

■ **Extensive inputs (max. 13) for external playback components**
- BD/DVD/CD player connection 27
- Game console / video camcorder connection 32
- Multi-format player / external decoder connection 32
- iPod/iPhone wired connection 69
- iPod/iPhone wireless connection 71
- Bluetooth component connection 73

■ **1-button input/sound program/setting switching (SCENE function) 46**

■ **Built-in sound programs and surround decoders for playback variety of sources**
- Spatial sound playback with sound field effects (CINEMA DSP) 47
- Playback with no sound field effects (straight decoding) 48
- High-fidelity sound playback (Pure Direct) 49
- Enhanced sound playback for compressed sources (Compressed Music Enhancer) 49

■ **Tuner playback**
- FM/AM broadcast 59

■ **Playback and control via network**
- Playback of music on the PC and DLNA server 62
- Internet radio service playback 66
- Control this unit via network (Web Browser Control) 75

■ **Playback of music on the USB storage devices 64**

■ **Sophisticated on-screen display (OSD) for easy operation**
- Selection of input sources, scenes, and sound programs 52
- Navigation for the current input source (content window) 58
- Setup for this unit (ON SCREEN menu) 77
- Setup for each input source (Option menu) 54

Most of functions can be operated with on-screen display on the TV screen. Refer to “Using the TV OSD to operate the unit” on the following pages for information on functions that can be controlled using the on-screen display.

■ **Customizable remote control**
- Remote control code setup for operation of external components 106

■ **Multi-room listening capability (Zone2) 117**

Using the TV OSD to operate the unit

This unit features a sophisticated on-screen display (OSD) for the TV screen. The OSD is designed to enable visual guidance that simplifies operations. The OSD mainly displays the ON SCREEN and Option menus, as well as the content window that displays the content of current input sources.

Basic operation of OSD menu

■ Select an input source, scene and sound program

– Select an input source 52
– Select a scene 52
– Select a sound program 53

■ Select a language

– Change the language displayed on the TV screen <Language> 103

Viewing or modifying content for the current input source <Content window>

■ Operate the FM/AM tuner

– Display preset stations for selection 60
– Display information on the station currently received 60
– Perform operations such as searching for and registering stations using the screen buttons 60

■ Operate the Internet radio

– Display information on the station currently received 66
– Play back the radio contents 66
– Bookmark Internet radio stations 66

■ Operate the iPod music sources

– Display the list of iPod music sources for selection 70
– Perform operations such as play, stop and pause using the TV screen <Menu browse control> 70

Configuring settings for this unit <ON SCREEN menu>

■ Configure an input source

– Change the input source name <Rename/Icon Select> 78
– Specify a format for digital audio signals <Decoder Mode> 79
– Enhance the sound of compressed audio <Enhancer> 79
– Output a video signal input from another input source while playing a multi-channel audio signal <Video Out> 79
– Charge the iPod/iPhone when this unit is in standby mode <Standby Charge> 79
– Play the music sources on PC with the external control <DMC Control> 79

■ Customize a scene

– Register or clear settings for a selected scene <Save>, <Load>, <Reset> 81, 82
– Turn on a Yamaha BD/DVD player or CD player connected to this unit automatically when a scene is selected <SCENE IR> 81
– Changing a scene name and icon <Rename/Icon Select> 82

■ Adjust a sound program (sound program)

– Adjust sound program parameters 83

■ Display settings information for this unit

– Display audio signal information <Audio Signal> 104
– Display video signal information <Video Signal> 104
– Display HDMI signal information <HDMI Monitor> 104
– Display network information <Network> 105
– Display system information <System> 105
– Display Zone information <Zone> 105

Continues to the next page

■ **Adjust acoustic parameters to match your speakers and listening environment**
– Specify speaker acoustic parameters automatically (Yamaha Parametric Room Acoustic Optimizer - YPAO) 37
– Set up this unit's speaker configuration simply <Power Amp Assign> 90
– Specify settings for each speaker <Configuration> 90
– Control volume control for each speaker <Level> 92
– Apply speaker distance settings <Distance> 92
– Control equalizer sound quality <Parametric EQ> 92
– Adjust test tone speaker <Test Tone> 93

■ **Adjust audio signals output from this unit**
– Correct lag between audio and video signals <Lipsync> 93
– Select a dynamic range adjustment method <Dynamic Range> 94
– Specify the maximum volume <Max Volume> 94
– Specify the initial volume <Initial Volume> 94
– Restrict the video signals during the Pure Direct Mode <Pure Direct Mode> 94
– Adjust DSP effect and volume level <Adaptive DSP Level> 94

■ **Adjust video signals output from this unit**
– Convert analog video signal to another type of signal <Analog to Analog Conversion> 95
– Specify the resolution and aspect ratio of output video signals <Processing> 95

■ **HDMI settings**
– Assign the audio input source for the TV <TV Audio Input> 97
– Listen to TV audio with HDMI cable connection <ARC (Audio Return Channel)> 96
– Transmit HDMI audio/video to the TV during standby mode <Standby Through> 97
– Change the output destination of HDMI input audio signals <Audio Output> 97

■ **Network settings**
– Set the IP address of this unit <IP Address> 98
– Accept the commands via LAN network when this unit is in the standby mode <Network Standby> 98
– Set the mac address filter for this unit <MAC Address Filter> 98

■ **Enable listening in multiple rooms (multi-zone function)**
– Adjust Zone2 volume <Zone2 Set> 99
– Display the Zone2 menu on the TV <Monitor Out Assign> 99
– Rename each zone or scene <Zone2 Scene Rename/Zone Rename> 100

■ **Specify other functions for this unit**
– Enter standby mode automatically when no operations are performed <Auto Power Down> 101
– Assign the other input to the selected input source <Input Assignment> 101
– Adjust the brightness of the front panel display <Dimmer> 102
– Change the wall paper displayed on the TV screen <Wall Paper> 102
– Specify the function of the TRIGGER OUT jack for controlling external components <Trigger Output1/Trigger Output2> 102
– Prohibit changes to settings <Memory Guard> 103

Adjust settings for each input source <Option menu>

– Adjust bass and treble levels <Tone Control> 56
– Enable low-volume background music <Adaptive DRC> 56
– Enjoying more spatial sound fields <CINEMA DSP 3D Mode> 56
– Adjust the vertical position of dialogues <Dialogue Lift> 56
– Select the 5.1-channel signal playback method <Extended Surround> 56
– Adjust the volume of input sources <Volume Trim> 57
– Selecting audio input jacks <Audio Select> 57
– Shuffle or repeat the song <Shuffle/Repeat> 57
– Connect / Disconnect Bluetooth component to this unit <Connect/Disconnect> 57
– Pairing Bluetooth component with this unit <Pairing> 57

Part names and functions

Front panel

① **MAIN ZONE ⏻ (Power)**
Switches this unit between on and standby mode.

② **HDMI Through/iPod Charge indicator**
Lights up in any of the following cases while the unit is in standby mode.
- When the Standby Through function is enabled and audio/video from an external component connected with HDMI is output to a TV during standby mode (☞p. 97).
- When an iPod/iPhone, which is placed in the Universal Dock for iPod, is charging while the unit is in standby mode (☞p. 79). This indicator also lights up when the Yamaha Wireless System for iPod is connected to this unit (☞p. 71).

③ **Front panel display**
Displays information on this unit (☞p. 11).

④ **PURE DIRECT**
Switches this unit to Pure Direct Mode (☞p. 49).

⑤ **INPUT selector**
Selects an input source from which to playback. Rotate this selector to cycle through the input sources in order.

⑥ **VOLUME**
Adjusts the volume level.

■ Opening and closing the front panel door

To use controls or jacks behind the front panel door, gently press the bottom of the door to open it. Keep the door closed when not using controls or jacks behind the front panel door.





Continues to the next page

Front panel with the cover opened

⑦ **ON SCREEN**
Turns on and off the ON SCREEN menu.

⑧ **OPTION**
Turns on and off the Option menu (☞p. 54).

⑨ **TONE/BALANCE**
Adjusts high-frequency/low-frequency output of speakers/headphones in each zone (☞p. 45, p. 119).
Adjusts the balance of the volume of the left and right channels in Zone2 (☞p. 119).

⑩ **STRAIGHT**
Changes a sound program to straight decoding mode (☞p. 48).

⑪ **PROGRAM ◅ / ▻**
Selects a sound program (☞p. 47). Press the left or right key repeatedly to cycle through sound programs.

⑫ **SCENE**
Switches the input source, the sound program, and the HDMI OUT with a single button (☞p. 46, p. 80). When this unit is in standby mode, press this key to switch on.

⑬ **MULTI ZONE**
ZONE2
Switches to enable/disable the audio and video output to Zone2 (☞p. 99, p. 117).
ZONE CONTROLS
Switches to Zone2 operation mode. This unit, or its remote control, can be used to select input sources or adjust volume for an external amplifier in another room or the built-in amplifier for speakers in another room (☞p. 119).

⑭ **INFO**
Changes the information displayed on the front panel display (☞p. 11).

⑮ **MEMORY**
Registers FM/AM stations as preset stations (☞p. 59). ♛1

⑯ **FM/AM**
Sets the FM/AM tuner band to FM or AM (☞p. 59). ♛1

⑰ **PRESET 〈 / 〉**
Selects an FM/AM preset station (☞p. 60). ♛1

⑱ **Cursor △ / ▽ / ◁ / ▷, ENTER, RETURN**

Cursor △ / ▽ / ◁ / ▷	Select menu items and change settings when menus, etc., are displayed.
ENTER	Confirms a selected item.
RETURN	Returns to the previous screen when menus are displayed, or close the menu.

⑲ **USB port**
For connecting a USB memory device or USB portable audio player (☞p. 35).

⑳ **DISPLAY**
Switches the display between the Now Playing view and the Browse view.

㉑ **YPAO MIC jack**
Connect the supplied YPAO microphone and adjust the speaker balance automatically (☞p. 37).

㉒ **PHONES jack**
For plugging headphones in. Sound effects applied during playback can also be heard through the headphones.

㉓ **VIDEO AUX jacks**
For connecting game consoles to this unit temporarily (☞p. 32).

㉔ **TUNING/CH 〈〈 / 〉〉**
Changes FM/AM tuner frequencies (☞p. 59). ♛1



♛1 : Usable when you have selected TUNER input.

Rear panel

① **PHONO jacks**
For connecting a turntable (☞p. 31).

② **DOCK jack**
For connecting an optional Universal Dock for iPod (such as YDS-12), Wireless System for iPod (YID-W10), or Bluetooth Wireless Audio Receiver (YBA-10) (☞p. 69, p. 71, p. 73).

③ **NETWORK port**
For connecting to the network (☞p. 34).

④ **HDMI OUT 1-2 jacks**
For connecting an HDMI - compatible TV to output audio/video signals (☞p. 25).

⑤ **MON.OUT/ZONE OUT jacks (S-VIDEO/VIDEO jacks)**
For connecting a TV capable of receiving video input, and outputting video signals to it (☞p. 25, p. 26).

⑥ **COMPONENT VIDEO jacks**
For connecting external components equipped component video-compatible outputs to receive video signals (☞p. 28).

⑦ **HDMI input jacks**
For connecting external components equipped with HDMI-compatible outputs to receive audio/video signals (☞p. 27).

⑧ **MONITOR OUT/ZONE OUT jacks (COMPONENT VIDEO jacks)**
For connecting TV that are compatible with component video signals, using three cables to output video signal (☞p. 25).

⑨ **REMOTE IN/OUT jacks**
For connecting an external component that supports the remote control function (☞p. 33).

⑩ **TRIGGER OUT 1-2 jack**
For connecting an external component that supports the trigger function to operate it linked with operation of this unit (☞p. 33).

⑪ **RS-232C terminal**
This is a control expansion terminal for custom installation. Consult your dealer for details.

⑫ **AV1-4 jacks**
For connecting to external components equipped with audio/video outputs to receive audio/video signals (☞p. 28).

⑬ **ANTENNA jacks**
For connecting AM and FM antennas (☞p. 36).

⑭ **AV OUT jacks**
For outputting audio/video signals received when analog inputs are selected (☞p. 34).

⑮ **AUDIO1-4 jacks**
For connecting external components equipped with audio outputs to receive audio signals (☞p. 31).

⑯ **MULTI CH INPUT jacks**
For connecting a player that supports a multi-channel output (☞p. 32).

⑰ **ZONE OUT jacks**
Outputs sound of this unit to an external amplifier set in a different room. (☞p. 117).

⑱ **PRE OUT terminals**
For connecting a subwoofer with built-in amplifier or an external power amplifier (☞p. 21, p. 22).

⑲ **SPEAKERS terminals**
For connecting the front, center, surround and surround back speakers (☞p. 19). Connect the presence speakers (☞p. 19) or the speakers for Zone2 (☞p. 18) to the EXTRA SP jacks.

⑳ **AC IN**
For connecting the supplied power cable.



Distinguishing the input and output jacks
The area around the audio/video output jacks is marked in white to prevent connection errors. Use these jacks to output audio/video signals to a TV or other external component.



Output jacks

Front panel display

① **Tuner indicator**
Light up according to the status of a received station (☞p. 59).

② **ZONE2 indicator**
Lights up when the audio and video output to Zone2 is enabled (☞p. 119).

③ **SLEEP indicator**
Blinks when the sleep timer is on (☞p. 12, p. 119).

④ **PARTY indicator**
Lights up when the party mode is active (☞p. 99).

⑤ **Multi information display**
Displays a range of information on menu items and settings.

⑥ **VOLUME indicator**
Displays the current volume level.

⑦ **HDMI indicator**
Lights up during normal HDMI communication.

IN indicator
Lights up when this unit detects the external component connected to the HDMI input jack (☞p. 27).

OUT 1/OUT 2 indicators
Indicate which HDMI OUT jack outputs audio/video signals (☞p. 25).

⑧ **ENHANCER indicator**
Lights up when the Compressed Music Enhancer is active (☞p. 49).

⑨ **CINEMA DSP indicator**
Lights up when a sound field effect that uses CINEMA DSP technology is selected.

⑩ **CINEMA DSP 3D indicator**
Lights up when CINEMA DSP 3D is activated (☞p. 48).

⑪ **Cursor indicators**
Light up if corresponding cursors on the remote control are available for operations.

⑫ **MUTE indicator**
Blinks when audio is muted.

⑬ **Speaker indicators**
Indicate speaker terminals from which signals are output.



⑭ **ADAPTIVE DRC indicator**
Lights up when the adaptive dynamic range control feature is tuned on (☞p. 56).

■ Switching information on the front panel display

The front panel can display sound programs and surround decoder names as well as the active input source.
Press 6INFO repeatedly to cycle through displayed informations. ♛2





♛1 : "SB" is displayed when using a 6.1-channel configuration only.
♛2 : During FM/AM reception, the frequency is displayed instead of the input source.

Remote control



1 Remote control signal transmitter
Transmits infrared signals.

2 MAIN/ZONE2
Switches the zone to be operated by the remote control between the Main zone and Zone2 (☞p. 119).

3 SOURCE ⏻ (SOURCE Power)
Switches an external component on and off.

4 Input selector
Select an input source on this unit from which to playback.

AV1-7	AV1-7 jacks
V-AUX	Front panel VIDEO AUX jacks
AUDIO1-4	AUDIO1-4 jacks
USB	A USB storage device connected to the USB port.
NET	Internet radio, a USB connected to the USB port, or a PC connected to the NETWORK port.
MULTI	MULTI CH INPUT jacks
DOCK	A Universal Dock for iPod, Wireless System for iPod, or Bluetooth Wireless Audio Receiver connected to the DOCK jack.
TUNER	FM/AM tuner
PHONO	PHONO jacks

5 Radio control keys
Operates the FM/AM tuner. These keys are used when using the tuner input.

FM	Sets the FM/AM tuner band to FM.
AM	Sets the FM/AM tuner band to AM.
MEMORY	Presets radio stations.
PRESET ∧ / ∨	Selects a preset stations when the FM/AM.
TUNING ⩓ / ⩔	Changes tuning frequencies.

6 INFO
Cycles the information displayed on the front panel display (the name of the currently selected input source, the sound program, the surround decoder, the FM/AM tuner frequency, etc.).

7 SLEEP
Switches this unit to standby mode automatically after a specified period of time has elapsed (sleep timer). Press this key repeatedly to set the time for the sleep timer function.

The SLEEP indicator lights up when the sleep timer is on.

8 PARTY
Switches the party mode on and off (☞p. 119).

9 SCENE
Switch the input source and the sound program with a single button (☞p. 46). When this unit is in standby mode, press this key to switch on.

10 ON SCREEN
Turns on and off the ON SCREEN menu.

■ Installing batteries in the remote control

When inserting batteries in the remote control, remove the battery compartment cover from the reverse side of the remote control, and insert four AAA batteries into the battery compartment so that they match with the polarity markings (+ and -).



Replace the batteries with new ones if the remote control can only be operated within a narrow range.

NOTE

If there are remote control codes for external components registered to the remote control, removing the batteries for more than 2 minutes, or leaving exhausted batteries in the remote control, may clear the remote control codes. If this should occur, replace the batteries with new ones, and set the remote control codes.

Continues to the next page

Remote control (sequel)



11 **Cursor △ / ▽ / ◁ / ▷, ENTER, RETURN**

Cursor △ / ▽ / ◁ / ▷	Select menu items and change settings when menus, etc, are displayed.
ENTER	Confirms a selected item.
RETURN	Returns to the previous screen when menus are displayed, or close the menu.
DISPLAY	Switches the display between the Now Playing view and the Browse view.

12 **External component operation keys**
Operate recording, playback, and menu displays etc. for external components (☞p. 106). 1

13 **Numeric keys**
Enter numbers.

14 **TV control keys**
Operate a monitor such as a TV.

15 **CODE SET**
Sets remote control codes for external component operations (☞p. 107).

16 **SOURCE/RECEIVER**
Switches remote control key function to operate this unit or an external component (☞p. 106). Operate an external component when this key glows green, or this unit when this key glows orange.

17 **RECEIVER ⏻ (RECEIVER Power)**
Switches this unit between on and standby mode.

18 **HDMI OUT**
Switches the output jack connected to an HDMI compatible TV (☞p. 44).

19 **Sound selection keys**
Switch between the sound field effect (sound program) you are using and the surround decoder (☞p. 47).

20 **OPTION**
Turns on and off the Option menu (☞p. 54).

21 **VOLUME +/-**
Adjust the volume level (☞p. 44).

22 **MUTE**
Turns the mute function of the sound output on and off (☞p. 44).

1 : You can use 12 **External component operation keys** for each input source to operate registered components. Remote control codes must be registered for each input in advance if you want to operate external components (☞p. 107).

On-screen display

When a TV is connected to this unit, the supplied remote control can be used to specify and verify this unit's settings via menus and options displayed on the TV screen.



The following displays are available in the on-screen display.

ON SCREEN menu



Press 10**ON SCREEN** to display the ON SCREEN menu.

Detailed settings for this unit can be configured. Use this menu to select desired settings, change their values, or check the current status of this unit.
Refer to "SETUP" (☞p. 77) for details.

Option menu

Press 20**OPTION** to display the Option menu.

Configure the optional settings for each input source. Settings such as "Tone Control" and "Volume Trim" are applied to this unit regardless of the input source.
Refer to "Configuring settings specific to an individual input source (Option menu)" (☞p. 54) for details.

Content window

Press 4**Input selector** to display the content window.

Includes the Browse view and the Now Playing view. The Now Playing view displays the status of the source from which music is currently played back. Adjust settings for music content from the Browse view.
Refer to "Confirming and operating input sources from the content window" (☞p. 58) for details.

Connecting speakers

This unit uses acoustic field effects and sound decoders to bring you the impact of a real movie theater or concert hall. These effects will be brought to you with ideal speaker positioning and connections in your listening environment.

Speaker channels and functions

Front left and right speakers

The front speakers are used for the front channel sounds (stereo sound) and effect sounds.



E.g.

Front speaker layout:
Place these speakers at an equal distance from the ideal listening position in the front of the room. When using a projector screen, the appropriate top positions of the speakers are about 1/4 of the screen from the bottom.

Center speaker

The center speaker is for the center channel sounds (dialog, vocals, etc.).

E.g.

Center speaker layout:
Place it halfway between the left and right front speakers. When using a TV, place the speaker just above or just under the center of the TV with the front surfaces of the TV and the speaker aligned. When using a screen, place it just under the center of the screen.

Surround left and right speakers

The surround speakers are for effect and vocal sounds when playing back a 5.1-channel source or higher. If used with no surround back speaker when playing back a 6.1-channel source or higher (including a surround back channel), the sound of the surround back channel is distributed between the left and right surround speakers.



E.g.

Surround speaker layout:
Place the speakers at the rear of the room on the left and right sides facing the listening position. They should be placed between 60 degrees and 80 degrees from the listening position and with the speaker tops at a height of 1.5 – 1.8 m from the floor.

Presence left and right speakers

The presence speakers are used for front effect sounds. When used in combination with the sound programs (☞p. 50), a sound with a richer and more spatial presence is possible.



E.g.

Presence speaker layout:
Place the left and right presence speakers 0.5 – 1 m to the outside of the left and right front speakers respectively. The tops of the presence speakers should be 1.8 m above the floor.

Surround back left and right speakers

The surround back speakers are for rear effect sounds when playing back a 6.1-channel source or higher. If used with only one surround back speaker when playing back a 7.1-channel source or higher, the sound of the left and right surround back channel is mixed and output from a single speaker.



E.g.

Surround back speaker layout:
When used with 7.1ch sound, arrange the left and right speakers towards the listening position, to the rear of the listening position. Arrange the left and right speakers at least 30 cm apart. The same separation as with the front left and right speakers is optimum. When used with 6.1ch sound, arrange these to the rear of the listening position.

Subwoofer

The subwoofer speaker is used for bass sounds and low-frequency effect (LFE) sounds included in Dolby Digital and DTS. Use a subwoofer that is equipped with built-in amplifier.

E.g.

Subwoofer speaker layout:
Place it to the outside of the front left and right speakers facing slightly inward to reduce echoes from the wall. You can use one or two subwoofers.

Speaker layout

In addition to the 7.1-channel speaker layout, a variety of speaker configurations can be specified with presence speaker connection, bi-amp connection or the Zone2 function.
And, this unit is equipped with “Power Amp Assign” function which can easily apply the appropriate speaker setting to this unit according to your speaker configuration.

Connection of speakers

Connect the speakers to the appropriate jacks shown in the table for each speaker layout. Refer to “Connecting speakers and subwoofers” (☞p. 19) for details on connecting speakers.
You can also use two subwoofers by connecting them to both SUBWOOFER1 and SUBWOOFER2 jacks. In this case, monaural sound of subwoofer channel is output from both speakers.

Assigning a speaker configuration

A speaker configuration must be assigned to this unit to activate the speakers. Use the Power Amp Assign function to apply the appropriate settings shown in the table for each speaker layout. Refer to “Power Amp Assign” (☞p. 90) for details on setting.

Enjoying the 7.1 channel audio source

■ 7.1-channel speaker layout (7 speakers + subwoofer)



Audio from a 7.1-channel audio source can be played back with no degradation with this speaker configuration.

■ Connections of speakers

FRONT jacks	Front L/R speakers	**SURROUND BACK jacks**	Surround back L/R speakers
CENTER jack	Center speaker	**SUBWOOFER (PRE OUT) jack**	Subwoofer
SURROUND jacks	Surround L/R speakers		

■ Assigning a speaker configuration

Power Amp Assign	7ch Normal **(Default)**

1 : The sound of surround back channel can also be output from a single surround back speaker. When only one surround back speaker is used, connect it to the SURROUND BACK L (SINGLE) jack and place it directly behind the listening position.

Adding the presence speakers for a richer sound field effect

■ Presence speaker layout (7 speakers + subwoofer + presence speakers)



This unit automatically selects the presence speakers or surround back speakers to output sounds according to the selected sound program.
When the sound program is changed, the speakers that output the sound are switched between the presence speakers and surround back speakers automatically. 2

■ Connections of speakers

FRONT jacks	Front L/R speakers	**SURROUND BACK jacks**	Surround back L/R speakers
CENTER jack	Center speaker	**SUBWOOFER (PRE OUT) jack**	Subwoofer
SURROUND jacks	Surround L/R speakers	**EXTRA SP jacks**	Presence L/R speakers

■ Assigning a speaker configuration

Power Amp Assign	7ch Normal **(Default)**

Enjoying the audio source without surround back speakers

■ 5.1-channel speaker layout (5 speakers + subwoofer)



This unit can mix 7.1-channel audio source down to 5.1-channel sound. This enables 7.1-channel sound without surround back speakers.

■ Connections of speakers

FRONT jacks	Front L/R speakers	**SURROUND jacks**	Surround L/R speakers
CENTER jack	Center speaker	**SUBWOOFER (PRE OUT) jack**	Subwoofer

■ Assigning a speaker configuration

Power Amp Assign	7ch Normal **(Default)**

1 : The sound of surround back channel can also be output from a single surround back speaker. When only one surround back speaker is used, connect it to the SURROUND BACK L (SINGLE) jack and place it directly behind the listening position.
2 : Sound cannot be output from the surround back speakers when it is output from the speakers connected to the EXTRA SP jacks.

Using the front speakers that support bi-amp connections for a high quality sound

■ 5.1-channel speaker layout (Front speakers (Bi-amp) + 3 speakers)



Using the front speakers that support bi-amp connections reproduces a high quality sound.

■ Connections of speakers

FRONT jacks	Front L/R speakers (bi-amp)	**SURROUND BACK jacks**	Front L/R speakers (bi-amp)
CENTER jack	Center speaker	**SUBWOOFER (PRE OUT) jack**	Subwoofer
SURROUND jacks	Surround L/R speakers		

■ Assigning a speaker configuration

Power Amp Assign	5ch BI-AMP

Using speakers in two rooms (Zone2 function)

■ 7.1-channel speaker layout + Zone2 (7 speakers (in main zone) + subwoofer (in main zone) + front speakers (in secondary zone))



In addition to the main room, speakers in another room can also be controlled.
When the built-in amplifier assigned to speakers in another room is turned on, sound output automatically switches from the surround back speakers to the speakers in the other room. ♛2

■ Connections of speakers

FRONT jacks	Front L/R speakers	**SURROUND BACK jacks**	Surround back L/R speakers
CENTER jack	Center speaker	**SUBWOOFER (PRE OUT) jack**	Subwoofer
SURROUND jacks	Surround L/R speakers	**EXTRA SP jacks**	Zone2 speakers

■ Assigning a speaker configuration

Power Amp Assign	7ch + 1ZONE

♛1 : The sound of surround back channel can also be output from a single surround back speaker. When only one surround back speaker is used, connect it to the SURROUND BACK L (SINGLE) jack and place it directly behind the listening position.
♛2 : Sound cannot be output from the surround back speakers when it is output from the speakers connected to the EXTRA SP jacks.

Connecting speakers and subwoofers

Connect your speakers to their respective terminals on the rear panel.

CAUTION

- Remove the power cable of this unit from the power outlet before connecting the speakers.
- Generally speaker cables consist of two parallel insulated cables. One of these cables is a different color, or has a line running along it, to indicate different polarity. Insert the different colored (or lined) cable into the "+" (positive, red) terminal on this unit and the speakers, and the other cable into the "–" (negative, black) terminal.
- Be careful that the core of the speaker cable does not touch anything or come into contact with the metal areas of this unit. This may damage this unit or the speakers. If the speaker cables short circuit, "CHECK SP WIRES!" will appear on the front panel display when this unit is switched on.

■ Front/Center/Surround/Surround back speaker and Subwoofer connection

When connecting only one surround back speaker, connect the speaker to the SURROUND BACK L (SINGLE) jacks.



■ Presence speaker connection

When using the presence speakers, connect the speakers to the EXTRA SP jacks as shown in the diagram below.



The presence speakers (PL/PR) that output front effect sounds can be connected to this unit. With the sound programs (☞p. 50), sound with a richer and more spatial presence can be created.



Connection of presence speakers is recommended to take full advantage of the effects of CINEMA DSP sound programs.

Continues to the next page

■ Bi-amp connection

This unit can be connected to speakers that support bi-amp connections. When connecting speakers, connect the FRONT jacks and the SURROUND BACK/BI-AMP jacks as in the diagram below. Configure the bi-amp settings to activate connections.



NOTE

Before making bi-amplification connections, remove any brackets or cables that connect a woofer with a tweeter. Refer to the instruction manuals of speakers for details. When not making bi-amplification connections, make sure that the brackets or cables are connected before connecting the speaker cables.

■ Multi-zone audio system using the internal amplifier of this unit

Connect the speakers in the second zone to the EXTRA SP jacks as in the diagram below.



CAUTION

The EXTRA SP jacks of this unit should not be connected to a Passive Loudspeaker Selector Box or more than one loudspeaker per channel.

Connection to a Passive Loudspeaker Selector Box or multiple speakers per channel could create an abnormally low impedance load resulting in amplifier damage. See this owner's manual for correct usage.

Compliance with minimum speaker impedance information for all channels must be maintained at all times. This information is found on the back panel of this unit.

Changing speaker impedance

This unit is configured for 8 Ω speakers at factory setting. When connecting to 6 Ω speakers, carry out the following procedure to switch to 6 Ω. When this unit is configured for 6 Ω speakers, 4 Ω speakers can also be used as the front speakers.

1 Switch this unit to the standby mode.

2 Press MAIN ZONE ⏻ while pressing and holding STRAIGHT on the front panel.

Release the keys when "ADVANCED SETUP" is displayed on the front panel display.

After approximately a few seconds, the top menu item is displayed. 1



Continues to the next page

1 : Refer to the "Extended functionality that can be configured as needed (Advanced Setup menu)" (☞p. 109) for details on the Advanced Setup menu.

3 **Check that “SPEAKER IMP.” is displayed on the front panel.**

4 **Press STRAIGHT repeatedly to select a “6ΩMIN.”**

5 **Switch this unit to the standby mode, and then switch it on again.**

The power turns on, when the settings you made has been configured.

Connecting speakers

This type of jack can connect to the following speakers or connection.

- Front L/R speakers
- Center speaker
- Surround L/R speakers
- Surround back L/R speakers
- Presence L/R speakers
- Zone2 speakers
- Bi-amp connection (Front L/R speakers)



1 **Remove approximately 10 mm of insulation from the ends of the speaker cables, and twist the bare wires of the cables together firmly so that they will not cause short circuits.**

2 **Loosen the speaker terminals.**

3 **Insert the bare wire of the speaker cable into the gap on the side of the terminal.**

4 **Tighten the terminal.**

Connecting the subwoofers



1 **Connect the subwoofer input jack to the SUBWOOFER 1 and/or 2 jack on this unit with an audio pin cable.** 1

2 **Set the subwoofer volume as follows.**

Volume: Set to approximately half volume (or slightly less than half).

Crossover frequency (if available): Set to maximum.



Subwoofer examples

NOTE

After connection, applying this setting to this unit is required to activate all speaker connections. With using “Power Amp Assign” function, you can easily apply the speaker configuration.

Refer to “Power Amp Assign” (☞p. 90) for details on using “Power Amp Assign” function.

1 : When using the only one subwoofer, connect the subwoofer to the SUBWOOFER 1.

Advanced speaker configuration

Speaker layout utilizing an external power amplifier

More speakers can be used by connecting an external amplifier to this unit's PRE OUT jacks. The speaker layout specified using the Power Amp Assign function varies when an external amplifier is connected.

Symbols on the table

L	Front L speaker	SBL	Surround back L speaker
C	Center speaker	SBR	Surround back R speaker
R	Front R speaker		Speakers that output sound
SL	Surround L speaker	EA	External amplifier
SR	Surround R speaker		

Connections of speakers

Connect the speakers to the following jacks according to the speaker layout. Refer to "Front/Center/Surround/Surround back speaker and Subwoofer connection" for details on connecting speakers (☞p. 19). Also, refer "Connecting an external amplifier" for details on connecting an external amplifier.
You can also use two subwoofers by connecting them to both SUBWOOFER1 and SUBWOOFER2 jacks. In this case, monaural sound of subwoofer channel is output from both speakers.

Assigning a speaker configuration

A speaker configuration must be assigned to this unit to activate speakers and an external amplifier. Use the "Power Amp Assign" function to easily apply the appropriate speaker settings to this unit in accordance with speaker configuration.

Using front speakers that support bi-amp connection and surround back speakers

■ 7.1-channel speaker layout (Front speaker (Bi-amp) + 3 speakers + external surround back speakers)



Connecting surround back speakers to an external amplifier enables simultaneous use of front speakers that support bi-amp connection and surround back speakers.

■ Connections of speakers

FRONT jacks	Front L/R speakers (bi-amp)
CENTER jack	Center speaker
SURROUND jacks	Surround L/R speakers
SURROUND BACK jacks	Front L/R speakers (bi-amp)
SUR. BACK (PRE OUT) jacks	External amplifier (for surround back L/R speakers)
SUBWOOFER (PRE OUT) jack	Subwoofer

■ Assigning a speaker configuration

Power Amp Assign	5ch BI-AMP + SB

Connecting an external amplifier

The same channel signals are output from the jacks of the PRE OUT terminals as from their corresponding SPEAKERS terminals. When connecting an external power amplifier (pre-main amplifier) to enhance speaker output, connect the input terminals of the power amplifier to the PRE OUT terminals of this unit.

NOTES

- When a component is connected to the PRE OUT terminals, do not connect speakers to the SPEAKERS terminals corresponding to those PRE OUT terminals.
- When an external amplifier equipped with a volume adjustment function is connected, a sufficient volume level may not be achieved. Use of the following components is recommended.
  - An amplifier with no volume adjustment function.
  - An integrated amplifier equipped with a function that bypasses volume circuitry, such as the Yamaha A-S2000 with MAIN IN input.



① **FRONT (PRE OUT) jacks**
Front channel or front presence channel output jacks.

② **SURROUND (PRE OUT) jacks**
Surround channel output jacks.

③ **SUR. BACK (PRE OUT) jacks**
Surround back output jacks. When you only connect one external amplifier for the surround back channel, connect it to the SUR. BACK (SINGLE) jack.

④ **CENTER (PRE OUT) jack**
Center channel output jack.

Connecting external components

Jacks and cables

This unit is equipped with the following input/output jacks. Use jacks and cables appropriate for components that you are going to connect.

Audio/Video jacks

HDMI jacks

Digital video and digital sound are transmitted through a single jack.
Only use an HDMI cable.



HDMI cable



- Use a 19-pin HDMI cable with the HDMI logo.
- We recommend using a cable less than 5.0 m long to prevent signal quality degradation.
- When a TV that supports HDMI functions and Audio Return Channel function is connected, audio output from the TV can be input to this unit (☞p. 115).
- When a player and TV that support the 3D video format are connected to this unit, 3D content can be played back.
- If you connect this unit to a component that has a DVI jack, an HDMI/DVI-D cable is required.

Analog video jacks

COMPONENT VIDEO jacks

The signal is separated into three components:
luminance (Y), chrominance blue (P_B), and chrominance red (P_R).
Use component video pin cables with three plugs.



Component video pin cable



S-VIDEO jacks

To transmit S-video signals that include luminance (Y) and chrominance (C) components.
Use S-video cables.

S-video cable



VIDEO jacks

These jacks transmit conventional analog video signals.
Use video pin cables.



Video pin cable



Audio jacks

OPTICAL jacks

These jacks transmit optical digital audio signals.
Use fiber-optic cables for optical digital audio signals.



Digital audio fiber-optic cable

COAXIAL jacks

These jacks transmit coaxial digital audio signals.
Use pin cables for digital audio signals.

Digital audio pin cable



AUDIO jacks

These jacks transmit conventional analog audio signals.
Use stereo pin cables, connecting the red plug to the red R jack, and the white plug to the white L jack.



Stereo pin cable



Connecting a TV monitor

This unit is equipped with the following four types of output jack for connection to a TV. HDMI OUT 1-2, COMPONENT VIDEO, S-VIDEO or VIDEO. Select the proper connection according to the input signal format supported by your TV.



When connecting to an HDMI compatible TV

Video signal such as component video, S-video and video received by this unit is converted to HDMI and output to the TV. Just select HDMI input on the TV to view video from any external source connected to this unit. 1



When connecting to a non-HDMI compatible TV

Connect to the TV using the same type of connection that you used to connect to the external component, and change the inputs on your TV to match that of the external component you are using for playback. If the external component and TV are equipped with different types of analog video jacks, this unit will convert the component video, S-video or video signal to component video, S-video or video signal, according to the type of video input jacks used by the TV. 2, 3



1 : You can change the resolution and aspect ratio when converting to HDMI to suit your requirements (☞p. 95).
2 : Set “Analog to Analog Conversion” to “On” (☞p. 95).
3 : Analog to analog conversion is available only for 480i/576i-resolution video signal.

Connecting an HDMI video monitor

Connect the HDMI cable to one of the HDMI OUT 1-2 jacks.



- Use a 19-pin HDMI cable with the HDMI logo.
- We recommend using a cable less than 5.0 m long to prevent signal quality degradation.
- When a TV that supports the HDMI function and Audio Return Channel function is connected, audio output from the TV can be input to this unit (☞p. 115).
- When a player and TV that support the 3D video format are connected to this unit, 3D content can be played back.
- This unit is equipped with HDMI OUT 1 and 2 jacks. The active HDMI OUT jack(s) can be selected (☞p. 44). The active HDMI OUT jack(s) can be registered with the SCENE function (☞p. 80).

Connecting a component video monitor 1

Connect the component video cable to the COMPONENT VIDEO (MONITOR OUT) jacks.



Connecting a S-video monitor 1

Connect the S-video cable to the S-VIDEO (MONITOR OUT) jack.



1 : The video signal for the COMPONENT VIDEO or S-VIDEO jacks is converted and output from HDMI OUT 1-2 jacks. When connecting to a TV via the HDMI jack, you do not need to use these jacks.

Connecting a video monitor 1

Connect the video pin cable to the VIDEO (MONITOR OUT) jack.



■ Listening to TV audio

To transmit sound from the TV to this unit, connect as followings according to the TV:

When using a TV that supports the Audio Return Channel function and HDMI Control function

When your TV supports both HDMI Control (e.g., Panasonic VIERA Link) and Audio Return Channel functions, audio/video output from the unit to the TV and audio output from the TV to the unit are possible using a single HDMI cable.
The input source is switched automatically to match operations carried out on the TV, and that makes TV sound control easier to use.
For the connections and settings, refer to “Single HDMI cable input to TV audio with Audio Return Channel function” (☞p. 115).

When using a TV that supports the HDMI Control functions

When using a TV that supports HDMI Control functions (e.g., Panasonic VIERA Link), if HDMI Control functions are enabled on the unit, then input source can be switched automatically to match operations carried out on the TV.
For the connections and settings, refer to “Switching the input source on this unit automatically when listening to TV audio” (☞p. 114).

When using other TVs

To transmit sound from the TV to this unit, connect the TV’s audio output to the AUDIO1-4 jacks.

TV audio output	Connection
Optical digital audio output	Connect to the OPTICAL jack of the AUDIO1 with a fiber-optic cable.
Coaxial digital audio output	Connect to the COAXIAL jack of the AUDIO2 with a digital audio pin cable.
Analog stereo output	Connect to one of the AUDIO1-4 with a stereo pin cable.

Select the input source connected via TV’s audio output jack to enjoy the TV sound.
If the TV supports optical digital audio output, we recommend that you connect the TV audio output to the receiver’s AUDIO1 jack.
Connecting to AUDIO1 allows you to switch the input source to AUDIO1 with just a single key operation using the SCENE function (☞p. 46).



You can control your TV using the receiver’s remote control by entering the TV’s remote control code (☞p. 107).

1 : The video signal for the VIDEO jacks is converted and output from HDMI OUT 1-2 jacks. When connecting to a TV via the HDMI jack, you do not need to use these jacks.



4 Input selector
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
20 OPTION

Connecting BD/DVD players and other devices

This unit has the following input jacks. Connect them to the appropriate output jacks on the playback devices such as BD/DVD players.

Input jack	Video input	Audio input
AV1 1	HDMI/Component video/S-video/Video	HDMI/Coaxial digital/Analog (Stereo)
AV2 1	HDMI/Component video/S-video/Video	HDMI/Coaxial digital/Analog (Stereo)
AV3 1	HDMI/Component video/S-video/Video	HDMI/Optical digital/Analog (Stereo)
AV4 1	HDMI/Component video/S-video/Video	HDMI/Optical digital/Analog (Stereo)
AV5	HDMI	HDMI
AV6	HDMI	HDMI
AV7	HDMI	HDMI
AUDIO1	—	Optical digital/Analog (Stereo)
AUDIO2	—	Coaxial digital/Analog (Stereo)
AUDIO3	—	Analog (Stereo)
AUDIO4	—	Analog (Stereo)
VIDEO AUX	HDMI/S-video/Video	HDMI/Optical digital/Analog (Stereo)
PHONO	—	Analog (for turntable connection only)

Connecting BD/DVD players and other devices with HDMI cable

Connect the device with an HDMI cable to one of the HDMI jacks of the AV1-7. The HDMI IN jack of the VIDEO AUX on the front panel can also be used.
Select the input source (AV1-7 or V-AUX) that the playback device is connected to for playback.





■ Receiving video signals from the HDMI jack and audio signals from jacks other than HDMI

This unit can use the AV1-4 or AUDIO1-4 input jacks to receive audio signals from other input jacks.
For example, if a playback device cannot produce audio signals from an HDMI jack, use the following method to change the audio input.



1 Press 4Input selector to choose an input source (AV1-4, V-AUX, AUDIO1-4, or PHONO).

2 Press 20OPTION to enter the Option menu.

3 Press 11Cursor △ / ▽ to choose “Audio Select” and press 11ENTER.

4 Press 11Cursor ◁ / ▷ to choose an audio input jack and press 11ENTER.

5 Once setup is complete, press 20OPTION to close the Option menu.

1 : Coaxial digital and optical digital jacks function can be assigned to other AV jacks using “Input Assignment.” Refer to “Input Assignment” for details (☞p. 101).

Connecting BD/DVD players and other devices with component video cables

Connect the device with a component video cable to one of the AV1-4 input jacks.

Using optical digital audio output sources

Connect the playback device to the AV3 or AV4 jacks.



Using coaxial digital audio output sources

Connect the playback device to the AV1 or AV2 jacks.



Using analog stereo audio output sources

Connect the playback device to the AV1, AV2, AV3 or AV4 jacks.



Connecting BD/DVD players and other devices with S-video cables

Connect the playback device with a S-video cable to one of the AV1-4 input jacks.

Using optical digital audio output sources

Connect the playback device to the AV3 or AV4 jacks.



Using coaxial digital audio output sources

Connect the playback device to the AV1 or AV2 jacks.



Using analog stereo audio output sources

Connect the playback device to the AV1, AV2, AV3 or AV4 jacks.



Connecting BD/DVD players and other devices with video cables

Connect the playback device with a video pin cable to one of the AV1-4 input jacks.

Using optical digital audio output sources

Connect the playback device to the AV3 or AV4 jacks.



Using coaxial digital audio output sources

Connect the playback device to the AV1 or AV2 jacks.



Using analog stereo audio output sources

Connect the playback device to the AV1, AV2, AV3 or AV4 jacks.



Connecting CD players and other audio devices

Using analog stereo output sources

Connect the playback device to the AUDIO1, AUDIO2, AUDIO3 or AUDIO4 jacks.



Using optical digital output sources

Connect the playback device to the AUDIO1 jack.



Using coaxial digital output sources

Connect the playback device to the AUDIO2 jack.



We recommend connecting audio devices with a coaxial digital output to the AUDIO2 coaxial digital jack on this unit. This connection allows you to switch to the AUDIO2 just by pressing the "CD" SCENE key (☞p. 46).

Connecting a turntable

Connect the audio output of the turntable to PHONO jacks. ❦1



Connect your turntable to the GND terminal of this unit to reduce noise in the signal.

❦1 : When connecting a turntable with a low-output MC cartridge to the PHONO jacks, use an in-line boosting transformer or MC-head amplifier.

Connecting game consoles or video camcorders

Use the VIDEO AUX jacks on the front panel to temporarily connect devices such as a game console or video camcorder to the receiver.
Select the V-AUX input to use these connected devices.

When connecting an HDMI compatible device

Connect the HDMI output of the device to the HDMI IN jack of the VIDEO AUX.



When connecting an non-HDMI compatible device

Connect the video and audio outputs of the device to the VIDEO or S-VIDEO, and AUDIO or OPTICAL jacks of the VIDEO AUX.



- Be sure to turn down the volume when connecting this unit and the other devices.
- When both the HDMI connection and the analog video/audio connection are performed between the HDMI compatible device and this unit, only the HDMI signal will be input.

Connecting a multi-format player or an external decoder

This unit has 8 sets of input jacks (FRONT L/R, CENTER, SURROUND L/R, SUR. BACK and SUBWOOFER) to input multi-channel analog sound signals. If your playback component, such as a DVD player or SACD player, has multi-channel analog output capability, you can enjoy up to 7.1-channel multi-channel sound. To output multi-channel sound, connect the audio output jacks of your playback component to the MULTI CH INPUT jacks of this unit, and set the input source of this unit to "MULTI CH."



Multi-format player/External decoder (7.1-channel output)

- When you select "MULTI CH" as the input source, the digital sound field processor and tone control are automatically disabled.
- As this unit does not redirect signals input through the MULTI CH INPUT jacks to compensate for missing speakers, make appropriate settings on the multi-format player or the external decoder that suit to the speaker configuration.
- When the input source is switched to "MULTI CH," images input from a component connected to the AV1-7 or VIDEO AUX jacks can be displayed on a video monitor (☞p. 79). If your DVD player does not support multi-channel digital output, connect it to these input jacks.

Connecting a SCENE link playback-compatible device

When the components are the Yamaha products and have the capability of the transmission of the remote control signals, connect the REMOTE IN and REMOTE OUT jacks to the remote control input and output jack with the monaural analog mini cable as follows.



- When a Yamaha component that supports the SCENE link playback function is connected via the REMOTE OUT jack, playback begins automatically when the SCENE function is used (☞p. 46).
- If the component connected to the REMOTE OUT jack is not a Yamaha product, set “SCENE IR” in the Scene menu to “Off” (☞p. 81).

Using the Trigger function to link external component power

When this unit is connected to a Yamaha subwoofer that supports the system connection or the component with TRIGGER IN jack, you can turn on and off the component by using this unit.



Functions of the TRIGGER OUT jack can be specified (☞p. 102).

Connecting audio/video recording devices

This receiver can transmit selected incoming audio/video signals to external components through the AV OUT jacks. You can record these input audio and video signals to VCRs or similar devices, or send them to other TVs or external components.



HDMI audio/video signals and component video signals cannot be transmitted from these jacks.

Connecting to the network

To connect this unit to your network, plug one end of a network cable (CAT-5 or higher straight cable) into the NETWORK port of this unit, and plug the other end into one of the LAN ports on your router that supports the DHCP (Dynamic Host Configuration Protocol) server function. To enjoy Internet Radio or music files saved on PC and DLNA server such as NAS (Network Attached Storage), each device must be connected properly in the network.

- Use an STP (shielded twisted pair) cable (commercially available) to connect a network hub or router and this unit.
- If the DHCP server function on your router is disabled, you need to configure the network settings manually (☞p. 98).



Connecting a USB storage device

Connect a USB memory device or USB portable audio player to the USB port on the front panel of this unit.



USB memory device or USB portable audio player

NOTE

Be careful that the USB storage device is facing the correct way when inserted into the USB port of this unit.

Connecting the FM/AM antennas

An indoor FM antenna and an AM loop antenna are supplied with this receiver. Connect these antennas properly to their respective jacks.

Indoor FM antenna

AM loop antenna
Position the AM antenna away from the receiver. The wires of the AM antenna have no polarity.
You can connect either wire to the AM jack or the GND jack.



Connecting the AM loop antenna



Assembling the AM loop antenna



■ Improving FM reception

We recommend using an outdoor antenna. For more information, consult the nearest authorized dealer.

■ Improving AM reception

Connect this unit to an outdoor antenna with a 5 – 10 m vinyl-coated wire. Make sure the AM loop antenna is still connected.
Connecting the GND jack can reduce noise. Connect the jack to a store-bought ground bar or copper plate with a vinyl-covered wire and bury this new attachment in moist ground.
The GND jack is not to be connected to the ground socket of an electrical outlet.

Setting up the speaker parameters automatically (YPAO)

This unit is equipped with a Yamaha Parametric Room Acoustic Optimizer (YPAO) that adjusts the configuration, size, and volume balance of the speakers in order to provide an optimal sound field. Using YPAO allows you to automatically configure settings, such as adjusting speaker output and acoustic parameters to suit your listening room (the room in which this unit is placed). 💡1

Be aware of the following when using YPAO.

- The amount of time for measurement varies from about two to ten minutes according to settings.
- The test tone is output at high volume. Refrain from using this function at night when it may be a nuisance to others.
- Take care that the test tone does not frighten small children.

YPAO operations can be viewed on the front panel display or TV screen.

1 Check the following before using YPAO.

This unit

- The headphones are removed.

TV

- This unit is connected to the TV correctly.
- The power is turned on.
- The video input to which the video output from this unit has been selected.

Subwoofer

- The power is turned on.
- Volume is set to approximately half, and the cross-over frequency (if present) is set to maximum.



Subwoofer examples

Power amp assign

- "Power Amp Assign" applies the appropriate speaker settings to this unit according to speaker configuration.
  Refer to "Speaker layout" and "Speaker layout utilizing an external power amplifier" for details (☞p. 16, p. 22).

2 Place the supplied YPAO microphone at ear height in your listening position.

Face the head of the YPAO microphone upwards.

YPAO microphone



When positioning the microphone, we recommend that you use equipment that allows you to adjust the height (such as a tripod) as a microphone stand. When using a tripod, use the tripod screws to fix the microphone in place.

3 Switch this unit on.

Continues to the next page

💡1 : When you have changed the number of speakers or the locations in which they are installed, first use YPAO to adjust the speaker balance.



11 Cursor △ / ▽
11 ENTER
11 RETURN

4 Connect the YPAO microphone to the YPAO MIC jack on the front panel.



"Mic On View ON SCREEN" appears on the front panel display, and the following display appears on the front panel display or TV screen.

5 Press 11Cursor △ / ▽ to select the "Multi Position" and press 11ENTER to set the number of listening positions to measure.

To measure at the multiple listening positions (up to 8), press 11Cursor △ / ▽ to select "Yes" and press 11ENTER.

To measure at one listening position, press 11Cursor △ / ▽ to select "No" and press 11ENTER.

"Multi Position" is set to "Yes" as the initial factory settings. If not necessary, skip this step.

This completes preparation. To achieve more accurate results, take note of the following when measuring acoustics.

- It takes a few minutes to accurately measure acoustics for one position. Keep the room as quiet as possible while acoustics are measured.
- Wait in a corner of the room, or leave it entirely, while acoustics are measured to avoid creating an obstruction between the speakers and the YPAO microphone.

6 Press 11Cursor △ / ▽ repeatedly to select the "Measure" and press 11ENTER to start measurement.

Auto measurement starts in 10 seconds.

- To start the measurement immediately, press 11ENTER again.
- To cancel the automatic setup, press 11RETURN and then 11ENTER.

Display during measurement

Continues to the next page

When “Multi Position” is set to “No” in step 5

The following display appears when measurement finishes without any problems.

Go to step 8.

When “Multi Position” is set to “Yes” in step 5

The following display appears when measurement at the first position finishes without any problems.

Go to step 7.

7 Replace the optimizer microphone at your choosing position and press 11ENTER to restart the automatic measurement.

Auto measurement restarts in 10 seconds.

The following illustration shows how to place the optimizer microphone to optimize the setup of this unit for eight listening positions for example. Up to 8 listening positions can be measured. 1



Repeat step 7 until the measurement at all listening positions are made.

The following display appears when measurement at the last position finishes without any problems.

NOTE

If a problem occurs, an error message or report is displayed either during or after acoustic measurement. Refer to “When an error message is displayed during measurement” (☞p. 42), or “When a warning message is displayed after measurement” (☞p. 42) to resolve the problem and measure acoustics with YPAO again.

Continues to the next page

1 : Measure from the most frequent listening position, such as directly in front of the TV, first.

11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Result	Displays the results of automatic acoustics measurement. Refer to "Reviewing automatic setup parameters" (☞p. 41) for details.	
Save/Exit	SAVE	Applies the result to the speaker setup and finishes the automatic measurement. ♛1
	CANCEL	Returns to the previous screen.
	EXIT	Finishes the automatic measurement without applying the result to the speaker setup.

- When the warning message appears on this display, refer to "When a warning message is displayed after measurement" (☞p. 42) for details.
- Press 11RETURN to return to the previous screen.

8 Press 11Cursor △ / ▽ to select "Save/Exit" and press 11ENTER.

9 Press 11Cursor ◁ / ▷ to select "SAVE" and press 11ENTER.

10 Press 11ENTER.

Automatic setup is completed. Disconnect the YPAO microphone.

The YPAO microphone is sensitive to heat. When you have finished measuring, store the microphone out of direct sunlight, and away from locations that may experience high temperatures, such as on top of AV equipment.

♛1 : The result of the measurement is assigned to the "Setting Pattern" currently selected. Refer "Setting Pattern" (☞p. 89) for details on "Setting Pattern."

11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Reviewing automatic setup parameters

The results of automatic acoustics measurement can be reviewed once measurement is complete.

1 Press 11Cursor △ / ▽ repeatedly to select "Result" and press 11ENTER immediately after the automatic measurement.

The Result menu can be viewed only by performing the automatic measurement.

The results of acoustics measurement are displayed.



① **List of menu items**
Menu items available in the Result menu are displayed.

② **Number of measurement**
Indicates the number of measurements for multiple listening positions.

③ **Diagram**
Shows the speaker setup and sound adjustment as diagram.

2 Select the desired menu item (or enable a function) using 11Cursor △ / ▽ / ◁ / ▷ and 11ENTER.

Wiring	Displays the speakers connected to this unit and the polarity of each connected speaker. • "Normal" is displayed when the polarity of the connected speaker is normal. • "Reverse" is displayed when the polarity of the connected speaker is opposite.
Size	Displays the size of the connected speakers. • "Large" is displayed when the connected speaker has the ability to reproduce the low-frequency signals effectively. • "Small" is displayed when the connected speaker does not have the ability to reproduce the low-frequency signals effectively.
Distance	Displays the distance from the listening position to speakers. The unit for distance can be switched between "ft" (feet) and "m" (meter) by pressing 11Cursor ◁ / ▷.
Level	Displays the result of the adjustment of each connected speaker output level.
Setup Reload 1	Clears the fine-adjustment with Manual Setup and reloads the result of automatic setup. For details, refer to "Reloading automatic setup parameters."

3 Press 11RETURN to finish the Result menu.

The result of automatic setup can be fine-tuned manually by "Manual Setup." Refer to "Manual speaker setup" (☞p. 89) for details.

Reloading automatic setup parameters

If you are not satisfied with the fine-adjustment of setup parameters with Manual Setup, the result of automatic setup saved on this unit can be reloaded. Select "Setup Reload" in the Result menu.

NOTE
When automatic setup parameters are reloaded, manually configured settings are cleared. To avoid clearing manually configured settings by reloading automatic setup parameters, see "Prohibiting setting changes" (☞p. 103).

1 : This item is displayed after the fine-adjustment is performed with "Manual Setup." Use this item to return the settings to the result of automatic setup.

11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

When an error message is displayed during measurement

See “Error messages” (☞p. 43) for instructions on resolving the problem and measure acoustics again.

Check the error code displayed and use YPAO to measure acoustics again as described below.

When “E-1,” “E-2,” “E-3,” “E-4” or “E-6” is displayed:

1 **Press 11ENTER.**

2 **Press 11Cursor ▷ to select “EXIT.”**

3 **Press 11ENTER to terminate YPAO, and switch the unit to standby mode.**

4 **Check that the speakers are properly connected.**

5 **Turn on the unit and use YPAO again.**

When “E-7” or “E-8” is displayed:

1 **Press 11ENTER.**

2 **Check that the environment is suitable for accurate measurement.**

3 **Press 11Cursor ▷ to select “RETRY.”**

4 **Press 11ENTER to use YPAO again.**

When “E-5” or “E-9” is displayed:

1 **Press 11ENTER.**

2 **Check that the environment is suitable for accurate measurement.**

3 **Press 11Cursor ◁ / ▷ to select a option.**

PROCEED:
When “E-5” is displayed, measurement can proceed. However, the measurement in noisy environment may reduce the accuracy.
When “E-9” is displayed, resume the aborted step.
RETRY:
Restart measurement from the beginning.

4 **Press 11ENTER to execute the selected option.**

When “E-10” is displayed:

1 **Press 11ENTER.**

2 **Press 11Cursor ▷ to select “EXIT.”**

3 **Press 11ENTER to terminate YPAO, and switch the unit to standby mode.**

4 **Turn on the unit and use YPAO again.**

When a warning message is displayed after measurement

See “Warning messages” (☞p. 43) for instructions on resolving the problem. The speaker causing the problem can be confirmed from the TV screen display.

NOTE
Although the results of acoustics measurement can be applied when a warning message is displayed, optimal sound will not be achieved. Resolving the problem and using YPAO to measure acoustics again is recommended.

To exit YPAO with some options

1 **Use 11Cursor △ / ▽ to select “Save/Exit” and press 11ENTER.**

2 **Use 11Cursor ◁ / ▷ to select one of the following options and press 11ENTER.**

SAVE:
Exits YPAO applying the results of measurement.
CANCEL:
Returns to the previous screen (warning message screen).
EXIT:
Exits YPAO without saving the results.

Message list

NOTE
If the following messages appear, resolve the problems that have occurred and carry out the measurement process again.

■ When a warning message is displayed before measurement

Connect MIC!	The YPAO microphone is not connected.	Connect the YPAO microphone to the YPAO MIC jack on the front panel.
Unplug HP!	The headphones are connected.	Remove the headphones.
Memory Guard!	The settings of this unit are protected.	Set “Memory Guard” in the Setup menu to “Off” (☞p. 103).

■ Error messages

E-1: No Front SP	The unit was not able to find the front channel.	Check that the left and right front speakers are connected correctly.
E-2: No Sur. SP	The unit was only able to find one of side of the surround channels.	Check that the left and right surround speakers are connected correctly.
E-3: No F.PRNS SP	The unit was only able to find one of side of the presence channels.	Check that the left and right presence speakers are connected correctly.
E-4: SBR→SBL	Only one surround back speaker is connected and only the right side surround back channel sound is detected.	When only one surround back speaker is connected, connect to the left side (SINGLE) terminal.
E-5: Noisy	The noise is too loud, preventing accurate measurements from being taken.	Measure again in quiet surroundings. Turn off any devices in the room that may be emitting noise, or place them further away from the YPAO microphone. When this message is displayed, selecting “PROCEED” will allow you to continue measuring. However, we recommend resolving the problem and measuring again, as continuing measurement without doing so will not give accurate results.
E-6: Check Sur.	Even though surround left and right speakers are not connected, only the surround back speakers are connected.	When using surround back speakers, connection of the surround left/right speakers is necessary.
E-7: No MIC	The YPAO microphone has been removed.	While measuring, take care not to touch the YPAO microphone.
E-8: No Signal	The YPAO microphone could not distinguish a test tone.	Check that the YPAO microphone has been installed correctly. Check that each speaker has been connected and installed correctly. The YPAO microphone or the YPAO MIC jack may be broken. Inquire at the retailer where you purchased this unit, or the nearest Yamaha service center.
E-9: User Cancel	You have carried out an operation that has cancelled the measuring process.	Carry out the measuring process again. Do not operate this unit by, for example, adjusting the volume.
E-10: Internal Error	An internal error has occurred.	Carry out the measuring process again. Contact a Yamaha service center if “E-10” is displayed again.

■ Warning messages

W-1: Out of Phase	The speakers displayed are connected with the opposite polarity. Depending on the type of speakers you are using and the environment in which you have them installed, this message may occur even if the speakers are connected correctly.	Depending on the type of speakers, “W-1” may display even if the speakers are connected correctly. Check that the speaker polarity + (positive), and - (negative) are correct. If these are connected correctly, you can use the speakers normally even this message appears.
W-2: Over 24m/80ft	The speakers displayed are separated from the listening position by more than 24 m, and cannot be adjusted correctly.	Install the speakers with 24 m of the listening position.
W-3: Level Error	Volume level varies greatly for individual channels, and cannot be adjusted correctly.	Check that all speakers are installed in the same surroundings. Check that the speaker polarity + (positive), and - (negative) are correct. We recommend the same speakers or speakers with as similar specifications as possible. Adjust the volume of the subwoofer.

If “W-2” or “W-3” appears, you can apply measurement results, but they will not give optimal results. We recommend that you resolve the problem and carry out the measurement process again.

PLAYBACK

Basic playback procedure



4 Input selector
18 HDMI OUT
21 VOLUME +/-
22 MUTE

1 Turn on external components (TV, DVD player, etc.) connected to this unit.

2 Use the 4Input selector to select the input source.

The name of the selected input source is displayed on the front panel display. 1

When USB, NET, DOCK or TUNER is selected, the content window is displayed (☞p. 58).

3 Play the external component that you have selected as the source input, or select a radio station on the tuner.

Refer to the instruction manuals provided with the external component for details on playback.

For details on the following operations, refer to the corresponding pages:

- "FM/AM tuning" (☞p. 59)
- "Playing back tunes on the PC" (☞p. 62)
- "Playing back tunes on the USB storage devices" (☞p. 64)
- "Listening to the Internet Radio" (☞p. 66)
- "Playing back tunes from your iPod™/iPhone™" (☞p. 69)
- "Playing back tunes from Bluetooth™ components" (☞p. 73)

4 Press 21VOLUME +/- to adjust the volume.

To mute the output.

Press 22MUTE to mute the audio output.
Press 22MUTE again to unmute.

Selecting the active HDMI OUT jack

Use this function to select the HDMI OUT jack(s) used to output signal.

Press 18HDMI OUT repeatedly to select setting.

The HDMI output setting changes as follows.

OUT 1+2	Outputs the signal at both the HDMI OUT 1 and HDMI OUT 2 jacks simultaneously.
OUT 1	Outputs the signals at the HDMI OUT 1 jack.
OUT 2	Outputs the signals at the HDMI OUT 2 jack.
Off	Any signals are not output at the HDMI OUT 1 and HDMI OUT 2 jacks. Select this setting when you do not use the video monitor connected to one of the HDMI OUT jacks.

- The HDMI OUT jack that utilizes the HDMI Control function can be selected with "Control Select" (☞p. 96).
- When "HDMI Control" is set to "On," the HDMI OUT jack selected with "Control Select" is automatically enabled in addition to the HDMI OUT jack selected here by commands from the external component supporting HDMI Control connected to the jack (☞p. 96).
- The active HDMI OUT jack(s) can be registered with the SCENE function (☞p. 80).

1 : You can change the input source name displayed on the front panel display as necessary (☞p. 78).

Adjusting high/low-frequency sound (Tone control)

You can adjust the balance of the high-frequency range (Treble) and low-frequency range (Bass) of sounds output from the front left and right speakers to obtain desired tone.

The tone control of the speakers or headphones can be set separately. Set the headphone tone control with the headphones connected.

1 Press TONE/BALANCE on the front panel repeatedly to select “Treble” or “Bass.”



The current setting is displayed on the front panel display.

2 Press PROGRAM ◁ / ▷ to adjust the output level in the following frequency range.

Adjustable range	-6.0 dB to +6.0 dB
Adjustment increments	0.5 dB

The display returns to the previous display soon after you release the key.

- The tone control settings are not effective when this unit is in the Pure Direct Mode or “MULTI CH” is selected as an input source.
- If you set the balance extremely off, sounds may not match those from other channels well.
- The tone control can also be adjusted in the Option menu (☞p. 56).

Changing input settings with a single key (SCENE function)

This unit has a SCENE function that allows you switch this unit on and change input sources, the settings of Audio Select, HDMI Output, Sound Program, Pure Direct Mode, Tone Control, Adaptive DRC, and Compressed Music Enhancer with one key.

Selecting the SCENE suitable for the external component

At initial factory settings, SCENE functions are configured for the following components. Select a scene according to the component that you want to play back.

SCENE 1

Settings are configured for viewing DVD or Blu-ray Disc content. Press this key and play back content from the DVD or Blu-ray Disc player connected to the AV1 jack on this unit.

SCENE 2

The settings are configured for viewing a TV content. Press this key and turn on the TV connected to the AUDIO1 jack on this unit.

SCENE 3

The settings are configured for listening to CD content. Press this key and play back the CD player connected to the AUDIO2 jack on this unit.

SCENE 4

Settings are configured for listening to a radio station. Press this key and tune into a radio station.

SCENE 5-12

The nothing is registered on the scenes at initial factory setting. The favorite settings can be registered on the scenes and reloaded by using “Save” and “Load” in Scene menu. For details, refer to “Scene menu” (☞p. 81).

- When switching scenes, also change the external component that the remote control operates (☞p. 106).
- We recommend that selecting a scene and editing the SCENE function are performed in the Scene menu (☞p. 80).
- This unit has eight additional scene functions. After selecting one of these scenes, one of the additional eight scenes may also be selected (☞p. 81).
- Press and hold 9**SCENE** key for about three seconds to register the current setting to the scene.

Four scenes are available for different uses, such as playing movies or music. The following settings such as input sources, sound programs, and HDMI Output are provided at initial factory settings. Settings that are not checked (☐) are not enabled when a scene key is pressed. Use “Load” in the Scene menu to check settings to be enabled. Refer to “Adjusting settings registered with the SCENE function” (☞p. 81) for details.

SCENE	Input	Audio Select	HDMI Output	Sound Program	Pure Direct Mode	Tone Control	Adaptive DRC	Compressed Music Enhancer	CINEMA DSP 3D Mode	Dialogue Lift	Extended Surround	Video Processing	Master Volume	Lipsync	Delay	Setting Pattern	PEQ Select
	☑		☑	☑		☑			☐			☐	☐	☐		☐	
1 (BD/DVD Movie Viewing)	AV1	Auto	OUT 1+2	Drama	Auto	Bass: 0.0 dB Treble: 0.0 dB	On	Off	On	0	Auto	Off	-40.0 dB	Auto	0 ms	Pattern1	Natural
2 (TV Viewing)	AUDIO1	Auto	OUT 1+2	STRAIGHT	Auto	Bass: 0.0 dB Treble: 0.0 dB	On	On	On	0	Auto	Off	-40.0 dB	Auto	0 ms	Pattern1	Natural
3 (CD Music Listening)	AUDIO2	Auto	OUT 1+2	STRAIGHT	Auto	Bass: 0.0 dB Treble: 0.0 dB	Off	Off	On	0	Auto	Off	-40.0 dB	Auto	0 ms	Pattern1	Natural
4 (Radio Listening)	TUNER	---	OUT 1+2	STRAIGHT	Auto	Bass: 0.0 dB Treble: 0.0 dB	Off	On	On	0	Auto	Off	-40.0 dB	Auto	0 ms	Pattern1	Natural

19 MOVIE
19 MUSIC
19 ENHANCER
19 SUR. DECODE
19 STRAIGHT
19 PURE DIRECT

Enjoying favorite sound field effect

This unit is also equipped with a Yamaha digital sound field processing (DSP) chip. Multi-channel playback from almost any audio source can be enjoyed using a variety of sound decoders and various sound field effect programs stored on the chip. Sound field effect programs built into this unit are called “sound programs.”

Selecting sound programs and sound decoders

This unit offers sound programs in many different categories suitable for movies, music and other uses. Choose a sound program that sounds best with the source you are playing back, rather than relying on the name or explanation of the program.

- Sound programs are stored for each input source. When you change the input source, the sound program previously selected for that input source is applied again.
- When you playback DTS Express sources or audio signals with sampling frequency of higher than 96 kHz, the straight decoding mode (☞p. 48) is automatically selected.
- When you playback DTS-HD sources with CINEMA DSP, the DTS decoder is automatically selected.

Selecting sound program (☞p. 50):
MOVIE, ENTERTAINMENT category: Press 19**MOVIE** repeatedly
CLASSICAL, LIVE/CLUB, STEREO category: Press 19**MUSIC** repeatedly

Selecting stereo reproduction (☞p. 49):
Press 19**MUSIC** repeatedly

Selecting surround decoder:
Press 19**SUR. DECODE** repeatedly

Turning on Straight decoding mode (☞p. 48):
Press 19**STRAIGHT**

Turning on Pure Direct Mode (☞p. 49):
Press 19**PURE DIRECT**

Turning on Compressed Music Enhancer (☞p. 49):
Press 19**ENHANCER** repeatedly

Sound program categories

Program

- You can use the speaker indicators on the front panel display to check what speakers are currently outputting sound (☞p. 11).
- You can adjust sound field elements (sound field parameters) for each of the programs (☞p. 83).

Enjoying spatial sound with the CINEMA DSP function

Enjoying sound programs without surround speakers

This unit allows you to use virtual surround speakers to enjoy sound field surround effects, even without any surround speakers (Virtual CINEMA DSP mode). You can even enjoy surround sound presence with just a minimal configuration of the front speakers only. This unit will switch to Virtual CINEMA DSP mode automatically when Surround is set to “None” in Configuration (☞p. 91). ♛1

Enjoying sound programs with headphones

Even when headphones are connected, you can enjoy the reproduction sound field presence with ease (SILENT CINEMA mode). ♛2

♛1 : However, Virtual CINEMA DSP mode is not available under the following conditions:
- When headphones are connected to this unit.
- When a “7ch Stereo” or “2ch Stereo” sound program is selected.
- When Pure Direct Mode or straight decoding mode is selected.

♛2 : However, SILENT CINEMA mode is not available under the following conditions:
- When a “2ch Stereo” sound program is selected.
- When Pure Direct Mode or straight decoding mode is selected.

19 STRAIGHT

Enjoying more spatial sound fields (CINEMA DSP 3D mode)

CINEMA DSP 3D mode creates an intensive and accurate stereoscopic sound field in the listening room. Connection of presence speakers is recommended to take full advantage of the effects of CINEMA DSP 3D mode. Do the following steps. 1

- Connect the presence speakers to the EXTRA SP jacks and set the speakers to use (☞p. 17).
- Enable CINEMA DSP 3D in the Option menu (☞p. 54).

When a sound program runs in CINEMA DSP 3D mode, the CINEMA DSP 3D indicator on the front panel lights up.

Lights up

Enjoying sound programs without presence speakers

This unit allows you to use virtual presence speakers to create an intensive and accurate stereoscopic sound field, even when no presence speakers are connected (Virtual CINEMA DSP 3D mode). You can even enjoy surround sound presence with front speakers, center speaker, and surround speakers.
This unit automatically switches to Virtual CINEMA DSP 3D mode when presence speakers are not available. Do the following steps.

- At minimum, connect the front speakers, center speaker, and surround speakers.
- Enable the center speaker and surround speakers in "Configuration" (☞p. 90).
- Enable CINEMA DSP 3D in the Option menu (☞p. 56).

Enjoying unprocessed playback (Straight decoding mode)

Use straight decoding mode when you want to playback sound without sound field processing. You can playback as follows in straight decoding mode.

2-channel sources such as CD

Stereo sound plays through the front left and right speakers.

Multi-channel playback sources such as BD/DVD

Plays back audio from a playback source without applying sound field effects, using an appropriate decoder to split the signal into multiple channels.

Press 19STRAIGHT to enable the straight decoding mode.

To disable straight decoding mode, press 19STRAIGHT again.

Previously selected program

1 : However, CINEMA DSP 3D mode is not available under the following conditions:
- When headphones are connected to this unit.
- When a "7ch Stereo" or "2ch Stereo" sound program is selected.
- When Pure Direct Mode or straight decoding mode is selected.

19 Sound selection keys
19 MUSIC
19 ENHANCER
19 PURE DIRECT

Enjoying Hi-Fi Sound Quality (Pure Direct Mode)

Use Pure Direct Mode to enjoy the pure high fidelity sound of the selected source. When Pure Direct Mode is enabled, this unit plays back the selected source with the least circuitry. 1

Press 19PURE DIRECT to turn Pure Direct Mode on. 2

To disable Pure Direct Mode, press 19PURE DIRECT again.

Enjoying stereo playback

Select “2ch Stereo” from the sound programs when you want to playback 2-channel stereo sound (from the front speakers only), regardless of the playback source. Selecting “2ch Stereo” will playback as follows for the playback of CD and BD/DVD sources.

2-channel sources such as CD

Stereo sound plays back through the front speakers.

Multi-channel sources such as BD/DVD

Playback channels other than the front channels in the playback source are mixed with the front channels and played back through the front speakers.

Press 19MUSIC repeatedly to select “2ch Stereo.”

To disable stereo playback, press any of the 19Sound selection keys to select a sound program other than “2ch Stereo.”

Enjoying compressed music source with better sound quality (Compressed Music Enhancer)

Compressed Music Enhancer improves the sound quality of the compressed music source closer to its original depth and width. 3
This mode can be used along with any other DSP modes.

Press 19ENHANCER to turn Compressed Music Enhancer on.

Lights up Compressed Music Enhancer is active

To disable Compressed Music Enhancer, press 19ENHANCER again.

1 : The following features are disabled in Pure Direct Mode.
- sound program, tone control, PEQ Select, and Adaptive DRC
- displaying and operating the Option menu and ON SCREEN menu

2 : While Pure Direct Mode is on, the front panel display screen turns off in order to reduce noise. When turning Pure Direct Mode off, the screen returns on.

3 : However, Compressed Music Enhancer is not available in the following audio:
- Signals of which sampling rate is over 48kHz
- High Definition stream

Sound programs

CINEMA DSP in the table indicates the sound program for CINEMA DSP.

Category: CLASSICAL

This sound field is suitable when listening to music sources such as CDs.

Hall in Munich CINEMA DSP	This sound field simulates a concert hall with approximately 2500 seats in Munich, using stylish wood for the interior finishing as normal standards for European concert halls. Fine, beautiful reverberations spread richly, creating a calming atmosphere. The listener's virtual seat is at the center left of the arena.
Hall in Vienna CINEMA DSP	This is an approximately 1700-seat, middle-sized concert hall with a shoebox shape that is traditional in Vienna. Pillars and ornate carvings create extremely complex reflections from all around the audience, producing a very full, rich sound.
Chamber CINEMA DSP	This program creates a relatively wide space with a high ceiling like an audience hall in a palace. It offers pleasant reverberations that are suitable for courtly music and chamber music.

Category: LIVE/CLUB

This sound field is suitable when listening to music sources such as CDs.

Cellar Club CINEMA DSP	This program simulates a live house with a low ceiling and homey atmosphere. A realistic, live sound field features powerful sound as if the listener is in a row in front of a small stage.
The Roxy Theatre CINEMA DSP	This is the sound field of a rock music live house in Los Angeles, with approximately 460 seats. The listener's virtual seat is at the center left of the hall.
The Bottom Line CINEMA DSP	This is the sound field at stage front in The Bottom Line, a famous New York jazz club once. The floor can seat 300 people to the left and right in a sound field offering real and vibrant sound.

Category: ENTERTAINMENT

Sound programs are optimized for video sources such as TV programs and games.

Sports CINEMA DSP	This program allows the listeners to enjoy stereo sport broadcasts and studio variety programs with enriched live feeling. In sports broadcasts, the voices of the commentator and sportscaster are positioned clearly at the center while the atmosphere of the stadium expands in an optimal space to offer the listeners a feeling of presence in the stadium.
Action Game CINEMA DSP	This sound field is suitable for action games such as car racing, fighting games and FPS games. The reality of, and emphasis on, various effects makes the player feel like they are right in the middle of the action, allowing for greater concentration. Use this program in combination with Compressed Music Enhancer for a more dynamic and strong sound field.
Roleplaying Game CINEMA DSP	This sound field is suitable for role-playing and adventure games. This program adds depth to the sound field for natural and realistic reproduction of background music, special effects and dialogue from a wide variety of scenes. Use this program in combination with Compressed Music Enhancer for a more clear and spatial sound field.
Music Video CINEMA DSP	This sound field offers an image of a concert hall for live performance of pop, rock and jazz music. The listener can indulge oneself in a hot live space thanks to the presence sound field that emphasizes the vividness of vocals and solo play and the beat of rhythm instruments, and to the surround sound field that reproduces the space of a big live hall.

Category: MOVIE

Sound programs optimized for viewing video sources such as movies.

Standard CINEMA DSP	This program creates a sound field emphasizing the surround feeling without disturbing the original acoustic positioning of multi-channel audio such as Dolby Digital and DTS. It has been designed with the concept of an ideal movie theater, in which the audience is surrounded by beautiful reverberations from the left, right and rear.
Spectacle CINEMA DSP	This program represents the spectacular feeling of large-scale movie productions. It reproduces a broad theater sound field that matches cinemascope and wider-screen movies with an excellent dynamic range providing everything from very small sound effects to large, impressive sounds.
Sci-Fi CINEMA DSP	This program clearly reproduces the finely elaborated sound design of the latest science fiction and special effects-featuring movies. You can enjoy a variety of cinematographically created virtual spaces reproduced with clear separation between dialogue, sound effects and background music.
Adventure CINEMA DSP	This program is ideal for precisely reproducing the sound design of action and adventure movies. The sound field restrains reverberations but puts emphasis on reproducing a powerful space expanded widely to the left and right. The reproduced depth is also restrained relatively to ensure the separation between audio channels and the clarity of the sound.
Drama CINEMA DSP	This sound field features stable reverberations that match a wide range of movie genres from serious dramas to musicals and comedies. The reverberations are modest but offer an optimum 3D feeling, reproducing effects tones and background music softly but cubically around clear words and center positioning in a way that does not fatigue the listener even after long hours of viewing.
Mono Movie CINEMA DSP	This program is provided for reproducing monaural video sources such as a classic movie in an atmosphere of a good old movie theater. The program produces the optimum expansion and reverberation to the original audio to create a comfortable space with a certain sound depth.

Category: STEREO

Sound programs are optimized for listening to stereo sources.

2ch Stereo	Use this program to mix down multi-channel sources to 2-channels. When multi-channel signals are input, they are down mixed to 2-channels and output from the front left and right speakers.
7ch Stereo CINEMA DSP	Use this program to output sound from all speakers. When you playback multi-channel sources, this unit down-mixes the source to 2-channels, and then outputs the sound from all speakers. This program creates a larger sound field and is ideal for background music at parties, etc.

Category: SUR.DECODE (Surround decode mode)

Select this program to playback sources with selected decoders. You can playback 2-channel audio sources in up to 7-channels using a surround decoder.

DD Pro Logic	Reproduces sound using the Dolby Pro Logic decoder. This is suitable for all kinds of audio sources.
DD PLIIx Movie / DD PLII Movie	Reproduces sound using the Dolby Pro Logic IIx (or Dolby Pro Logic II) decoder. This is suitable for movies. 1
DD PLIIx Music / DD PLII Music	Reproduces sound using the Dolby Pro Logic IIx (or Dolby Pro Logic II) decoder. This is suitable for music. 1
DD PLIIx Game / DD PLII Game	Reproduces sound using the Dolby Pro Logic IIx (or Dolby Pro Logic II) decoder. This is suitable for games. 1
Neo:6 Cinema	Reproduces sound using the DTS Neo:6 decoder. This is suitable for movies.
Neo:6 Music	Reproduces sound using the DTS Neo:6 decoder. This is suitable for music.

1 : You cannot select the Dolby Pro Logic IIx decoder in the following conditions:
- When “Surround Back” is set to “None” (☞p. 91).
- When headphones are connected.



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Controlling this unit while viewing the TV screen

This unit features a sophisticated on-screen display (OSD) that helps you to control the amplifier function of this unit. With the OSD, you can view information of the signals being input and the status of this unit. Visual guidance simplifies operations for menus.

Basic operations via the TV screen display

A TV screen is required to display the ON SCREEN or Option menu. Refer to “Connecting a TV monitor” for instructions on connecting a TV screen (☞p. 24).

This section describes basic operations for configuring “Input,” “Scene” and “Sound Program” using the OSD.

Press 10ON SCREEN.

The ON SCREEN menu is displayed on the TV screen.

Selecting an input source

1 Use 11Cursor △ / ▽ to select “Input” and press 11ENTER.



Input source icons are displayed at the bottom of the TV screen.

2 Use 11Cursor ◁ / ▷ to select a Input source press 11ENTER.

The input source is selected.



- Pressing 11RETURN displays the previous menu screen. Press 11RETURN repeatedly to close the ON SCREEN menu.
- In addition to selecting an input source, detailed settings for each input source can be configured. Refer to “Configuring input sources (Input menu)” (☞p. 77) for details.

Selecting a scene

1 Use 11Cursor △ / ▽ to select “Scene” and press 11ENTER.



Scene icons are displayed at the bottom of the TV screen.

2 Use 11Cursor ◁ / ▷ to select a scene and press 11ENTER.

The scene is selected.

- Pressing 11RETURN displays the previous menu screen. Press 11RETURN repeatedly to close the ON SCREEN menu.
- Refer to “Changing input settings with a single key (SCENE function)” (☞p. 46) for details on the default scene settings.
- Detailed SCENE function settings can be edited. Refer to “Editing the SCENE function (Scene menu)” (☞p. 80) for details.

11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Selecting a sound program

1 **Use 11Cursor △ / ▽ to select “Sound Program” and press 11ENTER.**



Sound program icons are displayed at the bottom of the TV screen.

2 **Use 11Cursor ◁ / ▷ to select a sound program and press 11ENTER.**

The sound program is selected.

- Pressing 11RETURN displays the previous menu screen. Press 11RETURN repeatedly to close the ON SCREEN menu.
- Refer to “Enjoying favorite sound field effect” (☞p. 47) for various sound programs.
- You can configure the detailed settings for each sound program. Refer to “Setting sound program parameters (Sound Program menu)” (☞p. 83) for details.

NOTES

Menus can be operated and the status of this unit confirmed from the following three main displays.

- **ON SCREEN menu (☞p. 77)**
- **Option menu (☞p. 54)**
- **Content window (☞p. 58)**

These menus and status features can be used to configure more various functions in addition to selecting “Input,” “Scene” and “Sound Program.” Refer to each references for details on menus and status.

Configuring settings specific to an individual input source (Option menu)

This unit has a unique Option menu for each input source. Option menus can be used to enable features such as volume trim for compatible input sources or to display audio/video data.



4 Input selector
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN
20 OPTION

Option menu display and setup

Option menu operations are displayed on the front panel display or TV screen. TV display is used here to explain operation.

1 Use 4Input selector to select an input source to which options will be applied.

2 Press 20OPTION.

The Option menu is displayed.

Option menu

The displayed Option menu settings differ depending on the input source.
For more information, refer to the “Option menu” on the next page.

3 Use 11Cursor △ / ▽ to select the desired setting and press 11ENTER.

Parameters of the selected item are displayed.

4 Use 11Cursor ◁ / ▷ to select the desired item (or enable a function).

- Press 11RETURN to display the previous screen or close the Option menu.
- The Option menu may close automatically when some functions are enabled.

5 Press 20OPTION to close the Option menu.

The keys on the remote control may not respond for a few seconds after the Option menu is closed. Should this occur, select the input source again.

Option menu

The following items are provided for each input source. "✓" indicates the available menu for each input source. ♛1

	AV1-4	AV5-7	V-AUX	AUDIO1-4	PHONO	MULTI CH	USB	PC	NET RADIO	DOCK (iPod)	DOCK (Bluetooth)	TUNER
Tone Control	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
Adaptive DRC	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
CINEMA DSP 3D Mode	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
Dialogue Lift ♛2	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
Extended Surround	✓	✓	✓	✓ ♛3								
Volume Trim	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Audio Select	✓		✓	✓ ♛3	✓ ♛3							
Shuffle							✓	✓		✓ ♛4		
Repeat							✓	✓		✓ ♛4		
Connect											✓	
Disconnect											✓	
Pairing											✓	

♛1 : When "Tone Control," "Adaptive DRC," "CINEMA DSP 3D Mode," "Dialogue Lift," or "Extended Surround" is adjusted for an input source, the same value is applied to other input sources and "ALL" is displayed on the front panel display. When settings specific to a certain input source are selected, the input source name is displayed on the front panel display. If the name of the input source has been changed (☞p. 78), the original name of the input source is displayed.

♛2 : "Dialogue Lift" can be adjusted only when the presence speakers are available.

♛3 : This function is only available when "Coax/Opt" is assigned to this input source from "Input Assignment" in the Setup menu. Refer to "Assigning component input and output jacks" (☞p. 101) for details.

♛4 : Not available for Yamaha iPod wireless receiver.

Adjusting high/low-frequency sound

Tone Control

You can adjust the balance of the high-frequency range (Treble) and low-frequency range (Bass) of sounds output from the front left and right speakers to obtain desired tone.

Adjustable range	-6.0 dB to +6.0 dB
Adjustment increments	0.5 dB

Auto-adjusting the sound level to make even low volumes more audible

Adaptive DRC

Adjusts the dynamic range in conjunction with the volume level (from minimum to maximum). When this item is set to “On,” dialogue and sound effects are clearer. 1

On	Adjusts the dynamic range automatically.
Off **(Default)**	Does not adjust the dynamic range automatically.

When “On” is selected, the dynamic range is adjusted as follows.

If the volume level is low, the dynamic range is narrow.
If the volume level is high, the dynamic range is wide.



Enjoying more spatial sound fields

CINEMA DSP 3D Mode

When CINEMA DSP 3D is enabled, set whether to use sound programs in CINEMA DSP 3D mode (☞p. 48).

Adjusts the vertical position of dialogues

Dialogue Lift

Adjusts the vertical position of center sound such as dialogues when presence speakers are used. Increasing this parameter raises the position.



If the dialog seems to come out from a lower position than the video monitor screen, increase this parameter.



“0” (default) corresponds to the lowest position and “5” to the highest position.

- “Dialogue Lift” can be adjusted only when the presence speakers are available.
- You cannot move the dialog position lower than the default setting.

Selecting the 5.1-channel signal playback method

Extended Surround

Selects whether to reproduce 5.1-channel input signals in 6.1- or 7.1-channel when surround back speakers are used. 2

Auto **(Default)**	Automatically selects the most suitable decoder if a flag for reproducing surround back channel is present, and reproduces the signals in 6.1- or 7.1-channel.
DD PLIIx Movie	Always reproduces signals in 7.1-channel using the Dolby Pro Logic IIx Movie decoder whether or not surround back channel signals are contained. You can select this parameter when two surround back speakers are connected.
DD PLIIx Music	Always reproduces signals in 6.1- or 7.1-channel using the Dolby Pro Logic IIx Music decoder whether or not surround back channel signals are contained. You can select this parameter when one or two surround back speakers are connected.
EX/ES	Automatically selects the most suitable decoder for input signals whether or not the flag for reproducing surround back channel is present, and always reproduces signals in 6.1-channel.
Off	Always reproduces original channels whether or not the flag for reproducing surround back channel is present.

1 : “Adaptive DRC” is also effective when you use headphones.
2 : AV5-6 or AUDIO1-2 are available when “Audio Return Channel” is on, and the input source is used for “TV Audio Input.”

Adjusting volume between input sources

Volume Trim

Reduces any change in volume when switching between input sources by correcting volume differences in each input source. You can adjust this parameter for each input source.

Adjustable range	-6.0 dB to +6.0 dB
Default setting	0.0 dB
Adjustment increments	0.5 dB steps

Selecting audio input jacks

Audio Select

Select the audio input jack through which source signal is input when an input source is connected to more than one jack.

Auto **(Default)**	Automatically selects input signals in the following order: (1) HDMI (2) Digital signals (3) Analog signals
HDMI	Selects only HDMI signals. When HDMI signals are not input, no sound is output.
Coax/Opt	Selects only coaxial or optical signal. When no signal is input, no sound is output.
Analog	Selects only analog signals. If no analog signals are input, no sound is output.

Shuffle playback

Shuffle

Plays back songs or albums in random order. When the shuffle function is enabled, "" appears on the TV screen. 1

Off	The shuffle function is turned off.
On 2	The shuffle function is tuned on.
Songs 3	Plays songs back in random order.
Albums 3	Plays albums back in random order.

Repeat playback

Repeat

Plays songs or albums repeatedly. When the repeat function is enabled, "" (Single / One[iPod])" or "" (All)" appears on the TV screen. 1

Off	The repeat function is turned off.
Single / One[iPod]	Plays a song back repeatedly.
All	When all songs have completed playback, returns to the start and repeats playback.

Connect / Disconnect Bluetooth component

Connect

Disconnect

Switches communication with a Bluetooth component on and off (☞p. 73).

Pairing Bluetooth component

Pairing

Performs pairing of this unit and a Bluetooth component (☞p. 73).

1 : Not available for Yamaha Wireless System for iPod.
2 : This item is displayed only when PC or USB is selected as input source.
3 : This item is displayed only when DOCK (iPod) is selected as input source.



4 USB
4 NET
4 DOCK
4 TUNER
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN
11 DISPLAY

Confirming and operating input sources from the content window

When USB, NET, DOCK or TUNER is selected, the content window is displayed on the TV screen. Playback style for iPod, functions for FM/AM tuner, Internet Radio, PC, and USB can be set in the content window.

A TV screen is required to display the content window. Refer to “Connecting a TV monitor” for instructions on connecting a TV monitor (☞p. 24).

Displaying the content window on the TV screen

Press 4USB, 4NET, 4DOCK or 4TUNER to display the content window.

The content window consists of two main displays, the Now Playing view and the Browse view.

Below is the example of the Now Playing view for DOCK (iPod).

① **Image display**
Icon for each input source or album art is displayed.

② **Information display**
Information on the current input source is displayed.

③ **Screen button area**
Buttons to operate each input source are displayed here. These buttons vary depending on the selected input. For details on operations for each input, see the following.
– FM/AM stations (☞p. 60)
– PC servers (☞p. 63)
– USB storage (☞p. 65)
– Internet Radio (☞p. 67)
– iPod (☞p. 70)

- In the Now Playing view, press 11ENTER and use 11Cursor △ / ▽ to select a button. Then press 11ENTER to execute the selection.
- In the Browse view, press 11Cursor ▷ and use 11Cursor △ / ▽ to select a button. Then press 11ENTER to execute the selection.
- Press 11RETURN repeatedly to exit from the operation.

Switching the display between the Now Playing view and the Browse view

You can switch the display between the Now Playing view and the Browse view by the following methods.

- **Press 11DISPLAY to cycle between the Now Playing view and the Browse view.**
- **In the Now Playing view, press 11ENTER and use 11Cursor △ / ▽ to select the ☰ icon. Then press 11ENTER to switch to the Browse view.**
- **In the Browse view, press 11Cursor ▷ and use 11Cursor △ / ▽ to select the ♪ icon. Then press 11ENTER to switch to the Now Playing view.**

Browse view

☰ or 11DISPLAY ↑ ↓ ♪ or 11DISPLAY

Now Playing view

When selecting “DOCK (iPod)” as input source and playing back video content of iPod/iPhone, the screen switches as follows by pressing 11DISPLAY repeatedly.
Now Playing view → Browse view →
Video playback screen (content window disappears) → Now Playing view

FM/AM tuning

4 TUNER
5 FM
5 AM
5 MEMORY
5 TUNING ⩓ / ⩔
13 Numeric keys

When using the FM/AM tuner, adjust the direction of the FM/AM antenna connected to this unit to get the best reception.

Selecting a frequency for reception (Normal tuning)

1 **Press 4TUNER to switch to the tuner input.**

2 **Press 5FM or 5AM to select a band to receive.**

3 **Use 5TUNING ⩓ / ⩔ to set a frequency to receive.**

5TUNING ⩓
Increases the frequency. Press and hold this key for longer than a second to search automatically for a station on a higher frequency than the current one. 1

5TUNING ⩔
Decreases the frequency. Press and hold this key for longer than a second to search automatically for a station on a lower frequency than the current one. 1

Lights up when a broadcast is received from a station

Lights up when a stereo broadcast is received

■ Entering a frequency number

In normal tuning mode, use the 13Numeric keys to enter a frequency. Leave the decimal point out when entering a number. 2

For example, enter as follows to select a station on 98.50 MHz.

9 → 8 → 5 → 0

or

9 → 8 → 5 → ENT

■ Registering stations manually (Manual Preset)

Select stations manually and register them as presets individually.

1 **Tune in to the station you want to register, referring to “Selecting a frequency for reception (Normal tuning).”**

2 **Use one of the following methods to register the station you are currently receiving.**

■ Registering to a preset number to which no station is registered

Press 5MEMORY for 3 seconds or longer.
The station will be registered automatically to the lowest open preset number (or the next number after the one registered most recently).

Registered frequencies

Continues to the next page

1 : When searching for a station, release the key once the search has started.
2 : “Wrong Station!” appears on the front panel display when you enter a frequency that is out of receivable range. Make sure that the frequency entered is correct.



4 TUNER
5 MEMORY
5 PRESET ∧ / ∨
11 Cursor △ / ▽
11 ENTER
11 RETURN
13 Numeric keys

■ Designating a preset number for registration

Press 5MEMORY once, to display “Manual Preset” on the front panel display. After a small wait, the preset number that the station has been registered to will appear. 1



Press 5PRESET ∧ / ∨ to select the preset number to register the station to, and then press 5MEMORY to register.

To select a registered station, press 5PRESET ∧ / ∨ to select the preset number of the station. 2

Navigating the FM/AM tuner from the content window

The station currently received can be confirmed from the menu displayed on the TV screen. Various FM/AM tuner operations can be performed from the content window rather than controls on the front panel display. The content window is displayed when 4TUNER is pressed.
You can operate the FM/AM tuner from the Now Playing view or the Browse view.

Operating from the Now Playing view



① **Tuned indicator**
Lights up when a station is received.
② **Stereo indicator**
Lights up when a stereo broadcast is received. When “FM Mode” is set to “Mono,” the indicator does not light.
③ **Preset number**
The selected preset number is displayed.
④ **Band**
The selected band (FM or AM) is displayed.
⑤ **Frequency**
The frequency currently received is displayed.
⑥ **Frequency guide**
The frequency currently received is displayed as a cursor on the bar.
⑦ **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Now Playing view” for details.

Screen buttons on the Now Playing view

To use these buttons, first press 11ENTER. Then select the desired one with 11Cursor △ / ▽ and 11ENTER.

Manual Tuning

You can tune in to a desired FM/AM station by specifying its frequency.

FM	Switches a band to FM.
AM	Switches a band to AM.
Tuning -	Decreases the frequency.
Tuning +	Increases the frequency.
Auto -	Automatically searches for a station on a lower frequency than the current station.
Auto +	Automatically searches for a station on a higher frequency than the current station.
Direct	Selects the frequency manually.
Memory	Registers the station currently received as a preset station. Up to 40 FM/AM stations can be registered.

1 : Press 11RETURN or wait with no operation for 30 seconds to exit the Manual Preset mode.

2 : To select a station by selecting a preset number, use the 13Numeric keys to enter the preset number of the station you want to listen. When an invalid number is entered, “Wrong Num.” appears on the front panel display. Check that you have entered the correct number.

11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

Preset Select

You can call preset stations.

Preset -	Selects the previous preset number.
Preset +	Selects the next preset number.
Preset -8	Returns the previous page.
Preset +8	Goes to the next page.
Memory	Registers the station currently received as a preset station. Up to 40 FM/AM stations can be registered.
Direct	Selects a station directly by entering the preset number.

Utility

FM Mode	Selects “Stereo” or “Mono” when receiving the FM station (☞p. 59).

Scroll

Switches the scroll target.

Browse

Switches the display to the Browse view.

Operating from the Browse view

① **Preset station list**
The list of preset stations is displayed.

② **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Browse view” for details.

Screen buttons on the Browse view

To use these buttons, first press 11Cursor ▷. Then select the desired one with 11Cursor △ / ▽ and 11ENTER.

Utility

Auto Preset	Detects FM stations with a strong signal and automatically registers up to 40 FM stations, beginning with the next number after the current number (☞p. 61). AM stations cannot be registered by using “Auto Preset.”
Clear Preset	Clears registration of the preset station highlighted in the preset station list.
Clear All Preset	Clears registration of all preset stations.

1 Page Up

1 Page Down

Scrolls the list to the next or previous page.

Now Playing

Switches the display to the Now Playing view.



4 NET
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Playing back tunes on the PC

You can enjoy playback of audio files stored on PCs connected to this unit via your network. To play back audio files on your PC, you need to install Windows Media Player on the PC and configure the media sharing setting of Windows Media Player.

If you do not use a DHCP server, configure the network parameters (IP address, etc.) of this unit manually (☞p. 98).

Windows Media Player setup

1 Install Windows Media Player on your PC.

You can download the installer of Windows Media Player from the Microsoft website, or use the upgrade function of the installed Microsoft Windows Media Player.

2 Turn on your PC then allow media sharing.

Activate Windows Media Player first, enable the media sharing and then select this unit as a device to which the media is shared.

NOTES

- Some security software installed on your PC (anti-virus software, firewall software, etc.) may block the access of this unit to your PC. In such cases, configure the security software appropriately.
- You can connect this unit to up to 16 PC servers, and each server must be connected to the same subnet as this unit.

Playback of PC music contents

For a complete list of status messages that appear on the front panel display and GUI screen, see “USB and Network” (☞p. 124).

The PC music contents can be operated from the menu displayed on the TV screen.
You can operate the PC contents from the Now Playing view or the Browse view.

Operating from the Browse view



① **Repeat icon**
② **Shuffle icon**
③ **Play icon**
④ **Current directory name**
⑤ **Menu items**
⑥ **Album art / Input icon**
⑦ **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Browse view” for details.
⑧ **Current menu number / Number of all menu items**

Screen buttons on the Browse view

To use these buttons, first press 11 Cursor ▷. Then select the desired one with 11 Cursor △ / ▽ and 11 ENTER.

10 Pages Up

10 Pages Down

Goes to 10 pages forwards or backwards.

1 Page Up

1 Page Down

Scrolls the list to the next or previous page.

Now Playing

Switches the display to the Now Playing view.

1 Press 4 NET repeatedly to select “PC” as the input source.

2 Press 11 Cursor △ / ▽ to select a PC server and music file to play back.

- To select a PC server, folder or file, press 11 Cursor △ / ▽.
- To confirm the selection, press 11 ENTER.
- To return to the previous menu, press 11 RETURN.

3 Press 11 ENTER to start playback.

The Now Playing view appears during playback.



6 INFO
11 Cursor △ / ▽
11 ENTER
12 ▷
12 □
12 ▯▯
12 ▷▷|
12 |◁◁

Operating from the Now Playing view



① **Repeat icon**
② **Shuffle icon**
③ **Play icon**
④ **Album image**
⑤ **Artist name**
⑥ **Album title**
⑦ **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Now Playing view” for details.
⑧ **Song title**
⑨ **Elapsed time**

- You can switch the information displayed on the front panel display by pressing 6 INFO (☞p. 11).
- Album images are available only when the file contains image data.

Screen buttons on the Now Playing view

To use these buttons, first press 11 ENTER. Then select the desired one with 11 Cursor △ / ▽ and 11 ENTER.

Play Control

Operates the basic playback functions of PC.

▷ (Play)	Starts playback.
□ (Stop)	Stops playback.
▯▯ (Pause)	Stops playback temporarily.
|◁◁ (Skip -)	Skips to the beginning of the currently playing song. Press 11 ENTER at the beginning of the song to skip to a previous song.
▷▷| (Skip +)	Skips to the beginning of the next song.

Scroll

Switches the scroll target (artist name, album title, or song title).

Browse

Switches the display to the Browse view.

Compatibility of Digital Media Controller

A DLNA-compliant Digital Media Controller (DMC) device can also be used to control music playback. Refer to “Using a PC to control this unit over a network” (☞p. 79) for details. ♛1, ♛2

CAUTION
When DMC controls are used to adjust volume, playback volume may be unexpectedly loud. This could result in damage to this unit or the speakers. “Max Volume” can be used to specify the maximum volume level to prevent excessively loud playback (☞p. 94).

Operating basic playback functions with the remote control

Use the following remote control keys to operate (playback, stop, skip, etc.) your PC contents.

12 ▷	Play
12 □	Stop
12 ▯▯	Switches between playback and pause.
12 ▷▷|	Skip forward during playback
12 |◁◁	Skip backward during playback

Shuffle/repeat playback

Use the Option menu to apply playback shuffle and repeat settings. Refer to “Shuffle playback” (☞p. 57) and “Repeat playback” (☞p. 57) for details.

♛1 : A shortcut button cannot be registered when a DMC is used.
♛2 : Set “DMC Control” to “Disable” to automatically play back the last song played when this unit is turned on.

Playing back tunes on the USB storage devices

You can enjoy playback of WAV (PCM format only), MP3, WMA, MPEG-4 AAC and FLAC files stored on your USB memory device or USB portable player connected to the USB port on the front panel of this unit. This unit supports USB mass storage class devices (FAT 16 or FAT 32 format, except USB HDDs).



4 **USB**
11 **Cursor △ / ▽ / ◁ / ▷**
11 **ENTER**
11 **RETURN**

- You can play back only the files stored in the first partition.
- Some files may not be playable depending on models and types of USB storage devices.
- For a complete list of status messages that appear on the front panel display and GUI screen, see “USB and Network” (☞p. 124).
- This unit is compatible with sampling frequency of up to 48 kHz for the USB storage device.

Playback of the USB storage device

The USB storage device can be operated from the menu displayed on the TV screen.
You can operate the contents of USB storage device from the Now Playing view or the Browse view.

Operating from the Browse view

If you have connected the USB storage device to this unit before, playback of the music file played at the last time automatically starts.



① **Repeat icon**
② **Shuffle icon**
③ **Play icon**
④ **Current directory name**
⑤ **Menu items**
⑥ **Input icon**
⑦ **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Browse view” for details.
⑧ **Current menu number / Number of all menu items**

Screen buttons on the Browse view

To use these buttons, first press 11**Cursor ▷**. Then select the desired one with 11**Cursor △ / ▽** and 11**ENTER**.

10 Pages Up

10 Pages Down

Goes to 10 pages forwards or backwards.

1 Page Up

1 Page Down

Scrolls the list to the next or previous page.

Now Playing

Switches the display to the Now Playing view.

1 Connect your USB storage device to the USB port on the front panel (☞p. 35).

2 Rotate the INPUT selector (or press 4USB) to select “USB” as the input source.

3 Press 11Cursor △ / ▽ / ◁ / ▷ to select a music file to play back.

- To select a file or folder, press 11**Cursor △ / ▽**.
- To confirm the selection, press 11**ENTER**.
- To return to the previous menu, press 11**RETURN**.

4 Press 11ENTER to start playback.

The Now Playing view appears during playback.



6 INFO
11 Cursor △ / ▽
11 ENTER
12 ▷
12 □
12 ▷▷|
12 |◁◁

Operating from the Now Playing view



① **Repeat icon**
② **Shuffle icon**
③ **Play icon**
④ **Album image**
⑤ **Artist name**
⑥ **Album title**
⑦ **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Now Playing view” for details.
⑧ **Song title**
⑨ **Elapsed time**

- You can switch the information displayed on the front panel display by pressing 6 **INFO** (☞p. 11).
- Album images are available only when the file contains image data.

Screen buttons on the Now Playing view

To use these buttons, first press 11 **ENTER**. Then select the desired one with 11 **Cursor △ / ▽** and 11 **ENTER**.

Play Control

Operates the basic playback functions of USB.

□ (Stop)	Stops playback.
|◁◁ (Skip -)	Skips to the beginning of the currently playing song. Press 11 **ENTER** at the beginning of the song to skip to a previous song.
▷▷| (Skip +)	Skips to the beginning of the next song.

Scroll

Switches the scroll target (artist name, album title, or song title).

Browse

Switches the display to the Browse view.

Operating basic playback functions with the remote control

Use the following remote control keys to operate (playback, stop, skip, etc.) USB storage device.

12 ▷	Play
12 □	Stop
12 ▷▷|	Skip forward during playback
12 |◁◁	Skip backward during playback

Shuffle/repeat playback

Use the Option menu to apply playback shuffle and repeat settings. Refer to “Shuffle playback” (☞p. 57) and “Repeat playback” (☞p. 57) for details.



4 NET
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Listening to the Internet Radio

You can listen to Internet Radio stations using the vTuner Internet Radio station database service particularly customized for this unit, providing a database of over 2000 radio stations. Also, you can store your favorite stations with bookmarks.

- To use this feature, your network must be connected to the Internet.
- A narrowband Internet connection (i.e. 56K modem, ISDN) will not provide satisfactory results, and a broadband connection is strongly recommended (i.e. a cable modem, an xDSL modem, etc.). For detailed information, consult with your ISP.
- If you do not use a DHCP server, configure the network parameters (IP address, etc.) of this unit manually (☞p. 98).
- Some security devices (such as firewall) may block the access of this unit to Internet Radio stations. In such cases, configure the security settings appropriately.
- This service may be discontinued without notice.
- Some Internet Radio stations may not be played.

Listening to Internet Radio

For a complete list of status messages that appear on the front panel display and GUI screen, see “USB and Network” (☞p. 124).

The Internet Radio can be operated from the menu displayed on the TV screen.
You can operate the Internet Radio from the Now Playing view or the Browse view.

Operating from the Browse view



① **Play icon**
② **Current directory name**
③ **Menu items**
④ **Album art / Input icon**
⑤ **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Browse view” for details.
⑥ **Current menu number / Number of all menu items**

Screen buttons on the Browse view

To use these buttons, first press 11 Cursor ▷. Then select the desired one with 11 Cursor △ / ▽ and 11 ENTER.

Bookmark On

The selected Internet Radio station is added to the Bookmarks list in “NET RADIO.”

Bookmark Off

This item is displayed in the bookmark directory.
The selected Internet Radio station is removed from the Bookmarks list.

10 Pages Up

10 Pages Down

Goes to 10 pages forwards or backwards.

1 Page Up

1 Page Down

Scrolls the list to the next or previous page.

Now Playing

Switches the display to the Now Playing view.

1 Press 4 NET repeatedly to select “NET RADIO” as the input source.

2 Press 11 Cursor △ / ▽ to select an item to play back.

- To select an item, press 11 Cursor △ / ▽.
- To confirm the selection, press 11 ENTER.
- To return to the previous menu, press 11 RETURN.

3 Press 11 ENTER to start playback.

The Now Playing view appears during playback.



6 INFO
11 Cursor △ / ▽
11 ENTER
12 □
12 ▷

Operating from the Now Playing view



① **Play icon**
② **Album image**
③ **Elapsed time**
④ **Current station name**
⑤ **Screen button area**
Buttons for available operations are displayed. See "Screen buttons on the Now Playing view" for details.

You can switch the information displayed on the front panel display by pressing 6**INFO** (☞p. 11).

Screen buttons on the Now Playing view

To use these buttons, first press 11**ENTER**. Then select the desired one with 11**Cursor △ / ▽** and 11**ENTER**.

Bookmark On

The station currently being played back is added to the Bookmarks list in "NET RADIO."

Play Control

The following operation is available.

□ (Stop)	Stops playback.

Browse

Switches the display to the Browse view.

Operating basic playback functions with the remote control

Use the following remote control keys to operate (playback, stop) the Internet Radio.

12 ▷	Play
12 □	Stop

You can also register your favorite Internet Radio stations on this unit by accessing the website with the web browser on your PC. To use this feature, you need the vTuner ID of this unit and your e-mail address to create your personal account. For details, refer to the help information on the website.
URL: http://yradio.vtuner.com/

NOTE

To clear the personal account such as vTuner ID or e-mail address, perform "NETWORK" of "INITIALIZE" in the Advanced Setup menu (☞p. 111).

Using shortcut function



5 MEMORY
5 PRESET ∧ / ∨
11 RETURN
13 Numeric keys

Use this feature to access the desired music sources (WAV, MP3 and WMA files on the connected PC or USB storage devices and Internet Radio Stations) directly. You can preset up to 40 items for above input sources.

■ Assigning the items to the preset number

1 Select a desired content you want to assign to a preset number, and then play back the content.

2 Press 5MEMORY.

This unit automatically selects an empty preset number and the following display appears.

Preset number (Blinks)

- To automatically assign the selected content to an empty preset number, press and hold 5MEMORY for at least 2 seconds with step 2. In this case, the following steps are unnecessary.
- To cancel the preset, press 11RETURN.
- When you do not complete each of the following steps within 30 seconds, the memory preset mode is automatically canceled. In this case, start over from step 2.

3 Press 5PRESET ∧ / ∨ or 13Numeric keys to select the preset number that you want to assign.

Valid numbers as the preset number are “01” to “40.”

4 Press 5MEMORY.

The following display appears on the front panel display and the preset content is set.

■ Selecting the item assigned to the preset number

Press 5PRESET ∧ / ∨ to select the preset number to which the desired item is assigned to select the item as the input source.

This unit starts the playback of the source assigned to the selected numeric button.

NOTES

- “xx:Empty” appears on the front panel display when you select the preset number to which no items are assigned.
- This unit does not recall the correct item assigned to the selected preset number in the following cases:
  - the connected USB device is incorrect.
  - the PC which stores the selected item is turned off or disconnected from the network.
  - the selected Internet Radio station is temporary unavailable or out of service.
  - the directory of the selected item has been changed.

This unit stores the relative position of the preset items in a directory or playlist, and does not recall the correct item by using 13Numeric keys if you add or delete music files to or from the same directory or playlist as the preset items. In such cases, preset the desired item to the preset numbers again.
We recommend the following methods:

USB storage devices

Create several directories containing the desired content in a directory beside the directory containing all music files, and then assign the top item of each directory to a preset number. To change the content assigned to preset numbers, replace the content in the directory to new content without deleting the directory.

PC server

Create eight playlists containing the desired content, and then assign the top item of each playlist to a preset number. To change the content assigned to preset numbers, replace the content registered with a playlist with new content without deleting the playlist.

Playing back tunes from your iPod™/iPhone™

Once you have connected a Universal Dock for iPod (such as the YDS-12, sold separately) to this unit, you can enjoy playback of your iPod/iPhone using the remote control supplied with this unit. When playing back from an iPod/iPhone, you can also use the compressed music enhancer sound programs to give compressed audio formats such as MP3 a sharper, more dynamic sound (☞p. 49). A Yamaha Wireless System for iPod (YID-W10, sold separately) can also be connected to this unit to play back iPod/iPhone with wireless connection.

4 DOCK
6 INFO

- **When playing back iPod/iPhone with wired connection**
  Refer to “Connecting the Universal Dock for iPod.”
- **When playing back iPod/iPhone with wireless connection**
  Refer to “Playing iPod™/iPhone™ with wireless connection” (☞p. 71).

Connecting the Universal Dock for iPod

Use the dedicated cable to connect the dock to the DOCK jack on the rear panel of this unit. Refer to the operating instructions of the Universal Dock for iPod for information on how to connect your iPod/iPhone.

- iPod touch, iPod (4th Gen/5th Gen/Classic), iPod nano, iPod mini, iPhone, iPhone 3G, and iPhone 3GS are supported (As of March 2010).
- When connecting iPhone, iPhone 3G and iPhone 3GS, use a YDS-12.
- Some features may not be compatible depending on the model or the software version of your iPod/iPhone.
- Some functions may not be available for some Universal Dock for iPod models. This explanation focuses on the YDS-12.

CAUTION
To prevent accidents, switch this unit to standby mode before connecting the Universal Dock for iPod.

Switch this unit on and place your iPod/iPhone in the dock. The unit is now ready for playback.



Locate the wireless dock at the distance as far as from the unit.

When this unit is in standby mode, iPod/iPhone can be charged automatically (☞p. 79).

Controlling an iPod™/iPhone™

After setting your iPod/iPhone in your dock, just press 4 DOCK to switch to DOCK input to play your iPod/iPhone.
The iPod/iPhone can be operated in the following two ways.

Menu browse control:
Plays the iPod/iPhone while viewing the menu displayed on the TV. Refer to “Playing iPod™/iPhone™ from the menu screen (Menu browse control)” (☞p. 70).

Simple remote control:
Plays audio and video through this unit while viewing the menu displayed on the iPod/iPhone screen. Refer to “Operating basic playback functions via the remote control (Simple remote control)” (☞p. 71).

- Song information (artist, album, song) is displayed on the front panel. Press 6 INFO repeatedly to display subsequent/previous information when displaying Now Playing view in Menu browse control.
- The Yamaha logo is displayed on the iPod screen when iPod stationed in the Universal Dock for iPod (does not apply to the iPod touch or iPhone). However, the Yamaha logo is not displayed in Simple remote control.
- Manual control of the iPod/iPhone is not possible while the iPod stationed in the Universal Dock for iPod and Menu browse control is displayed.



4 DOCK
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

Playing iPod™/iPhone™ from the menu screen (Menu browse control)

The iPod/iPhone can be operated from the menu displayed on the TV screen.
You can operate the iPod/iPhone from the Now Playing view or the Browse view.

Operating from the Browse view



① **Repeat icon**
② **Shuffle icon**
③ **Play icon**
④ **Current directory name**
⑤ **Menu items**
⑥ **Input icon**
⑦ **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Browse view” for details.
⑧ **Current menu number / Number of all menu items**

Screen buttons on the Browse view

To use these buttons, first press 11Cursor ▷. Then select the desired one with 11Cursor △ / ▽ and 11ENTER.

10 Pages Up

10 Pages Down

Goes to 10 pages forwards or backwards.

1 Page Up

1 Page Down

Scrolls the list to the next or previous page.

Now Playing

Switches the display to the Now Playing view.

Close

Returns to the video playback, turning off the menu display.

1 Press 4DOCK to switch to the DOCK input.

2 Press 11Cursor △ / ▽ to select the content (music or video) that you want to play, and press 11ENTER. 1

3 Press 11Cursor △ / ▽ to select iPod/iPhone menu items, and press 11ENTER to play.

The Now Playing view appears during playback. 2

Operating from the Now Playing view



① **Repeat icon**
② **Shuffle icon**
③ **Play icon**
④ **Album image**
⑤ **Artist name**
⑥ **Album title**
⑦ **Screen button area**
Buttons for available operations are displayed. See “Screen buttons on the Now Playing view” for details.
⑧ **Song title**
⑨ **Remaining time**
⑩ **Progress bar**
⑪ **Elapsed time**

1 : Videos will not be displayed when your iPod or Universal Dock for iPod do not support the browser function for browsing video files.
2 : When selecting the video content, the following display is not displayed.



4 DOCK
11 Cursor △ / ▽
11 ENTER
11 RETURN
12 REC
12 □
12 ▯▯
12 ▷
12 ◁◁
12 ▷▷
12 |◁◁
12 ▷▷|

Screen buttons on the Now Playing view

To use these buttons, first press 11ENTER. Then select the desired one with 11Cursor △ / ▽ and 11ENTER.

Play Control

Operates the basic playback functions of iPod/iPhone.

▷ (Play)	Starts playback.
□ (Stop)	Stops playback.
▯▯ (Pause)	Stops playback temporarily.
|◁◁ (Skip -)	Skips to the beginning of the currently playing song. Press 11ENTER at the beginning of the song to skip to a previous song.
▷▷| (Skip +)	Skips to the beginning of the next song.
◁◁ (Scan -)	Searches backwards.
▷▷ (Scan +)	Searches forwards.

Scroll

Switches the scroll target (artist name, album title, or song title).

Browse

Switches the display to the Browse view.

Close

Returns to the video playback, turning off the menu display.

Operating basic playback functions via the remote control (Simple remote control)

Use the following remote control keys to operate (playback, stop, skip, etc.) your iPod/iPhone.
Press 12REC to enable the Simple remote control.
Press 12REC again to return to the Menu browse control.

4DOCK	Switches to the DOCK (iPod) input.
11Cursor △ / ▽	Move the cursor up and down to different fields.
11RETURN	Returns to the previous menu.
11ENTER	Confirms the selected menu.
12 ◁◁	Searches backwards while held down.
12 ▷▷	Searches forwards while held down.
12 |◁◁	Skips to the beginning of the currently playing song. Pressing repeatedly skips one song backwards with each press.
12 ▷▷|	Skips to the beginning of the next song.
12 □	Stops playback.
12 ▯▯	Switches between playback and pause.
12 ▷	Switches between playback and pause.
12REC	Switches the control method between the Menu browse control and Simple remote control.

Playing iPod™/iPhone™ with wireless connection

A Wireless System for iPod (YID-W10, sold separately) can be connected to this unit to play back iPod/iPhone with wireless connection. The iPod/iPhone can be used as the remote control. 1

Connecting the Wireless System for iPod and playing back iPod/iPhone

Use the dedicated cable to connect the receiver of the Wireless System for iPod to the DOCK jack on the rear panel of this unit. Refer to the operating instructions of the YID-W10 for more information.

CAUTION
To prevent accidents, unplug the power cable of this unit before connecting the receiver of the Wireless System for iPod.

Continues to the next page

1 : Video signals cannot be transmitted wirelessly.

4 DOCK

Place the iPod/iPhone in the wireless transmitter. Setup is complete.



When this unit is in standby mode, iPod/iPhone can be charged automatically, if “Standby Charge” is set to “Auto” (☞p. 79) or “Power & Input” of “iPod Interlock” is set to “On” (☞p. 79).

Use iPod/iPhone to start playback.



- This unit, which is placed in the main zone, functions as follows when iPod/iPhone controls are used to start playback.
  - The input source switches to DOCK (iPod) when this unit is turned on.
  - When this unit is in standby mode when iPod/iPhone playback starts, this unit turns on and the input source switches to DOCK (iPod). 1
- This unit automatically enters standby mode when the following operations are performed.
  - iPod/iPhone is removed from the YID-W10
  - iPod/iPhone is not operated for a while after playback is stopped

- Pressing 4 DOCK also switches the input source to DOCK (iPod).
- When a menu is operated, this function is not activated.
- When “iPod Interlock” → “Power & Input” in the Input menu is set to “Off,” the power and the input source do not switch automatically (☞p. 79).

- Adjusting volume control on the iPod/iPhone also adjusts the volume (max 0.0 dB) of this unit.

- When “iPod Interlock” → “Volume” in the Input menu is set to “Off,” the volume of this unit is not adjusted when iPod/iPhone volume controls are adjusted (☞p. 79).
- This unit may restrict the volume level to prevent excessively loud play back. In such a case, gradually increase the volume level.

CAUTION

When iPod/iPhone controls are used to adjust volume, playback volume may be unexpectedly loud. This could result in damage to this unit or the speakers. If the volume suddenly increases during playback, immediately remove the iPod/iPhone from the Wireless System for iPod. “Max Volume” can be used to specify the maximum volume level to prevent excessively loud playback (☞p. 94).

1 : This function is also activated when sound of application is reproduced or ringtone is received.

Playing back tunes from Bluetooth™ components

You can connect a Yamaha Bluetooth Wireless Audio Receiver (such as the YBA-10, sold separately) to this unit and enjoy wireless playback from Bluetooth-compatible portable music players. 1

NOTE

When playing back from a Bluetooth component for the first time, you must first pair the devices (register the Bluetooth components). When establishing a wireless connection you must carry out pairing on both this unit and on the Bluetooth component.



4 DOCK
5 MEMORY
11 Cursor △ / ▽
11 ENTER
11 RETURN
20 OPTION

Connecting a Yamaha Bluetooth Wireless Audio Receiver

Use the dedicated cable to connect the dock to the DOCK jack on the rear panel of this unit.
The Bluetooth Wireless Audio Receiver connection will be complete when this unit is turned on.



CAUTION

To prevent accidents, switch this unit to standby mode before connecting a Bluetooth Wireless Audio Receiver.

Pairing Bluetooth™ components

Be sure to carry out pairing when connecting a Bluetooth component for the first time, or when settings have been deleted. Refer to the operating instructions of your Bluetooth component as necessary when carrying out pairing.

The Yamaha Bluetooth Wireless Audio Receiver can be paired with up to eight Bluetooth components. When the ninth device is paired, the pairing settings for the device which has not been used for the longest period of time will be deleted.

1 **Press 4DOCK to switch to the DOCK input.**

2 **Turn on the Bluetooth component you want to pair with and set it to pairing mode.**

3 **Press 20OPTION to display the Option menu and use 11Cursor △ / ▽ to select “Pairing.”**

4 **Press 11ENTER to start pairing.**

- To cancel pairing, press 11RETURN.
- You can also press and hold 5MEMORY on the front panel to begin pairing.

5 **Make sure the Bluetooth component recognizes the Bluetooth Wireless Audio Receiver.**

When the device is recognized, it will appear in the Bluetooth component list, for example as “YBA-10 YAMAHA.”

6 **Select the Bluetooth Wireless Audio Receiver from the Bluetooth component list, and enter a pass key “0000” into the Bluetooth component.** 2

When pairing occurs correctly

1 : This unit supports A2DP (Advanced Audio Distribution Profile) of the Bluetooth profile.
2 : Depending on Bluetooth components, wireless connection is carried out right after the pairing. In this case, “BT connected” is displayed instead of “Completed.”



4 DOCK
11 Cursor △ / ▽
11 ENTER
20 OPTION

Using Bluetooth™ components

When pairing is complete, perform the following procedure to achieve a wireless connection between this unit and the Bluetooth component. When the wireless connection is complete, Bluetooth components can be played back.

> Depending on Bluetooth components, a wireless connection is established automatically or by operating the Bluetooth components. In that case, it is not necessary to carry out the following procedure.

1 **Press 4DOCK to switch to the DOCK input.**

2 **Press 20OPTION to display the Option menu.**

3 **Use 11Cursor △ / ▽ to select “Connect” and press 11ENTER. 1**

When wireless connection is complete

> “Not found” is displayed when there is an error connecting. Check that the following conditions have been satisfied, and try to establish a wireless connection again.
> - Both this unit and the Bluetooth component are paired.
> - The Bluetooth component is switched on.
> - The Bluetooth component is within 10 m of the Bluetooth Wireless Audio Receiver.

4 **Press 20OPTION to exit the Option menu.**

5 **Operate the Bluetooth component for playback.**

> To disconnect a wireless connection, repeat the same steps, and in step 3, select “Disconnect.”

1 : “Disconnect” is displayed when a Bluetooth component has been connected.

Controlling this unit by using the Web browser (Web Control Center)

Displaying and Operating Web Control Center

You can operate this unit by using a web browser. You can select the input source and sound field program, browse the iPod or network/USB contents, select the preset items, and adjust the parameters of this unit by using the graphical user interface (Web Control Center) that appears in the web browser. Check the IP address of this unit by using "IP Address" in "Network" menu (☞p. 98) in advance, and then enter the IP address to the web browser to access this unit to control it.

NOTE

When "Network Standby" is set to "On" in the Network menu, this unit can turns on and Web Control Center can be displayed on the PC even if this unit was in standby mode (☞p. 98). When "Network Standby" is set to "Off," we recommend that "Network Standby" is set to "On" to use Web Control Center.



- To use this feature, this unit and your PC must be connected properly in the network. Refer to "Connecting to the network" for details on the connections (☞p. 34).
- We recommend that you use Windows Internet Explorer 8 that is installed on Windows XP or Windows 7 PC to access this unit.
- You can select whether this unit accepts the controls by using the web browser when this unit is in the standby mode.
- You can register the MAC address of the PCs you want to use to control this unit and limit the PCs that can control this unit by using the web browser. You can select that this unit allows the access to this unit by the PCs whose MAC addresses are registered to this unit or allows the access by any PCs by using "MAC Address Filter" in the "Network" setup (☞p. 98).

Features of Web Control Center for each zone

Feature	Main Zone	Zone2
Power on/off	✓	✓
Sleep timer	✓	✓
Input select	✓	✓
Volume adjustment	✓	✓
Mute on/off	✓	✓
Content/channel select	✓	✓
Sound program	✓	—
Party Mode on/off	✓	✓
Required settings for web browse control	✓	✓

Top menu

① **CONTROL**
Changes the display to the zone control menu (☞p. 76).

② **SETTINGS**
Changes the display to the settings menu (☞p. 76).

③ **PARTY MODE**
Enables/disables the party mode (☞p. 99).

④ **SYSTEM POWER**
Turns on/off the power for all zones.

⑤ **STATUS**
Turns on/off the power for each zone, and displays the selected input source and volume level for each zone.

⑥ **MAIN VOLUME**
Adjusts the volume level or mutes the sound for the main zone. You can also switch the step for the volume control.

⑦ **RELOAD**
Reloads the current status of the receiver.

Zone control menu

You can control the selected zone.

① **PLAY INFO**
Controls the selected input for each zone.

② **TOP MENU**
Returns to the top menu.

③ **SCENE keys**
Selects the scene.

④ **POWER**
Turns on/off the power for the selected zone. You can also set the sleep timer for the selected zone.

⑤ **VOLUME**
Adjusts the volume level or mutes the sound for the main zone. You can also switch the step for the volume control.

⑥ **RELOAD**
Reloads the current status of the receiver.

Settings menu

You can make various settings regarding the web browse control.

① **Zone Rename**
Friendly Name indicates the identification name of the device (this unit) connected to the PC.
Friendly Name or the names of zones can be changed.

② **MAC Filter**
Applies the MAC address filter to this unit. Web Control Center can only be accessed from a computer with the same address as the MAC address registered here.

③ **Auto Reload**
Enables or disables the Auto Reload function which reloads the current status of the receiver every 5 minutes.

④ **Tips 1/Tips 2**
Displays the tips for use of Web Control Center.

⑤ **Create Link**
Customizes the display of Web Control Center.

⑥ **iPhone** ♛1
Selects the zoom rate for iPhone.

⑦ **BACK**
Returns to the top menu.

⑧ **RELOAD**
Reloads the current status of the receiver.

♛1 : This item appears only when accessing the Web Control Center with the iPhone.



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Configuring input sources (Input menu)

Settings, such as the name of an input source or the icon displayed for an input source can be changed from the Input menu.

Configuring input sources

The name of an input source and its icon, as well as other input source settings, can be changed from the Input menu displayed on the TV screen.

1 **Press 10ON SCREEN.**



2 **Use 11Cursor △ / ▽ to select “Input” and press 11ENTER.**



3 **Use 11Cursor ◁ / ▷ to select an input source to be configured and press 11Cursor △.**

4 **Use 11Cursor △ / ▽ to select an item and press 11ENTER.**

Settings

If the selected item contains additional items, use 11Cursor △ / ▽ to select the desired item and press 11ENTER.

5 **Use 11Cursor △ / ▽ to adjust the setting.**

Pressing 11RETURN displays the previous menu screen. Repeat steps 4 to 5 to adjust multiple settings.

6 **Press 10ON SCREEN to close the menu.**

Input menu



✓: available menu for each input source

	AV1-7	V-AUX	AUDIO1-4	PHONO	MULTI CH	USB	PC	NET RADIO	DOCK (iPod)	DOCK (Bluetooth)	TUNER
Rename/Icon Select	✓	✓	✓	✓	✓	✓			✓	✓	
Decoder Mode	✓	✓	✓								
Enhancer	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
DMC Control							✓				
Standby Charge									✓		
iPod Interlock									✓ 1		
Video Out					✓						

Changing an input source name or icon

Rename/Icon Select

Changes the input source name (up to nine characters) and icon displayed on the front panel display or TV screen.

1 **Use 11Cursor △ / ▽ repeatedly to select “Rename/Icon Select” and press 11ENTER.**

2 **Use 11Cursor ◁ / ▷ to choose an icon.**

3 **Press 11Cursor ▽ and 11ENTER.**

Editing the name is available.

4 **Press 11Cursor △ / ▽ to select a character, and press 11Cursor ◁ / ▷ to enter the selected character.**

5 **Repeat step 4 to enter the desired input source name.**

6 **Confirm the input source name by pressing 11ENTER.**

7 **Press 11Cursor ▽ to select “OK” and press 11ENTER to register the new input name.**

- To cancel the operation without applying changes, select “CANCEL” and then press 11ENTER.
- To clear the characters entered in step 5, select “CLEAR” and press 11ENTER.

1 : Not available when playing back iPod/iPhone with wired connection.

Setting the format of digital audio signals

Decoder Mode

Sets the format of digital audio to playback to DTS. For example, if the format is not automatically detected correctly even during playback of DTS format audio, this item can be used to set the playback format to DTS.

Auto **(Default)**	The audio format is automatically selected to match the format of the input audio.
DTS	Selects DTS signals only. Other input signals are not reproduced.

Selecting the sound program suitable for listening to compressed audio, such as MP3

Enhancer

Turns on/off the Compressed Music Enhancer.

Off	Turns off the Compressed Music Enhancer.
On	Turns on the Compressed Music Enhancer.

Using a PC to control this unit over a network

DMC Control

This unit can be operated via the DLNA compatible controller (e.g., Windows Media Player, etc.) to the same network of this unit. DMC stands for “Digital Media Controller.”

Disable	Disables the DMC control function.
Enable **(Default)**	Enables the DMC control function.

Charging an iPod™/iPhone™ in standby mode

Standby Charge

Charges an iPod/iPhone stationed in the Universal Dock for iPod or the receiver of the Wireless System for iPod while this unit is in standby mode.

Auto **(Default)**	This unit charges iPod/iPhone when this unit is in standby mode. While charging an iPod/iPhone, the HDMI Through/iPod Charge indicator lights. After the charging is complete, standby charge function is automatically off and the HDMI Through/iPod Charge indicator goes off. 1
Off	This unit does not charge iPod/iPhone.

Setting the interlock functions with iPod/iPhone (the receiver of the Wireless System for iPod is connected)

iPod Interlock

This unit can be automatically operated in conjunction with operations on iPod when the receiver of the Wireless System for iPod is connected to this unit.

Power & Input	Starting playback of iPod/iPhone turns on this unit and switches the input source to DOCK (iPod) automatically when this item is set to “On.” This unit automatically enters standby mode when iPod/iPhone is not operated for a while after playback is stopped. This interlock function is disable with “Off.”
Volume	Adjusting the volume on the iPod/iPhone also adjusts the volume of this unit when this item is set to “On.” This interlock function is disable with “Off.”

Outputting a video signal input from another input source while playing a multi-channel audio signal

Video Out

When “MULTI CH” is selected as the input source, a video signal input from another terminal can be output to the video monitor. For example, even if an audio and video component such as a DVD player that does not support a multi-channel digital audio output, the video signal can be output to the video monitor while reproducing a multi-channel analog audio signal.

1 : Standby charge function automatically turns off only when using YDS-10/11/12.



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Editing the SCENE function (Scene menu)

The SCENE function (☞p. 46) can be edited from the Scene menu displayed on the TV screen.

Editing a scene

Various settings, such as the name of a scene or the icon displayed for a scene, can be changed from the Scene menu.

1 **Press 10ON SCREEN.**



2 **Use 11Cursor △ / ▽ to select “Scene” and press 11ENTER.**



3 **Use 11Cursor ◁ / ▷ to select a scene to be edited and press 11Cursor △.**

4 **Use 11Cursor △ / ▽ to select an item and press 11ENTER.**



If the selected item contains additional items, use 11Cursor △ / ▽ to select the desired item and press 11ENTER.

5 **Use 11Cursor △ / ▽ / ◁ / ▷ to adjust the setting.**

Pressing 11RETURN displays the previous menu screen. Repeat steps 4 and 5 to adjust multiple settings.

6 **Press 10ON SCREEN to close the menu.**

Scene menu



Scene 5 to 12 can also be edited in the Scene menu. Select Scene 5 to 12 in the Scene menu.

Registering SCENE function settings

Save

Registers the settings currently applied to this unit for each SCENE.

Adjusting settings registered with the SCENE function

Load

Loads input sources or sound programs that have been registered with the SCENE function, or specifies whether or not an external component registered as the input source is automatically turned on when a scene is selected.

OK	Loads items indicated with a check mark in "DETAIL."
CANCEL	Cancels settings applied with "DETAIL."
DETAIL	Specifies "SCENE IR" function and displays settings registered with the SCENE function in detail. For more information, see "SCENE IR" and "Detail" at right.

SCENE IR

Specify whether or not a Yamaha BD/DVD player or CD player connected to this unit turns on automatically.

Off	Disables the SCENE IR function.
Yamaha BD/DVD Player1	Select this when a Yamaha BD/DVD player is connected to this unit.
Yamaha BD/DVD Player2	Select this if the player dose not turn on when "Yamaha BD/DVD Player1" is selected.
Yamaha CD Player	Select this when a Yamaha CD player is connected to this unit.

Detail

Display details of settings registered with the SCENE function. Items indicated with a check mark in "Setting" are loaded.

Input	☑	Displays the "Input" and "Audio Select" settings registered with the SCENE function.
HDMI Output	☑	Displays the HDMI output jack(s) registered with the SCENE function.
Mode	☑	Displays the sound program registered with the SCENE function.
Sound	☑	Displays the "Tone Control," "Adaptive DRC," and "Enhancer" settings registered with the SCENE function.
Surround	☐	Displays the "CINEMA DSP 3D Mode," "Dialogue Lift," and "Extended Surround" settings registered with the SCENE function.
Video	☐	Displays the "Video Processing" registered with the SCENE function.
Volume	☐	Displays the volume setting registered with the SCENE function.
Lipsync	☐	Displays the "Lipsync" and "Delay" settings registered with the SCENE function.
Speaker Setup	☐	Displays the "Setting Pattern" and "PEQ Select" settings registered with the SCENE function.



4 Input selector
9 SCENE
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

Changing a scene name and icon

Rename/Icon Select

Changes the scene name and icon displayed on the front panel display or TV screen.

1 Use 11Cursor △ / ▽ repeatedly to select "Rename/Icon Select" and press 11ENTER.

2 Use 11Cursor ◁ / ▷ to choose an icon.

3 Press 11Cursor ▽ and 11ENTER.

Editing the name is available.

4 Press 11Cursor △ / ▽ to select a character, and press 11Cursor ◁ / ▷ to enter the selected character.

Scene names may consist of up to 20 characters.

5 Repeat step 4 to enter the desired scene name.

6 Confirm the scene name by pressing 11ENTER.

7 Press 11Cursor ▽ to select "OK" and press 11ENTER to register the new input name.

- To cancel the operation without applying changes, select "CANCEL" and then press 11ENTER.
- To clear the characters entered in step 4, select "CLEAR" and press 11ENTER.

Resetting a scene

Reset

Restores all settings for the selected scene to their default values.

Simple registering as the SCENE

1 Use 4Input selector to select the input source you want to register.

2 Set the settings such as sound program, Compressed Music Enhancer, or HDMI OUT you want to register.

The following settings can be registered with a scene 1:
Input, Audio Select, HDMI Output, Sound Program, Pure Direct Mode, Tone Control, Adaptive DRC, Compressed Music Enhancer, CINEMA DSP 3D Mode, Dialogue Lift, Extended Surround, Video Processing, Master Volume, Lipsync, Setting Pattern, PEQ Select

3 Press the 9SCENE key until "SET Complete" appears on the front panel display.

Release the key when "SET Complete" is displayed

When changing "SCENE," also change the external component that the remote control operates (☞p. 106).

1 : The settings with unchecked boxes in "Load" of the Scene menu are not assigned to this unit even when pressing the correspond scene key.

Setting sound program parameters (Sound Program menu)

Sound effects can be adjusted from the Sound Program menu.



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Editing sound programs

Adjust sound field elements (sound program parameters) to achieve sound effects suited to the acoustics of audio/video sources or rooms if you are not satisfied with the results achieved with default sound program settings. Follow the procedure described below to adjust sound program parameters.

1 **Press 10ON SCREEN.**

2 **Press 11Cursor △ / ▽ to select “Sound Program” and press 11ENTER.**



3 **Use 11Cursor ◁ / ▷ to select a sound program and press 11Cursor △.**



4 **Use 11Cursor △ / ▽ to select a parameter and press 11ENTER.**



5 **Use 11Cursor △ / ▽ / ◁ / ▷ to adjust the parameter and press 11RETURN. 1**

When there are multiple parameters in the selected sound program, repeat steps 4 and 5 to adjust other parameters.

6 **Press 10ON SCREEN to close the Sound Program menu.**

■ To initialize sound program parameters

To set the parameters of the sound program back to their default settings, use 11Cursor △ / ▽ repeatedly to select “Reset” in step 4 and press 11ENTER. When the following message is displayed, select “OK” and press 11ENTER to initialize.



To cancel initializing, select “CANCEL” and press 11ENTER when the message above is displayed.

1 : An asterisk (*) appears on the left of the sound field parameter name displayed on the TV when you change the parameter from its default setting.

CINEMA DSP parameters

DSP Level

Change the effect level (level of the sound field effect to be added). You can adjust the level of the sound field effect while checking the sound effect.

Adjustable range	-6 dB to +3 dB
Default setting	0 dB

Adjust “DSP Level” as follows:
- The effect sound is too soft.
- There are no differences between effects of the sound programs.
  → Increase the effect level.
- The sound is dull.
- The sound field effect is added too much.
  → Reduce the effect level.

Initial Delay

Surround Initial Delay

Surround Back Initial Delay

Initial delay. Presence, surround, and surround back sound field initial delay. Changes the apparent size of the sound field by adjusting the delay between the direct sound and the first reflection heard by the listener. The smaller the value, the smaller the sound field seems to the listener.

Adjustable range	1 to 99 ms (Initial Delay) 1 to 49 ms (Surround Initial Delay and Surround Back Initial Delay)



When you adjust the initial delay parameters, we also recommend that you adjust the corresponding room size parameters likewise.

Room Size

Surround Room Size

Surround Back Room Size

Room size. Presence, surround, and surround back room size. Adjusts the apparent size of the sound field. The larger the value, the larger the surround sound field becomes. As the sound is repeatedly reflected around a room, the larger the hall is, the longer the time between the original reflected sound and the subsequent reflections. By controlling the time between the reflected sounds, you can change the apparent size of the virtual venue. Changing this parameter from one to two doubles the apparent length of the room.

Adjustable range	0.1 to 2.0



When you adjust the room size parameters, we also recommend that you adjust the corresponding initial delay parameters likewise.

Liveness

Surround Liveness

Surround Back Liveness

Liveness. Surround and surround back liveness. Adjusts the reflectivity of the virtual walls in the hall by changing the rate at which the early reflections decay. The early reflections of an audio source decay much faster in a room with acoustically absorbent wall surfaces than in one which has highly reflective surfaces. A room with acoustically absorbent surfaces is referred to as “dead,” while a room with highly reflective surfaces is referred to as “live.” This parameter lets you adjust the early reflection decay rate and thus the “liveness” of the room.

Adjustable range	0 to 10



Reverb Time

Reverberation time. Adjusts the amount of time taken for the dense, subsequent reverberation sound to decay by 60 dB at 1 kHz. This changes the apparent size of the acoustic environment over an extremely wide range. Set a longer reverberation time to get more sustaining reverberation sound, and set a shorter time to get articulate sound.

Adjustable range	1.0 to 5.0 s



Reverb Delay

Reverberation delay. Adjusts the time difference between the beginning of the direct sound and the beginning of the reverberation sound. The larger the value, the later the reverberation sound begins. A later reverberation sound makes you feel as if you are in a larger acoustic environment.

Adjustable range	0 to 250 ms



Reverb Level

Reverberation level. Adjusts the volume of the reverberation sound. The larger the value, the stronger the reverberation becomes.

Adjustable range	0 to 100%



Decode Type

Selects a surround decoder to be used with a sound program in the MOVIE category. 1

PLIIx Movie PLII Movie	Selects the Dolby Pro Logic IIx Movie (or Dolby Pro Logic II Movie) decoder.
Neo:6 Cinema	Selects the Neo:6 (Cinema) decoder.

Parameters usable in certain sound programs

2ch Stereo only

Direct

Automatically bypasses the DSP circuit and tone control circuit depending on the condition of tone control etc., when an analog audio source is played back. You can enjoy a higher quality sound.

Auto **(Default)**	Outputs sound by bypassing the DSP circuit and tone control circuit when both tone controls of “Bass” and “Treble” are set to 0 dB.
Off	Does not bypass the DSP circuit and tone control circuit.

7ch Stereo only

Center Level

Adjusts the center channel volume. 2

Adjustable range	0 to 100%
Default setting	100%

Surround L Level

Adjusts the volume of the surround L channel. 2

Adjustable range	0 to 100%
Default setting	100%

Surround R Level

Adjusts the volume of the surround R channel. 2

Adjustable range	0 to 100%
Default setting	100%

Surround Back L Level

Adjusts the volume of the surround back L channel. 2

Adjustable range	0 to 100%
Default setting	35% (7.1-channel configuration) 50% (6.1-channel configuration)

Surround Back R Level

Adjusts the volume of the surround back R channel. 2

Adjustable range	0 to 100%
Default setting	35% (7.1-channel configuration) 50% (6.1-channel configuration)

Front Presence L Level

Adjusts the volume of the front presence L channel. 2

Adjustable range	0 to 100%
Default setting	33%

1 : Surround decoders cannot be changed when used with the following MOVIE and ENTERTAINMENT sound programs.
- Mono Movie
- Sports
- Action Game
- Roleplaying Game

2 : Not displayed when speakers are set to be inactive.

Front Presence R Level

Adjusts the volume of the front presence R channel. ♛1

Adjustable range	0 to 100%
Default setting	33%

Parameters usable in surround decoder

Decode Type

Selects a surround decoder.

Pro Logic	Reproduces sound using the Dolby Pro Logic decoder. This is suitable for all kinds of audio sources.
PLIIx Movie / PLII Movie	Reproduces sound using the Dolby Pro Logic IIx (or Dolby Pro Logic II) decoder. This is suitable for movies. ♛2
PLIIx Music / PLII Music	Reproduces sound using the Dolby Pro Logic IIx (or Dolby Pro Logic II) decoder. This is suitable for music. ♛2
PLIIx Game / PLII Game	Reproduces sound using the Dolby Pro Logic IIx (or Dolby Pro Logic II) decoder. This is suitable for games. ♛2
Neo:6 Cinema	Reproduces sound using the DTS Neo:6 decoder. This is suitable for movies.
Neo:6 Music	Reproduces sound using the DTS Neo:6 decoder. This is suitable for music.

Dolby PLIIx Music and Dolby PLII Music only

Panorama

Adjusts the soundscape of the front sound field. Sends front left/right channels sounds to the surround speakers as well as the front speakers for a wraparound effect.

Off **(Default)**	Disables the effect.
On	Enables the effect.

Center Width

Spreads the center channel sound to the front left and right speakers to suit your needs or preferences. Set this parameter to 0 for outputting the center sound from the center speaker only, or to 7 for outputting it from the front left/right speaker only.

Adjustable range	0 to 7
Default setting	3

Dimension

Adjusts the difference in level between the front sound field and the surround sound field. You can adjust the difference in level created by the software being played back to obtain the preferred sound balance.
The surround sound gets stronger as you make the value more negative, and the front sound gets stronger as you make the value more positive.

Adjustable range	-3 to +3
Default setting	0

When Neo:6 Music is selected

Center Image

Adjusts the front left and right channel output relative to the center channel to make the center channel more or less dominant as necessary.

Adjustable range	0.0 to 1.0
Default setting	0.3

♛1 : Not displayed when speakers are set to be inactive.
♛2 : You cannot select the Dolby Pro Logic IIx decoder in the following conditions:
- When “Surround Back” is set to “None” (☞p. 91).
- When headphones are connected.



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Setting various functions (Setup menu)

Various settings, such as speaker volume or HDMI functions, can be changed from the Setup menu.

Operating the Setup menu

1 **Press 10ON SCREEN.**

2 **Press 11Cursor △ / ▽ repeatedly to select "Setup" and press 11ENTER.**



3 **Use 11Cursor ◁ / ▷ to select a menu and press 11ENTER.**



Setup menus

Speaker	Adjusts parameters for speakers, such as speaker status, and volume adjustment for each speaker (☞p. 89).
Sound	Sets functions related to audio output, such as adjustment of maximum volume and of dynamic range (☞p. 93).
Video	Sets video output functions, such as video conversion settings (resolution and aspect ratio) (☞p. 95).
HDMI	Sets HDMI functions, such as the HDMI Control function and output destination for HDMI sound (☞p. 96).
Network	Sets network status, such as IP Address or MAC Address Filter (☞p. 98).
Multi Zone	Sets multi-zone functions, such as volume adjustment for speakers in the secondary zone (☞p. 99).
Function	Sets functions such as the Auto Power Down function, that make the unit easier to use (☞p. 100).
Language	Selects the language of the menus and messages displayed on TV screen (☞p. 103).

4 **Use 11Cursor △ / ▽ to select an item and press 11ENTER.**

When the selected item contains detailed ones, use 11Cursor △ / ▽ to select the detailed item and press 11ENTER.

5 **Use 11Cursor △ / ▽ / ◁ / ▷ to adjust the setting.**

Pressing 11RETURN displays the previous menu screen. Repeat steps 4 to 5 to adjust multiple settings.

6 **Press 10ON SCREEN to close the menu.**

Setup menu

- Speaker
  - Auto Setup
  - Manual Setup
- Sound
  - Lipsync
  - Dynamic Range
  - Max Volume
  - Initial Volume
  - Pure Direct Mode
  - Adaptive DSP Level
- Video
  - Analog to Analog Conversion
  - Processing
- HDMI
  - HDMI Control
  - Control Select
  - ARC (Audio Return Channel)
  - TV Audio Input
  - Audio Output
  - Standby Through
- Network
  - IP Address
  - Network Standby
  - MAC Address Filter
- Multi Zone
  - Zone2 Set
  - Monitor Out Assign
  - Party Mode Set
  - Zone Scene Rename
  - Zone Rename
- Function
  - Auto Power Down
  - Input Assignment
  - Display Set
  - Trigger Output1
  - Trigger Output2
  - Memory Guard
- Language

Manages settings for speakers

Speaker setup items

Auto Setup	Optimizes the speaker configuration automatically.
Manual Setup	Manually adjusts parameters for speakers.

Automatic speaker setup

Auto Setup

Optimizes the speaker configuration automatically using YPAO (☞p. 37).

Manual speaker setup

Manual Setup

The following parameters can be specified manually.



Setting Pattern	Registers two speaker setting patterns and switches between the two.
Setting Data Copy	Copies “Setting Pattern” data.
Power Amp Assign	Adds the extra speakers to the 7.1-channel speaker connection.
Configuration	Manually manages speaker configuration, such as speaker size (sound production capacity), and bass audio processing.
Distance	Manually adjusts the output of each speaker based on distance to the listening position.
Level	Manually adjusts the volume of each speaker.
Parametric EQ	Selects an equalizer to adjust speaker output characteristics.
Test Tone	Generates test tones.

Setting Pattern

Registers two patterns for “Power Amp Assign,” “Configuration,” “Level,” “Distance,” and “Parametric EQ” settings and switches between the two setting patterns.
When the automatic speaker setup (YPAO) is performed, the result of measurement is registered on the currently selected Setting Pattern.

Setting Data Copy

Copies “Setting Pattern” data in the specified direction.

Pattern1 ► 2	Copies Pattern1 settings to Pattern2.
Pattern2 ► 1	Copies Pattern2 settings to Pattern1.

Power Amp Assign

In addition to the 7.1-channel speaker connection, various speaker configurations are possible using the presence speakers connection, bi-amp connection or multi-zone function (☞p. 19, p. 20).



7ch Normal	Enables the normal 7-channel speakers and front presence speakers (☞p. 16).
7ch +1ZONE	Enables the normal 7-channel speakers and zone2 speakers (☞p. 18).
5chBI-AMP	Enables the bi-amp connection (☞p. 18).
5chBI-AMP +SB	Enables the bi-amp connection and external surround back speakers (☞p. 22).

Configuration

Displays the speakers connected to this unit or changes the sizes of the speakers.



In the “Configuration,” you can select the speaker size characteristic (Large or Small). Select the size (sound reproduction capacity) that matches your speakers.



Woofer diameter
- 16 cm or larger → Large
- 16 cm or smaller → Small

When speaker size is set to “Small,” low-frequency components of the speakers that you configured are produced from the subwoofer (or from the front speakers if there is no subwoofer).

Front

Selects the size (sound reproduction capacity) of the front speakers. ♛1

Large	Select this for large speakers. The front speakers will produce all of the front channel frequency components.
Small **(Default)**	Select this for small speakers. The subwoofer will produce front channel low-frequency components. ♛2

Center

Selects the size of the center speaker.

Large	Select this when a large center speaker is connected.
Small **(Default)**	Select this when a small center speaker is connected.
None	Select this when there is no center speaker. The front speakers will produce center channel audio.

Surround

Selects the size of the surround speakers.

Large	Select this when the surround speakers are large.
Small **(Default)**	Select this when the surround speakers are small.
None	Select this when no surround speakers are connected. The front speakers will produce surround channel audio signals.

- When set to “None,” no sound is produced from the surround back speaker even if that speaker is connected.
- When set to “None,” the sound programs will change to Virtual CINEMA DSP mode.

♛1 : When “Subwoofer” is set to “None,” you can only choose “Large.” If the front speaker setting is “Small” and you change “Subwoofer” to “None,” it will automatically change to “Large.”

♛2 : You can set the low-frequency components of audio signals transmitted from the front speakers to the subwoofer by using “Bass Cross Over.”

Surround Back
Selects the size of the surround back speakers.

Largex1	Select when one large surround back speaker is connected.
Largex2	Select when two large surround back speakers are connected.
Smallx1	Select when one small surround back speaker is connected.
Smallx2 **(Default)**	Select when two small surround back speakers are connected.
None	Select this when no surround back speakers are connected.

- When there are no surround speakers are connected, the setting will automatically change to “None.”
- You can set surround back audio signals, including from the playback source, to be mixed down and produced from a single speaker (6.1-channel layout) or produced from left and right surround speakers (5.1-channel layout).

Front Presence
Specify connection of front presence speakers.

Use **(Default)**	Select this when front presence speakers are connected.
None	Select this when front presence speakers are not connected.

Subwoofer
Confirms the subwoofer.

Use **(Default)**	Select this when subwoofer is connected. During playback, the subwoofer will produce audio from the LFE (low-frequency effect) channel and bass audio from other channels. 1 Select the phase of the subwoofer from the following items if the bass audio is lacking or unclear. Normal **(Default)** Does not change the subwoofer phase. Reverse Reverses the subwoofer phase.
None	Select this when subwoofer is not connected. The front speakers will produce audio from the LFE (low frequency effect) channel and bass frequency audio from other channels when “Subwoofer” is set to “None.”

Extra Bass
Allows the front channel low-frequency components to be produced exclusively by the subwoofer, or by both the subwoofer and the front speakers.

Off **(Default)**	Depending on the size of the front speakers, either the front speakers or the subwoofer produce the front channel low-frequency components.
On	The subwoofer and the front speakers produce the front channel low-frequency components.

When “Subwoofer” is set to “None” or “Front” is set to “Small,” “Extra Bass” is disabled.

Bass Cross Over
Sets the lower limit of low-frequency component which is produced from speakers of which the size is set to “Small.”
A frequency sound which is lower than the specified frequency will be produced from the subwoofer or the front speakers. 2

40Hz	110Hz
60Hz	120Hz
80Hz **(Default)**	160Hz
90Hz	200Hz
100Hz	

1 : Enabling “Extra Bass” allows both the subwoofer and the front speakers to produce bass audio.
2 : If your subwoofer has a volume control or a crossover frequency control, set the crossover frequency to maximum and the volume to half (or slightly less).



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

Distance

Adjusts the timing at which the speakers produce audio so that sounds from the speakers reach the listening position at the same time.

Selecting adjustment units

Use 11Cursor △ / ▽ to select the unit for distance (meters or feet), and press 11ENTER.

Setting distances for each speaker

Use 11Cursor △ / ▽ to select the speaker you want to configure, and press 11ENTER.
Then use 11Cursor ◁ / ▷ to set the distance from the speaker to your listening position.

Adjustable range	0.30 m to 24.00 m (1.0 ft. to 80.0 ft.)
Default setting	3.00 m (10.0 ft.)
Adjustment increments	0.05 m (0.2 ft.)

Level

Separately adjusts the volume of each speaker.
Use 11Cursor △ / ▽ to select the desired speaker, and press 11ENTER.
Then use 11Cursor ◁ / ▷ to adjust the volume for the selected speaker.

Adjustable range	-10.0 dB to +10.0 dB
Default setting	0.0 dB
Adjustment increments	0.5 dB

Parametric EQ

Adjusts sound quality of tone using a parametric equalizer.

PEQ Select

Select an equalizer type.

Manual	Manually adjust equalizer sound.
Flat	Adjust individual speakers to achieve the same characteristics. Select this option if speakers offer the same quality.
Front	Adjust individual speakers to achieve the same characteristics as the front left and right speakers. Select this option if front left and right speakers offer significantly greater quality than other speakers.
Natural	Adjust all speakers to achieve a natural sound. Select this if high-frequency sounds seem too strong when "PEQ Select" is set to "Flat."
Through **(Default)**	Disable the equalizer.

PEQ Data Copy

Select 1 of the 3 parametric equalizer types acquired with automatic setup and manually copy that information to the manual adjustments.

Flat ▶ Manual	Copy the "Flat" parametric equalizer information acquired with automatic setup.
Front ▶ Manual	Copy the "Front" parametric equalizer information acquired with automatic setup.
Natural ▶ Manual	Copy the "Natural" parametric equalizer information acquired with automatic setup.

Front L/ Front R / Center / Surround L / Surround R / Surround Back L / Surround Back R / Front Presence L / Front Presence R

The parametric equalizer can be used to manually adjust sound quality for individual speakers.
Set "PEQ Select" to "Manual" and use "PEQ Data Copy" to copy information acquired with automatic setup. This information can be used as a basis for performing manual adjustments.

1 **Use 11Cursor △ / ▽ repeatedly to select "Band / Gain," "Freq. / Gain," or "Q / Gain" and press 11ENTER.**

2 **Use 11Cursor ◁ / ▷ repeatedly to adjust the parameter and use 11Cursor △ / ▽ repeatedly to adjust the gain.**

3 **Press 11ENTER to exit the edit window.**

4 **Repeat steps 1 to 3 to configure other parameters.**

To reset all parameter settings for the selected speaker, select "Yes" in "Reset" and press 11ENTER.

5 **Press 10ON SCREEN to close the menu.**

Test Tone

Turns the test tone generator on or off.

Off **(Default)**	Does not generate test tones.
On	Generates test tones. While “On” is selected, test tones are produced constantly.

You can use the test tone in a variety of circumstances. For example, you can adjust the volume balance settings for each speaker, or whenever you adjust the settings on the internal parametric equalizer, you can listen to the actual effect while operating this unit. Turn the test tone off when you have finished making adjustments.

Setting the audio output function of this unit

Sound setup items

Lipsync	Adjusts the delay between video and audio output.
Dynamic Range	Selects the dynamic range adjustment method for Dolby Digital and DTS playback.
Max Volume	Sets the maximum volume for this receiver.
Initial Volume	Sets the initial volume for when this receiver is turned on.
Pure Direct Mode	Selects whether or not this unit outputs video signal in the Pure Direct Mode.
Adaptive DSP Level	Adjusts the level of DSP effect in conjunction with the volume level.

Synchronizing audio/video output

Lipsync

Adjusts the delay between audio and video output (Lipsync function).
Selects a compensation method for the delay between audio and video output.

Auto **(Default)** 1	When connecting to a TV via HDMI, automatically adjusts output timing if the TV supports an automatic lipsync function.
Manual	Manually adjusts the correction time. Select this when the monitor does not support the automatic lipsync function.

Adjustable range	0 ms to 250 ms
Default setting	0 ms
Adjustment increments	1 ms

1 : The setting is effective at the HDMI OUT jack selected by using 18 HDMI OUT.

Auto-adjusting Dolby Digital and DTS dynamic range

Dynamic Range

Selects the dynamic range adjustment method for audio bitstream (Dolby Digital and DTS) signal playback.

MAX **(Default)**	Produces audio without adjusting the dynamic range.
STD	Adjusts the dynamic range for optimum volume for regular home use.
MIN/AUTO	(MIN) Sets the dynamic range suitable for low volume or a quiet environment, such as at night, for bitstream signals except for Dolby TrueHD signals. (AUTO) Adjusts the dynamic range for Dolby TrueHD signals based on input signal information.

Setting the maximum volume

Max Volume

Specify the maximum volume level so that sound is not too loud. The default setting of +16.5 dB produces the highest volume.

Adjustable range	-30.0 dB to +16.5 dB (maximum volume)
Default setting	+16.5 dB
Adjustment increments	5.0 dB

Setting the startup volume

Initial Volume

Sets the initial volume for when this receiver is turned on. When this parameter is set to “Off,” the volume is set at the level when the receiver last entered standby mode. 1

Adjustable range	Off, Mute, -80.0 dB to +16.5 dB
Default setting	Off
Adjustment increments	0.5 dB

Video signal output in Pure Direct Mode

Pure Direct Mode

Selects whether or not this unit outputs video signal in the Pure Direct Mode.

Auto **(Default)**	Automatically output video signal when the input source equipping video signal input jacks or content window is selected. If no video signal is input, only the wall paper is displayed.
Video Off	Does not output video signals including the wall paper.

Adjusting DSP effect and volume level

Adaptive DSP Level

Automatically adjust the level of DSP effect in conjunction with the volume level.

Off	Disables automatic adjustment of the level of DSP effect.
On **(Default)**	Adjusts the degree of DSP effect in conjunction with volume level. The higher the volume level, the less the DSP effect applied. The lower the volume level, the greater the DSP effect applied. This feature also corrects sound effect according to the result of automatic measurement.

1 : When you set “Max Volume” at a lower level than “Initial Volume,” “Max Volume” has priority.

Setting this unit's video output function

Video setup items

Analog to Analog Conversion	Enable or disable video conversion between analog video jacks.
Processing	Enable or disable adjustment of resolution, aspect ratio and video signal correction for video signal converted to HDMI video.

Analog-to-analog video conversion

Analog to Analog Conversion

Enables or disables video conversion between analog video jacks.

Off	Disables video conversion between analog video jacks.
On **(Default)**	Enables video conversion between analog video jacks.

- Analog-to-HDMI video conversion is always possible unless video signals are being input at the HDMI input jacks or 1080p-resolution analog video signals are being input (☞p. 129).
- This unit does not convert 480 line video signals and 576 line video signals interchangeably.
- 480p-, 576p-, 1080i- and 720p-resolution video signals can not be output at the S-video and video jacks of MON.OUT/ZONE OUT (☞p. 129).
- The converted video signals are only output at the MONITOR OUT jacks.
- When composite video or S-video signals from a VCR are converted into component video signals, the picture quality may suffer depending on your VCR.
- Unconventional signals input at the composite video or S-video jacks cannot be converted or may be output abnormally. In such cases, set "Analog to Analog Conversion" to "Off."

Adjusting video with conversion of video signal to HDMI

Processing

Adjust video with conversion of video input to HDMI video.

Off **(Default)**	Video are not adjusted with processing.
On	Video are adjusted with processing.

Resolution 1

Auto **(Default)**	Automatic upscaling in accordance with TV resolution.
480p (576p)	Upscaling to 480p (576p).
720p	Upscaling to 720p.
1080i	Upscaling to 1080i.
1080p	Upscaling to 1080p.
Through	No upscaling.

- The 720p-, 1080i- and 1080p-resolution video signals cannot be upscaled (☞p. 129).
- When a TV is connected to this unit via the HDMI jack, this unit automatically detects a resolution that the TV supports. Only the detected resolution can be selected.
- If this unit cannot detect the resolution that the TV supports, set "MONITOR CHECK" in the Advanced Setup menu to "SKIP" (☞p. 111) and try again.

Aspect 1

Specifies the method used to convert video signal with a 4:3 aspect ratio (480i/576i/480p/576p) to the 16:9 aspect ratio (720p/1080i/1080p).

Through **(Default)**	Does not adjust the aspect ratio of video signal sources.
16:9 Normal	Transmits 4:3 aspect ratio video signals to a 16:9 TV with black bands on either side of the screen.

1 : This item can be set when set "Processing" to "On."

Setting HDMI functions

HDMI setup items

HDMI Control	Turns the HDMI Control on or off.
Control Select	Choose an HDMI OUT jack on which HDMI Control function is enabled.
ARC (Audio Return Channel)	Turns the Audio Return Channel function on or off.
TV Audio Input	Chooses automatically selected audio input in conjunction with TV operation when the HDMI Control is turned on.
Audio Output	Specifies whether or not audio signal is output through this unit and a TV connected via the HDMI OUT 1-2 jacks.
Standby Through ♛1	Turns the Standby Through function on or off.

Receiver operation via TV (HDMI Control)

HDMI Control

Set the HDMI Control function to “On” to operate devices connected via HDMI. If the TV or other external components support HDMI Control (e.g., Panasonic VIERA Link), you can use the remote controls of those devices to operate some of this unit’s functions, and to synchronize this unit with the operation of those devices.
Refer to “Using the HDMI Control function” (☞p. 113) for setting instructions.

Off **(Default)**	Sets HDMI Control to “Off.”
On	Sets HDMI Control to “On.” ♛2

If this unit is connected to HDMI devices that do not support the HDMI Control function, these functions will not operate.

Selecting an HDMI OUT jack for the HDMI Control function

Control Select

Select the HDMI OUT jack that utilizes the HDMI Control function.
Refer to “Using the HDMI Control function” (☞p. 113) for setting instructions.

OUT1(TV1)	Applies the HDMI Control function for the HDMI OUT 1 jack.
OUT2(TV2)	Applies the HDMI Control function for the HDMI OUT 2 jack.

We recommend to unplug and plug again the power cable of this unit and the TV when changing the Control Select.

Listening to TV audio via single HDMI cable (Audio Return Channel)

ARC (Audio Return Channel)

You can enable or disable the Audio Return Channel function. When using a TV that supports Audio Return Channel function and the function is enabled, the TV’s audio output is transmit to this unit via an HDMI cable.
The TV audio input to this unit is regarded as the input source selected in “TV Audio Input.” ♛3
By means of this function, you do not need to connect the TV’s audio output (digital audio output or analog audio output) to the unit.

Off **(Default)**	Sets the Audio Return Channel to “Off.”
On	Sets the Audio Return Channel to “On.”

When the TV audio is input to the unit using Audio Return Channel, “TV” is displayed on the front panel display.

- “ARC (Audio Return Channel)” is enabled only for the HDMI OUT 1 or 2 jack selected with “Control Select.”
- Refer to “Single HDMI cable input to TV audio with Audio Return Channel function” (☞p. 115) for setting instructions.

♛1 : This item appears depending on “HDMI Control.”

♛2 : When the HDMI Control is “On,” the Standby Through function is automatically enabled. When this unit enters standby mode, the audio and video signals from the last-selected HDMI input source will continue to be transmitted to the TV. The HDMI input source can only be changed using the remote control.

♛3 : While the Audio Return Channel function is on, the jack selected for the input source cannot be used.

Selecting an input source to assign audio input for the TV

TV Audio Input

Select the input source that receives audio signals from TV while the HDMI Control function is on.
When the TV is set to output sounds via this unit, the TV audio input is automatically selected to the input source assigned here. ♛1

TV1

Audio input	AUDIO1-4
Default setting	AUDIO1

TV2

Audio input	AUDIO1-4
Default setting	AUDIO3

- "TV Audio Input" is enabled only for the HDMI OUT 1 or 2 jack selected with "Control Select."
- Refer to "Switching the input source on this unit automatically when listening to TV audio" (☞p. 114) for instructions.

Specify whether or not audio signal is output through this unit and a TV connected via the HDMI OUT jack

Audio Output

Choose whether audio from an external component, such as a BD/DVD player, connected via HDMI is played back through this unit or through a TV.

Amp
Specify whether or not audio signal is output through this unit.

Off	Audio is not output through this unit.
On **(Default)**	Audio is output through this unit. When this setting is selected, audio from the external component is output in a format compatible with this unit.

OUT1
Specify whether or not audio signal is output through a TV connected via the HDMI OUT 1 jack.

Off **(Default)**	Audio is not output through a TV connected via the HDMI OUT 1 jack.
On	Outputs audio through a TV connected via the HDMI OUT 1 jack. When this setting is selected, audio from the external component is output in a format compatible with the TV.

OUT2
Specify whether or not audio signal is output through a TV connected via the HDMI OUT 2 jack.

Off **(Default)**	Audio is not output through a TV connected via the HDMI OUT 2 jack.
On	Outputs audio through a TV connected via the HDMI OUT 2 jack. When this setting is selected, audio from the external component is output in a format compatible with the TV.

When "HDMI Control" is set to "On," the settings of "Amp" and the output jack (OUT1 or OUT2) selected with Control Select are interlocked with HDMI Control.

Transmitting HDMI audio/video to the TV during standby mode (Standby Through)

Standby Through

This function allows audio/video signals from HDMI inputs to continue to be transmitted to a TV when this unit is in standby mode. When the Standby Through function is "On," audio/video signals continue to be output to the TV from the last HDMI input source before this unit enters standby mode. The HDMI input source can be selected using 4AV1-7 or 4V-AUX in standby mode.

Off **(Default)**	Sets Standby Through to "Off."
On	Transmits audio/video signals from the selected HDMI input source to the TV.

- When "HDMI Control" is "On," Standby Through function is automatically enabled and "Standby Through" is not displayed.
- When the Standby Through function is on, the HDMI Through/iPod Charge indicator on the front panel lights during the standby mode. This unit consumes 2 to 5 W of power.
- Input source can be selected during Standby Through.

♛1 : While the Audio Return Channel function is on, the jack selected for the input source cannot be used.

Adjusting this unit's network parameters

Network setup items

IP Address	Selects whether this unit acquires the network parameters (IP address, etc.) from the network's DHCP server automatically, or whether these parameters are specified manually.
Network Standby	Selects whether or not commands are accepted over the network when this unit is in standby mode.
MAC Address Filter	Sets the MAC address filter to restrict network access to this unit.

Setting the network parameters (IP address, etc.)

IP Address

Selects whether or not this unit automatically acquires network parameters (IP address, subnet mask, default gateway, primary DNS server and secondary DNS server) from a network device such as a router equipped with DHCP function.

DHCP

Off	Select this setting to specify IP address manually.
On **(Default)**	Select this setting to acquire IP address from the network's DHCP server automatically.

Manual Setup

IP Address	Specifies the IP address assigned to this unit. An IP address used by another device on the same network may not be used.
Subnet Mask	Specifies the subnet mask assigned to this unit.
Default Gateway	Specifies the IP address of the default gateway.
DNS Server (Primary)/DNS Server (Secondary)	Specifies the IP addresses of the primary and secondary Domain Name System (DNS) servers.

If you have only one DNS address, enter the DNS address in "DNS Server (Primary)." If the network has two or more DNS addresses, enter one of the addresses in "DNS Server (Primary)" and another in "DNS Server (Secondary)."

Turning this unit on by the command over the network when in the standby mode

Network Standby

Selects whether or not to turn this unit on by the command over the network when in the standby mode.

Off **(Default)**	Disables to turn this unit on by the command over the network.
On	Enables to turn this unit on by the command over the network.

When "Network Standby" is set to "On," this unit can be turned on by the command over the network during the standby mode with the power consumption of about only 5 W.

Setting the MAC Address Filter

MAC Address Filter

Sets MAC address filter to restrict access to this unit via LAN.

Mode

Off **(Default)**	Disables the MAC address filter function.
On	Permits access to this unit only from network devices with the specified MAC addresses.

Address Setup

Specifies the MAC addresses of network devices permitted to access to this unit when "MAC Address Filter" is set to "On."

Setting this unit's multi-zone function

Multi Zone setup items

Zone2 Set	Sets the Zone2 functions.
Monitor Out Assign	Displays the menus of Zone2 on the TV monitor.
Party Mode Set	Enable or disable the party mode function.
Zone Scene Rename	Changes the scene names of Zone2.
Zone Rename	Changes the name of Zone2.

Adjusting Zone2 volume

Zone2 Set

Volume

Selects whether or not volume level adjustment of Zone2 speakers is enabled.

Fixed	Disables volume level adjustment of Zone2 speakers.
Variable **(Default)**	Enables volume level adjustment of Zone2 speakers.

When setting the Power Amp Assign function, "Volume" is automatically set to "Variable." Refer "Speaker layout" (☞p. 16) for details on the Power Amp Assign function.

Max Volume

Specify the maximum volume level in Zone2 so that sound is not too loud.

Adjustable range	-30.0 dB to +16.5 dB (maximum volume)
Default setting	+16.5 dB
Adjustment increments	5.0 dB

Initial Volume

Specify the initial volume level in Zone2 when this unit is turned on.

Adjustable range	Off, Mute, -80.0 dB to +16.5 dB
Default setting	Off
Adjustment increments	0.5 dB

Mono

Switches between stereo and monaural modes for Zone2 audio signal.

Off **(Default)**	Does not convert Zone2 audio signal to monaural sound.
On	Converts Zone2 audio signal to monaural sound.

Displaying the video on the TV monitor in Zone2

Monitor Out Assign

Sets the component video, S-video or video (MONITOR OUT/ ZONE OUT) jacks for the main zone, Zone2 use. When a TV monitor in the main zone is connected via one of the HDMI OUT jacks, MON.OUT jacks can be used to connect another monitor in Zone2.

Main **(Default)**	Outputs the video signals for the main zone.
Zone2	Outputs the video signals for Zone2.

Setting the party mode

Party Mode Set

In party mode, the main zone sources can be played in Zone2 simultaneously (☞p. 119). The party mode function can be enabled or disabled individually for Zone2.

Target : Zone2

Disable	Disables the party mode function in Zone2.
Enable **(Default)**	Enables the party mode function in Zone2.



Changing Zone2 scene name

Zone Scene Rename

Editing the name of the selected scene in Zone2.

1 **Use 11Cursor △ / ▽ repeatedly to select “Zone Scene Rename” and press 11ENTER.**

2 **Press 11ENTER.**

3 **Press 11Cursor △ / ▽ to select a scene you want to rename and press 11ENTER.**

4 **Press 11ENTER.**

Editing the name is available.

5 **Press 11Cursor △ / ▽ to select a character, and press 11Cursor ◁ / ▷ to enter the selected character.**

6 **Repeat step 5 to enter the desired scene name.**

7 **Confirm the zone name by pressing 11ENTER.**

8 **Press 11Cursor ▽ to select “OK” and press 11ENTER to register the new scene name.**

- To cancel the operation without applying changes, select “CANCEL” and press 11ENTER.
- To clear the characters entered in step 5, select “CLEAR” and press 11ENTER.
- Scene names may consist of up to 20 characters.

Changing Zone name

Zone Rename

Editing the name of the selected zone.

1 **Use 11Cursor △ / ▽ repeatedly to select “Zone Rename” and press 11ENTER.**

2 **Press 11Cursor △ / ▽ to select a zone you want to rename and press 11ENTER.**

3 **Press 11ENTER.**

Editing the name is available.

4 **Press 11Cursor △ / ▽ to select a character and press 11Cursor ◁ / ▷ to enter the selected character.**

5 **Repeat step 4 to enter the desired zone name.**

6 **Confirm the zone name by pressing 11ENTER.**

7 **Press 11Cursor ▽ to select “OK” and press 11ENTER to register the new zone name.**

- To cancel the operation without applying changes, select “CANCEL” and press 11ENTER.
- To clear the characters entered in step 4, select “CLEAR” and press 11ENTER.
- Zone names may consist of up to 9 characters.

Making the receiver easier to use

Function setup items

Auto Power Down	This unit enters standby mode if no operations are performed.
Input Assignment	Assigns the input jack to the selected input source.
Display Set	Specifies menu items displayed on TV screen and the front panel.
Trigger Output1	Specifies TRIGGER OUT 1 jack function.
Trigger Output2	Specifies TRIGGER OUT 2 jack function.
Memory Guard	Protects some settings against accidental modification.

11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN

Entering standby mode automatically when no operations are performed

Auto Power Down

If you do not operate this unit or use the remote control for an extended period of time, it will automatically go into standby mode (Auto Power Down function). This function's default setting is "Off." When you want to enable this function, set the amount of time to pass before this unit will enter standby.

4Hours	Goes into standby mode, when you have not operated this unit for four hours.
8Hours	Goes into standby mode, when you have not operated this unit for eight hours.
12Hours	Goes into standby mode, when you have not operated this unit for twelve hours.
Off **(Default)**	Auto Power Down function is disabled.

This unit starts a countdown of 30 seconds before entering the standby mode. Pressing any key of the remote control during the countdown cancels entering the standby mode and reset the timer.

Assigning component input and output jacks

Input Assignment

Assigns the coaxial or optical input jack(s) to the selected input source when this unit's initial settings do not correspond to your needs. Change the parameter to reassign the respective jacks and effectively connect more components.
Once the input jacks are reassigned, the corresponding component can be selected using the Input selector buttons.

Example: Assigning the OPTICAL input jack to "AV1."

1 Press 11ENTER to display the "Input Assignment" screen.

2 Press 11Cursor △ / ▽ / ◁ / ▷ to select the cell at the intersection with the "AV1" and "Coax/Opt" and then press 11ENTER.

3 Press 11Cursor ◁ / ▷ to select "③" and then press 11ENTER.

Select "None" to clear the existing assignment.

The choices indicate the following jacks.
①, ②, ⑥ : COAXIAL jacks
③, ④, ⑤ : OPTICAL jacks
Ⓐ, Ⓑ, Ⓒ, Ⓓ : COMPONENT VIDEO jacks
The choices indicate the jacks marked the same alphanumeric on the rear of this unit. For details on marks on the rear of this unit, refer to "Rear panel" (☞p. 10).

4 Press 11RETURN to apply change and return to the previous screen.

- A specific item cannot be selected more than once for the same type of jack.
- Only component, coaxial and optical jacks can be reassigned.
- Coaxial and optical jacks cannot be assigned to the input at the same time.

Specifying menu display

Display Set

Specify front panel display brightness and TV screen wall paper.

Front Panel Display

Specify front panel display brightness and message scroll pattern.

Dimmer	Adjustable range: -4 - 0 Reduce brightness of the front panel display. As the value is lowered, the panel display darkens.
Scroll	Selects the manner in which display scrolls when the total number of characters exceeds the display area on the front panel display. Select “Continue” for continuous scrolling of all characters. Select “Once” to scroll through all characters once and then halt scrolling for display of only the first 14 characters.

Wall Paper

Specify the wall paper displayed on the TV screen when no video signal is input. Select one that you prefer.

Picture 1-3	Displays an image on the TV screen when there is no video signal.
Gray	Displays a gray background on the TV screen when there is no video signal.

Setting TRIGGER OUT functions

Trigger Output1

Trigger Output2

Synchronizes TRIGGER OUT 1 or 2 jack function with the power status of each zone or input switching.

Trigger Mode

Specify timing of electronic signal transmission to the TRIGGER OUT 1 or 2 jack.

Power **(Default)**	TRIGGER OUT 1 or 2 jack function is synchronized with the power status of the zone specified with “Target Zone.”
Source	TRIGGER OUT 1 or 2 jack function is synchronized with input switching in the zone specified with “Target Zone.” Electronic signal is transmitted according to the “Target Source” setting.
Manual	Select this to manually switch the output level for electronic signal transmission with “Manual.”

Target Zone

Specify the zone with which TRIGGER OUT 1 or 2 jack function is synchronized.

Main	When “Trigger Mode” is set to “Power,” electronic signal transmission is synchronized with the power status of the main zone. When “Trigger Mode” is set to “Source,” electronic signal transmission is synchronized with input switching in the main zone.
Zone2	When “Trigger Mode” is set to “Power,” electronic signal transmission is synchronized with the power status of Zone2. When “Trigger Mode” is set to “Source,” electronic signal transmission is synchronized with input switching in Zone2.
All **(Default)**	When “Trigger Mode” is set to “Power,” electronic signal transmission is synchronized with the power status of the main zone or Zone2. When “Trigger Mode” is set to “Source,” electronic signal transmission is synchronized with input switching in the main zone or Zone2.

Target Source

Specify the output level of electronic signal transmitted each time input is switched.

Low ☀1	Terminates electronic signal transmission when the input source specified with this option is selected.
High **(Default)** ☀2	Electronic signal is transmitted when the input source specified with this option is selected.

This setting is available only when “Trigger Mode” is set to “Source.”

Manual

Manually switch the output level for electronic signal transmission. This setting can also be used to confirm proper function of the external component connected via the TRIGGER OUT 1 or 2 jack.

Low ☀1	Stops the electronic signal transmission.
High **(Default)** ☀2	Transmits the electronic signal.

This setting is available only when “Trigger Mode” is set to “Manual.”

Prohibiting setting changes

Memory Guard

Prohibits setting changes to prevent careless changes being made to the settings on Setup menu.

Off **(Default)**	Settings are not protected.
On	Prohibits changes to the settings on Setup menu until it is returned to “Off.” While set to “On,” the unit displays “Memory Guard!” when an attempt is made to change the settings.

Language

Select the language used for display of menus and messages. ☀3

Choices: English (English), 日本語 (Japanese), Français (French), Deutsch (German), Español (Spanish), Русский (Russian)

For details on selecting a language, refer to “Language selection” (☞p. 2).

☀1 : This unit outputs 0 V when selecting “Low.”
☀2 : This unit outputs 12 V when selecting “High.”
☀3 : Content window information is displayed in the language in which that information was released.



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

Confirming information of this unit (Information menu)

A variety of information for this unit can be displayed.

Selecting information

1 **Press 10ON SCREEN.**



2 **Use 11Cursor △ / ▽ to select “Information” and press 11ENTER.**

3 **Use 11Cursor ◁ / ▷ to select an Information menu and press 11ENTER.**

Audio Signal information

Displays information on the current audio signal.

Format	Signal format. When this unit is unable to detect a digital signal, it automatically switches to analog input.
Sampling	The number of samples taken per second from a continuous signal to make a discrete signal.
Channel	The number of source channels in the input signal (front/surround/LFE). For example, a multi-channel soundtrack with 3 front channels, 2 surround channels and LFE is displayed as “3/2/0.1”.
Bitrate	The number of bits passing a given point per second.
Dialogue	The dialogue normalization level preset to the current input bitstream signal.

- “---” is displayed when this unit cannot display the corresponding information.
- Some high-definition audio bitstream contents may not include the discrete surround back left and right channel signals, but are encoded at a sampling rate of 192 kHz.
- Even when direct bitstream output settings are applied, some players convert the Dolby TrueHD or Dolby Digital Plus bitstreams to the Dolby Digital bitstreams, while converting DTS-HD Master Audio or DTS-HD High Resolution Audio bitstreams to DTS bitstreams.

Video Signal information

Displays information on the current video signal.

HDMI Signal	Source video signal type and video signal output to this unit’s HDMI OUT 1-2 jacks.
HDMI Resolution	Input signal (analog or HDMI) and output signal (HDMI) resolution.
Analog Resolution	Resolution of the source video signal and the analog video signal output to this unit’s MONITOR OUT jacks.
HDMI Error	Error message for HDMI sources or connected HDMI devices (☞p. 120). This information is displayed only when the error come up.

HDMI Monitor information

Displays information on the TV screen connected to this unit’s HDMI OUT 1-2 jacks.

Interface	Displays information on the current connection interface.
Video Resolution	Displays the frequency for each video resolution of the TV currently connected.

Network information

Displays information on the network status. Refer to “Adjusting this unit’s network parameters” (☞p. 98) for details on setting the network status.

IP Address / Subnet Mask / Default Gateway	Displays the status of the current IP address assigned to this unit.
DNS Server (P) / DNS Server (S)	Displays the IP address of the primary and secondary DNS (Domain Name System) servers.
MAC Address	Displays the MAC address filter set to this unit.
Status	Displays the network status of this unit.

System information

Displays information on the current settings of the advanced setup.

Remote ID	Displays the Remote ID set to this unit.
TV Format	Displays the TV format set to this unit.
Speaker Impedance	Displays the speaker impedance set to this unit.
System ID	Displays the system ID of this unit.
Firmware Version	Displays the current version of the firmware installed to this unit.

When detecting the latest firmware over a network:
- exclamation point appears on the Information menu icon
- message indicating that the latest firmware is released appears in the System information

In this case, update the latest firmware by using “NETWORK” of “FIRM UPDATE” in Advanced Setup menu.

Zone information

Displays information on the currently selected input and the volume of Zone2.

Controlling the remote control to operate various functions

You can operate an external component such as TV and DVD player with the remote control of this unit by setting the code for external component (remote control code). The remote control code can be set for each input source. Individual setting allows you to switch external components seamlessly depending on the selected input source.



3 SOURCE ⏻
4 Input selector
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER
11 RETURN
11 DISPLAY
12 External component operation keys
12 TOP MENU
12 POP-UP MENU
13 Numeric keys
14 TV control keys
16 SOURCE/RECEIVER

Selecting input source connected to DVD player



Selecting input source connected to CD player



16 SOURCE/RECEIVER glows orange when operation of this unit is enabled.
16 SOURCE/RECEIVER glows green when operation of an external component is enabled.

Keys connecting external components

The remote control keys for controlling external components are available only when the external components have corresponding control keys.

3 SOURCE ⏻
Switches an external component on and off.

11 Cursor, 11 ENTER, 11 RETURN
Operates the menus of external components.

11 DISPLAY
Switches an external component display.

12 External component operation keys
Functions as a recording or playback key of an external component, or a menu display key.

13 Numeric keys
Functions as numeric keys of an external component.

14 TV control keys 1

14 INPUT	Switches video inputs of TV.
14 MUTE	Mutes TV volume temporarily.
14 TV VOL +/-	Controls the volume of TV.
14 TV CH +/-	Switches TV channels.
14 ⏻	Turns on and off TV.

Default remote control code settings

The following remote control codes are assigned to input sources at factory default settings. For a complete list of available remote control codes, refer to "Remote Control Code Search" in the CD-ROM.

Control area	Category	Manufacturer	Remote control code
AV1	Blu-ray player/ recorder	Yamaha	2064
AV2	—	—	—
AV3	—	—	—
AV4	—	—	—
AV5	—	—	—
AV6	—	—	—
AV7	—	—	—
V-AUX	—	—	—
AUDIO1	—	—	—
AUDIO2	CD player	Yamaha	5095
AUDIO3	—	—	—
AUDIO4	—	—	—
USB	—	—	—
NET	—	—	—
MULTI	—	—	—
DOCK	—	—	—
TUNER	—	—	—
PHONO	—	—	—

1 : When remote control codes for external components are registered with 4 Input selector or 14 ⏻ (14 TV control keys), the following operations are possible.
- When a TV remote control code is registered with 4 Input selector, the 11 Cursor, 11 DISPLAY, 12 TOP MENU, 12 POP-UP MENU, 13 Numeric keys and 14 TV control keys can be used to control the TV selected with 4 Input selector.
- When a remote control code for a device other than a TV is registered with 4 Input selector, keys including the 11 Cursor, 11 DISPLAY, 12 TOP MENU, 12 POP-UP MENU and 13 Numeric keys can be used to control external components, and the 14 TV control keys can be used to control the TV registered with 14 ⏻.
- When a TV remote control code is registered with 14 ⏻, only 14 TV control keys can be used to control the TV.

4 AV2
9 SCENE
13 Numeric keys
14 TV control keys
14 ⏻
15 CODE SET
16 SOURCE/RECEIVER

Registering remote control codes for external component operations

The following section describes how to register remote control code using an example of the registration of the remote control codes of a Yamaha BD player connected to AV2 jack.

- Perform each of the following steps within 1 minute. Settings will be automatically stopped if more than 1 minute passes since the last operation. To reset, repeat from step 2.
- Remote control code of an external component cannot be set from the name or model number of a unit. Use "Remote Control Code Search" in the CD-ROM to search the available remote control codes from the category or manufacturer of external components.
- If multiple remote control codes exist, first set the first code in the list, if it does not work then try the other codes.

1 Use "Remote Control Code Search" in the CD-ROM to search the available remote control codes from the category or manufacturer of external components.

"2064" can be used for a Yamaha BD player.

2 Press 15CODE SET using a pointed object such as the tip of a ballpoint pen.



3 Press 4AV2 to switch the input source to AV2. 1

Perform the following steps to register the selected input source here to the remote control code.

4 Enter a remote control code "2064" using 13Numeric keys. 2

2 → 0 → 6 → 4

Once the remote control code is registered successfully 16SOURCE/RECEIVER will blink twice.

Registration successful: blinks twice
Registration failed: blinks 6 times



- If the registration fails, repeat from step 2.
- In case of an external component with multiple remote control codes, the other remote control codes may be supported. Repeat from step 2 with the other remote control codes.

5 To switch between BD player linked to scene selections, press 9SCENE and at the same time press 4AV2 and hold it for approximately 3 seconds.

Then you can operate the external components by switching the input source to AV2, or selecting AV2 in the registered scene.

Same steps for operating other external components, press 9SCENE and at the same time press the input source key selected in step 3 and hold it for approximately 3 seconds.

1 : To control a TV that is not the input source, press 14⏻ (14TV control keys) in step 3.
2 : To control a TV that is not the input source, enter the TV remote control code in step 4.

13 Numeric keys
15 CODE SET
16 SOURCE/RECEIVER

Resetting all remote control codes

Resetting all remote control codes for external components to the initial factory settings.

Perform each of the following steps within 1 minute. Settings will be automatically stopped if more than 1 minute passes since the last operation. To reset, repeat from step 2.

1 Press 15CODE SET using a pointed object such as the tip of a ballpoint pen.

blinks twice



2 Press 16SOURCE/RECEIVER on the remote control.

3 Enter “9981” using 13Numeric keys.

9 → 9 → 8 → 1

Once the remote control code is reset successfully 16SOURCE/RECEIVER will blink twice.

Reset successful: blinks twice
Reset failed: blinks 6 times



If setup fails, repeat from step 1.

Extended functionality that can be configured as needed (Advanced Setup menu)

The Advanced Setup menu can be used for unit initialization and other useful extended functions. The Advanced Setup menu can be operated as follows.

Displaying/Setting the Advanced Setup menu

1 Switch this unit to the standby mode.

2 Press MAIN ZONE ⏻ while pressing and holding STRAIGHT on the front panel.

Release STRAIGHT when “ADVANCED SETUP” is displayed on the front panel display.
After a few seconds, the top menu items are displayed.



3 Press PROGRAM ◁ / ▷ repeatedly to select the item to be set from the following items.

In the Advanced Setup menu, you can set the following settings.

SPEAKER IMP.	Sets the impedance of speakers.
REMOTE SENSOR	Activate or deactivate the signal-receiving capability of the remote control sensor.
REMOTE CON AMP	Changes the remote control ID of a receiver.
TV FORMAT	Specifies the TV’s color encoding format.
MONITOR CHECK	Removes the up-scaling limitation on HDMI video output.
RECOV./BACKUP	Save and restore the settings of this unit.
INITIALIZE	Initializes various settings for this unit.
FIRM UPDATE	Update the firmware of this unit.
VERSION	Check the version of firmware currently installed on this unit.

4 Press STRAIGHT repeatedly to select the value you want to change.

5 Switch this unit to the standby mode, and then switch it on again.

The settings become effective and the unit is powered on.

Setting the impedance of speakers

Changes the unit settings depending on the impedance of the speakers connected. 💡1

6Ω MIN	Select the impedance when 6 Ω speakers are connected.
8Ω MIN **(Default)**	Select the impedance when speakers above 8 Ω are connected.

💡1 : For detailed procedures of speaker impedance settings, refer to “Changing speaker impedance” (☞p. 20).

13 Numeric keys
15 CODE SET
16 SOURCE/RECEIVER

Remote sensor

Activate or deactivate the signal-receiving capability of the remote control sensor on the front panel of this unit.

ON **(Default)**	Activate the signal-receiving capability of the remote control sensor
OFF	Deactivate the signal-receiving capability of the remote control sensor

"ON" is recommended in most cases.

Avoiding crossing remote control signals when using multiple Yamaha receivers

The remote control of the unit can only receive signals from a receiver which has an identical ID (remote control ID). When using multiple Yamaha AV receivers, you can set each remote control with a unique remote control ID for its corresponding receiver.
On the contrary, if you are setting the same remote control ID for all receivers, you can use one remote control to operate 2 receivers.

ID1 **(Default)**	Receives the remote control signals set in ID1.
ID2	Receives the remote control signals set in ID2.

ID1 is set for both remote control and receiver by default. To avoid crossing remote control, change the remote control ID for both remote control and receiver.

■ To change the remote control ID

Perform each of the following steps within 1 minute. Settings will be automatically stopped if more than 1 minute passes since the last operation. To reset, repeat from step 1.

1 Press 15CODE SET using a pointed object such as the tip of a ballpoint pen.

2 Press 16SOURCE/RECEIVER.

3 Enter the desired remote control ID code.

To switch to ID1:
Enter "5019" using 13Numeric keys.

To switch to ID2:
Enter "5020" using 13Numeric keys.

Once the remote control code is registered successfully 16SOURCE/RECEIVER will blink twice.

Registration successful: blinks twice
Registration failed: blinks 6 times



- If setup fails, repeat from step 1.
- Returns to ID1 after the remote control code is initialized (☞p. 108).

Changing TV format

Change the color encoding format of OSD to PAL (default) or NTSC, to match the format used by the TV connected via the HDMI OUT 1-2 or VIDEO (MONITOR OUT) jack.

Removing HDMI video output up-scaling limits

Removes the up-scaling limitation on video resolution when this unit and a TV are connected via HDMI jacks.
If a resolution supported by the monitor cannot be detected when configuring the up-scaling settings, this setting will remove the output limitation.

YES **(Default)**	Video output signals of a resolution not supported by the TV will not be transmitted.
SKIP	This unit ignores the TV's support capability and transmits input video signals to the TV.

Recovery and backup of the system settings

Save and restore the settings of this unit.

1 Press STRAIGHT repeatedly to select "BACKUP" or "RECOVERY" and press INFO on the front panel.



RECOVERY	Restores settings for this unit that have been saved.
BACKUP	Saves the current settings of this unit.

2 Press INFO to execute the "BACKUP" or "RECOVERY." 1

"RECOVERY" cannot be selected if settings have not be previously saved.

Initializing various settings for this unit

Initializes various settings stored in this unit and sets it back to default.
Select the items to be initialized from the following.

DSP PARAM	Initializes all parameters for the sound programs.
VIDEO	Resets video conversion settings (resolution/aspect ratio) in the Setup menu.
NETWORK	Resets the settings of network such as IP address or the account of vTuner.
ALL	Resets this unit to default factory settings.
CANCEL **(Default)**	Does not initialize.

When an option other than CANCEL is selected, the applicable default settings will be restored when the unit switches to standby mode.

1 : After performing "RECOVERY," turn off this unit.

Firmware update

Update the firmware of this unit. For details on updating the firmware, refer to information supplied with updates.
When this unit detects the latest firmware over a network, the message indicating that the firmware is released is displayed in the System information (☞p. 105).

1 Press STRAIGHT repeatedly to select “USB” or “NETWORK.”



USB **(Default)**	Updates the firmware of this unit using a USB flash drive.
NETWORK	Updates the firmware of this unit via network.

2 Press INFO to start update with the selected option.

- Do not use this feature unless the firmware must be updated.
- Be sure to read the information supplied with updates before updating firmware.

Firmware version

Check the version of firmware currently installed on this unit.

About the latest firmware

When installing the latest firmware, the new functions or fix of failure may be served.

- The latest firmware can be downloaded from our website.
- While displaying the ON SCREEN menu or “System” from Information menu, the information on the latest firmware is displayed via a network.

Using the HDMI Control function

This unit supports the HDMI Control function, which allows you to operate external components via HDMI. If devices that support HDMI Control (e.g., Panasonic VIERA Link-compatible TVs, DVD/Blu-ray Disc players, etc.) are connected ♛1, remote controls for those devices can be used to perform the following operations:

- Power synchronization (on/standby)
- Volume control, including Mute
- Changing the volume of the audio output signal device (either the TV or this unit)



NOTE

The following is an example of how to connect this unit, a TV, and a DVD/BD player. Follow the instructions in your TV and DVD/BD player manuals, as well as the ones written below.

- Set the TV's HDMI Control function to "On"
- Follow the AV amplifier connection instructions, and connect this unit to the TV

1 Connect the TV that supports the HDMI Control function to this unit's HDMI output jack.

2 Connect the DVD/BD player that supports the HDMI Control function to this unit's HDMI input jack.

3 Turn on the TV and this unit.

Refer to the TV's instruction manual on how to operate external components.

4 Set the TV and this unit's HDMI Control function to "On."

This unit	Confirm that "HDMI Control" is set to "On" (☞p. 96) and select the HDMI OUT jack connected to the TV in "Control Select" (☞p. 96). ♛2
TV and DVD/BD player	Check the instruction manuals for those devices.

5 Turn the TV off.

Other synchronized HDMI Control devices are turned off with the TV. If they are not synchronized, unplug the AC power cord of the TV.

6 Turn the TV on.

Confirm that this unit has turned on in conjunction with the TV. If it is still off, turn it on manually.

7 Change the TV's input setting to the input jack that is connected to this unit (e.g., AV1).

8 If DVD/BD player that supports the HDMI Control function are connected to this unit, turn them on.

This unit	Confirm that the input source for the DVD/BD players has been selected. If a different input source has been selected, change it manually.
TV and DVD/BD player	Confirm that the video signal from the player is being properly received by the TV.

Operations 1-8 will not be required more than twice. However, perform operations 1-8 again when switching the HDMI OUT jack using Control Select.

9 Confirm that this unit is properly synchronized with the TV through the following operations by using the TV remote control.

- Power On/Off
- Volume Control
- Switching between audio output devices

If this unit is not synchronized to the TV's power operations, check that the HDMI Control function is set to "On" for both devices.
If they will not properly synchronize, unplugging and re-plugging the AC power cords of this unit and the TV may solve the problem.

♛1 : We recommend that you use TVs and DVD/BD players from the same manufacturer whenever possible.
♛2 : The default setting for the HDMI Control function is "Off."



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

Switching the input source on this unit automatically when listening to TV audio

When the HDMI Control (☞p. 113) is operating properly, the input source of this unit is automatically changed to match operations carried out on the TV. When the TV is connected with HDMI OUT 1, the default input jack is AUDIO1. If the AUDIO1 optical digital jack is connected to the TV's audio output jack, then you can enjoy TV sound through this unit right away.



When the TV is connected with HDMI OUT 2, the default input jack is AUDIO3. If the AUDIO3 optical digital jack is connected to the TV's audio output jack, then you can enjoy TV sound through this unit right away.

To use other jacks to input audio signals from TV, carry out the following procedure.

1 Connect this unit and the TV with an HDMI cable.

2 Connect TV's audio output to this unit.

The input jacks listed below are available to input TV's audio signals. Use the same jack type as used for the TV.

TV output jack	Input jack
Optical digital audio output	AUDIO1
Coaxial digital audio output	AUDIO2
Analog stereo output	AUDIO1, AUDIO2, AUDIO3, or AUDIO4

Available input jacks



3 Press 10ON SCREEN. 1

4 Press 11Cursor △ / ▽ repeatedly to select "Setup" and press 11ENTER.



5 Press 11Cursor ◁ / ▷ repeatedly to select "HDMI" and press 11ENTER.

Continues to the next page

1 : Refer to the "Setting various functions (Setup menu)" (☞p. 88) for details on the Setup menu.



10 ON SCREEN
11 Cursor △ / ▽ / ◁ / ▷
11 ENTER

6 Make sure that "HDMI Control" is "On"

When "HDMI Control" is set to "Off," press 11ENTER and 11Cursor △ / ▽ to set to "On."

7 Press 11Cursor △ / ▽ to select "Control Select" and press 11ENTER.

8 Use 11Cursor △ / ▽ to select the HDMI OUT jack connected to the TV and press 11ENTER.

9 Press 11Cursor △ / ▽ to select "TV Audio Input" and press 11ENTER.

10 Use 11Cursor △ / ▽ to select the input jack connected in step 2.

11 Press 10ON SCREEN when you have finished changing the settings.

If the TV hereafter transmits audio output signals, this unit will automatically switch to the input source chosen in step 10.

Single HDMI cable input to TV audio with Audio Return Channel function

When using a TV that supports HDMI functions and Audio Return Channel function, audio/video output from this unit to the TV or audio output from the TV to this unit can be transmitted through a single HDMI cable (Audio Return Channel function). Audio signals transmitted from the TV to this unit can be assigned to any input source.

1 Connect this unit and the TV with an HDMI cable.



2 Press 10ON SCREEN. 1

3 Press 11Cursor △ / ▽ repeatedly to select "Setup" and press 11ENTER.



4 Press 11Cursor ◁ / ▷ repeatedly to select "HDMI" and press 11ENTER.

Continues to the next page

1 : Refer to the "Setting various functions (Setup menu)" (☞p. 88) for details on the Setup menu.



10 ON SCREEN
11 Cursor △ / ▽
11 ENTER
11 RETURN

5 **Make sure that "HDMI Control" is "On."**

When "HDMI Control" is set to "Off," press 11ENTER and 11Cursor △ / ▽ to set to "On."

6 **Press 11Cursor △ / ▽ to select "Control Select" and press 11ENTER.**

7 **Use 11Cursor △ / ▽ to select the HDMI OUT jack connected to the TV and press 11ENTER.**

8 **Press 11Cursor △ / ▽ to select "TV Audio Input" and press 11ENTER.**

9 **Use 11Cursor △ / ▽ to select the input source to which the HDMI audio signals will be assigned, and press 11RETURN.**

10 **Press 11Cursor △ / ▽ to select "ARC (Audio Return Channel)" and press 11ENTER.** 1

11 **Press 11Cursor ▽ to select "On."**

The Audio Return Channel function will turn on.

12 **Press 10ON SCREEN to close the Setup menu.**

If the TV hereafter transmits audio output signals, this unit will automatically switch to the input source chosen in step 9.

1 : While the Audio Return Channel function is on, the jack selected for the input source cannot be used.

Enjoying the contents in another room

This unit allows you to configure a multi-zone audio system. The Zone2 feature allows you to set this unit to reproduce separate input sources in the main zone and the second zone (Zone2). You can control this unit from the second zone using the supplied remote control.



Only analog signal can be sent to Zone2. If you want to output sound from Zone2, connect an external component to AV1-4, AUDIO1-4 or V-AUX by analog connection. For example, if you want to output sound from an HDMI DVD player in Zone2, you must connect the component to this unit by both HDMI and analog connections.

Connecting Zone2

You need the following additional equipment to use the multi-zone functions of this unit:

- An infrared signal receiver in the second zone.
- An infrared signal emitter in the main zone. This emitter transmits infrared signals from the remote control to a CD player or a DVD player, etc. in the main zone via the infrared signal receiver in the second zone.
- An amplifier and speakers in the second zone.
- A TV in the second zone.

Since there are many possible ways to connect and use this unit in a multi-zone configuration, we recommend that you consult with your nearest authorized Yamaha dealer or service center about the Zone2 connections that best meet your requirements.

When using the external amplifier

An amplifier located in the second zone can be connected to this unit as shown below.



To avoid unexpected noise, DO NOT USE the Zone2 feature with CDs encoded in DTS.

When using the internal amplifier of this unit

Connect the speakers in the second zone to the EXTRA SP jacks directly (☞p. 20).

Connecting zone video monitors

Connect the video monitor(s) in Zone2 to MONITOR OUT/ZONE OUT jacks. If you connect the multiple zone video monitors to these jacks, the video monitors play back the selected input source for the Zone2.

To assign the MONITOR OUT/ZONE OUT jacks to the main zone or Zone2, configure “Monitor Out Assign” (☞p. 99).



Controlling this unit with the remote control in another room

This unit is equipped with REMOTE IN and REMOTE OUT jacks. You can use these jacks to control this unit and other components from Zone2 (☞p. 33).

Some Yamaha models can be directly connected to the REMOTE jacks of this unit. These models may not require an infrared signal emitter. Up to 6 Yamaha components can be connected as shown below.





2 MAIN/ZONE2
4 Input selector
7 SLEEP
8 PARTY
9 SCENE
17 RECEIVER ⏻

Controlling Zone2

The remote control can be used to select and control Zone2 devices. The available operations are as follows:

- Selecting the input source of Zone2.
- Tuning into FM or AM when "TUNER" is selected as the input source of Zone2.
- Adjust the volume of Zone2 devices (when connected via the built-in amplifier).

Activating the Zone2 operation mode

Set 2 **MAIN/ZONE2** to ZONE2 before attempting to use the remote control to control Zone2 devices.

Operating Zone2

To enable and disable the audio output to Zone2

Press 17 **RECEIVER** ⏻.

To select an input source for Zone2

Press 4 **Input selector**.

Only the following sources are available for the Zone2.
AV1-4 (only analog audio input), V-AUX (only analog audio input), AUDIO1-4 (only analog audio input), PHONO, USB, NET, DOCK, TUNER

To use SCENE function for Zone2

Press and hold 9 **SCENE** key for about 3 seconds to register the current setting to the scene.
Press 9 **SCENE** key to load the registered setting.

The following settings can be registered for each scene of the Zone2.
Input, Master Volume, Tone Control

To enable the sleep timer for Zone2

Automatically switch the Zone2 device to standby mode after a specified period of time has elapsed (sleep timer). Press 7 **SLEEP** repeatedly to specify a time for the sleep timer function.

Adjusting Zone2 high-/low-frequency sound (Tone Control)

1 Press ZONE CONTROLS on the front panel.

2 Press TONE/BALANCE on the front panel repeatedly to select "Treble" or "Bass."

3 Press PROGRAM ◁ / ▷ to adjust the output level in the applicable frequency range.

Adjustable range	-10.0 dB to +10.0 dB
Adjustment increments	2.0 dB

The display returns to the previous display soon after the key is released.

Adjusting Zone2 front speaker balance

1 Press ZONE CONTROLS on the front panel.

2 Press TONE/BALANCE on the front panel repeatedly to select "Balance."

3 Press PROGRAM ◁ / ▷ to adjust balance.

The display returns to the previous display soon after the key is released.

Enjoying the music in all rooms

Use this feature to play main zone sources in Zone2 simultaneously. This feature is useful when you want to play back main sources as background music in a home party, etc. When using the party mode, set "Party Mode Set" to "Enable" (☞p. 99).

Press 8 PARTY to turn on or off the party mode.
"Party Mode On" or "Party Mode Off" appears on the front panel display or the TV screen.
While this unit is in the party mode, the PARTY indicators turn on in the front panel display.

- Input audio signals are mixed down to 2ch Stereo and output at the analog ZONE2 OUT jacks.
- Party mode can be turned on only when the power of main zone is turned on.
- Party mode automatically turns off when the power of main zone is turned off.

APPENDIX

Troubleshooting

Refer to the table below when this unit does not function properly.
If the problem you are experiencing is not listed below, or if the instructions below do not help, turn off this unit, disconnect the power cable, and contact the nearest authorized Yamaha dealer or service center.

General

Problem	Cause	Remedy	See page
The power will not turn on.	The protection circuitry operated 3 times consecutively.	As a safety precaution, when the protection circuitry operates 3 times consecutively, the capability to turn on the power is disabled. Contact your nearest Yamaha dealer or service center to request repair.	—
The unit enters standby mode soon after the power is turned on.	The power cable is not completely inserted.	Connect the power cable properly to an AC wall outlet.	—
	(When this unit is turned back on and "CHECK SP WIRES!" is displayed.) The protection circuitry has been activated because this unit was turned on while a speaker cable was shorted.	Make sure that all speaker cables between this unit and speakers are connected properly.	21
This unit cannot be turned off or does not work properly.	The internal microcomputer is hung-up due to an external electric shock (such as lightning or excessive static electricity) or by a drop in power supply voltage.	Disconnect the power cable from the AC wall outlet, wait about 30 seconds and then plug it in again.	—
	The batteries in the remote control may have lost their charge.	Replace all batteries.	12
The unit enters standby mode.	The protection circuitry has been activated because of a short circuit, etc.	Check that the speaker with an impedance of at least 6 Ω.	—
		Check that the speaker impedance settings are correct.	20
		Check that the speaker wires are not touching each other, then turn the unit back on.	—
	The sleep timer has turned off the unit.	Turn on the unit, and play the source again.	—

Problem	Cause	Remedy	See page
After display of a countdown on the front panel, the unit goes into standby mode.	If you do not use take any action, the Auto Power Down function operates.	Turn on the unit, and play the source again.	—
		In the Setup menu "Auto Power Down" ("Function" → "Auto Power Down"), increase the time until switching to standby mode, or turn off the Auto Power Down function.	101
No sound.	Incorrect input or output cable connections.	Connect the cables properly. If the problem persists, the cables may be defective.	27
	Speaker connections are not secure.	Secure the connections.	21
	The HDMI components connected to the unit do not support the HDCP copy protection standards.	Connect HDMI components that support the HDCP copy protection standards.	—
	The audio input into the device is set to playback through the TV.	In the Setup menu, set the "Amp" of "Audio Output" ("HDMI" → "Audio Output" → "Amp") to "On."	97
	No appropriate input source has been selected.	Select an appropriate input source with **Input selector**.	44
	The volume is turned down or muted.	Turn up the volume.	—
	Signals that this unit cannot reproduce are being input from a source component, such as a CD-ROM.	Use an input source that has signals that can be reproduced on this unit.	—

Problem	Cause	Remedy	See page
No picture.	The video signal output from this unit is not supported by a monitor connected to this unit via the HDMI OUT 1-2 jacks.	Displays the Advanced Setup menu and select “VIDEO” in “INITIALIZE” to reset the video parameters.	111
		Displays the Advanced Setup menu and set “MONITOR CHECK” to “YES.”	111
	An appropriate video input is not selected on the TV.	Select an appropriate video input on the TV.	—
No sound is output from a specific speaker.	The speaker is malfunctioning. Check the Speaker indicators on the front panel display. If the corresponding indicator lights up, connect another speaker and check if sound is output.	If sound is not output, the unit may be malfunctioning.	11
	The playback component or speakers are not connected properly.	Connect the cables properly. If the problem persists, the cables may be defective.	21, 27
	Output from that speaker is disabled.	Check the Speaker indicators on the front panel display. If the corresponding indicator is turned off, try the following. 1) Change to a different input source. 2) With the selected sound program, sound is not output from that speaker. Select another sound program. 3) “None” may have been selected for that speaker on this unit. Display “Speaker” in the Setup menu, and set respective parameters to enable output from that speaker (“Speaker” → “Manual Setup” → “Configuration”).	11, 90
	The volume of that speaker is set to the minimum in “Speaker” in the Setup menu.	Display “Speaker” in the Setup menu and adjust the volume (“Speaker” → “Manual Setup” → “Level”).	92
	(If hardly any sound comes from one channel) Speaker output balance is not set correctly.	Balance the volume of each speaker from “Level” in the Setup menu (“Speaker” → “Manual Setup” → “Level”).	92
	Sound may not be output from certain channels, depending on the input source or sound program.	Try another sound program.	47
Only the center speaker outputs substantial sound.	When a monaural source sound program is applied, for some surround decoders, sound from all channels is output from the center speaker.	Try another sound program.	47
No sound is heard from the presence speakers.	This unit is in straight decoding mode.	Press **STRAIGHT** to exit straight decoding mode.	48
	Sound may not be output from certain channels depending on input sources or sound programs.	Try another sound program.	47
No sound is heard from the surround speakers.	Sound may not be output from certain channels depending on input sources or sound programs.	Try another sound program.	47
No sound is heard from the surround back speakers.	“Extended Surround” in the Option menu is set to “Off,” or an input signal does not contain a surround back flag with “Extended Surround” set to “Auto.”	Set “Extended Surround” other than “Off” or “Auto.”	56
No sound is heard from the subwoofer.	A subwoofer is not connected, or it is inactive.	Check that a subwoofer is connected correctly, and from the Setup menu “Subwoofer” (“Speaker” → “Manual Setup” → “Configuration” → “Subwoofer”), set the subwoofer to “Use.”	21, 91
	The subwoofer is turned off.	Turn the subwoofer power on. If the subwoofer includes an Auto Power Off function, then lower the Auto Power Off sensitivity settings.	—
	The source does not contain LFE (☞p. 128) or low frequency signals.		—
The audio input sources cannot be played in the desired digital audio signal format.	The connected component is not set to output the desired digital audio signals.	Set the playback component properly referring to its instruction manual.	—

Problem	Cause	Remedy	See page
There is noise interference from digital or radio frequency equipment.	This unit is too close to other digital or radio frequency equipment.	Move this unit further away from such equipment.	—
Noise/hum noise is heard.	Incorrect cable connection. Connect the audio cables properly.	If the problem persists, the cables may be defective.	—
	A DTS-CD is being played back.	1) When only noise is output If a DTS bitstream signal is not properly input to this unit, only noise is output. Connect the playback component to this unit by digital connection and playback the DTS-CD. If the condition is not improved, the problem may results from the playback component. Consult the manufacturer of the playback component. 2) When noise is output during playback or skip operation Before playing back the DTS-CD, display the Input menu after selecting the input source and set “Decoder Mode” to “DTS.”	—
The volume cannot be increased, or the sound is distorted.	The component connected to the output jacks of this unit is not turned on.	When the component connected to the output jacks of this unit is not turned on, the sound may be distorted, or the volume may decreased due to the nature of AV receivers. Turn on all components connected to this unit.	—
	“Max Volume” is set to a low value.	Set it to a higher value.	94

HDMI™

Problem	Cause	Remedy	See page
The front panel display HDMI indicator is flashing.	An error with the HDMI connection has occurred.	Try re-inserting the HDMI cable.	—
		Confirm that HDMI video that is not supported by the unit is not being input (Information menu → “Video Signal information”).	104
No picture or sound.	The number of components is over the limit.	Disconnect some of the HDMI components.	—
	The connected HDMI component does not support high-bandwidth digital copyright protection (HDCP).	Connect an HDMI component that supports HDCP.	—
(When using HDMI Control function) TV sound is not output from this unit when operating the remote control of the TV.	The TV audio output is not connected to this unit, or the setting to match operations carried out on TV is not set.	Connect the TV audio output to this unit, and then select the connected input source in “TV Audio Input” (Setup menu → HDMI → TV Audio Input).	97
	(When using Audio Return Channel function) The Audio Return Channel function is not working.	Make sure that your TV supports Audio Return Channel. Set the Audio Return Channel function to on (Setup menu → HDMI → ARC (Audio Return Channel)).	96

Tuner (FM/AM)

FM

Problem	Cause	Remedy	See page
FM stereo reception is noisy.	You are too far from the station transmitter, or the input from the antenna is weak.	Check the antenna connections.	36
		Switch to monaural mode.	61
		Replace the outdoor antenna with a more sensitive multi-element antenna.	—
There is distortion, and clear reception cannot be obtained even with a good FM antenna.	There is multi-path interference.	Adjust the antenna height or orientation, or place it in a different location.	—
The desired station cannot be tuned into with the automatic tuning method.	You are in an area far from a station, or input from the antenna is weak.	Replace the outdoor antenna with a more sensitive multi element antenna.	—
		Use **TUNING** ⌃⌃ / ⌄⌄ to manually select the station.	59
“No Presets” is displayed.	No preset stations are registered.	Register stations you want to listen to as preset stations before operation.	59
“Wrong Station” is displayed.	An invalid FM/AM frequency has been input.	Input a frequency that can be received.	—

AM

Problem	Cause	Remedy	See page
The desired station cannot be tuned into with the automatic tuning method.	The signal is weak, or the antenna connections are loose.	Adjust the AM loop antenna orientation.	—
		Use the manual tuning method.	59
Automatic station preset does not work.	Automatic station preset is not available for AM stations.	Use manual station preset.	59
Continuous crackling and hissing noises are heard.	The supplied AM loop antenna is not connected.	Connect the AM loop antenna correctly even if you use an outdoor antenna.	36
	The noises may be caused by lightning, fluorescent lamps, motors, thermostats, or other electrical equipment.	It is difficult to completely eliminate noise, but it can be reduced by installing and properly grounding an outdoor AM antenna.	—
Buzzing and whining noises are heard.	A TV set is being used nearby.	Move this unit away from the TV set.	—

USB and Network

Problem	Cause	Remedy	See page
"No Device" is displayed even when a USB device is present.	This unit recognized the USB storage device as an illegal device.	Turn this unit off then on again.	—
The music files and directories in the USB device cannot be viewed.	The music files and directories are placed in locations other than the FAT area.	Place music files and directories in the FAT area.	—
	You are attempting to browse directory hierarchies of over 8 levels or a directory with more than 500 files.	Modify the data structure on your USB device.	—
The PC server/ Internet Radio does not function properly.	The IP address is not set properly.	Set the DHCP server function of the router to ON. Alternately, perform manual configuration according to the current operating environment.	98
	The network cable is not connected.	Connect it properly.	34
The music in the PC server cannot be played back.	The PC does not have Windows Media Player installed in it.	Install Windows Media Player in the PC.	—
	The music is recorded in a format that cannot be played on this unit. This unit cannot play music formats other than WMA, MP3, MPEG-4 AAC, FLAC and WAV (PCM format). Also note that it cannot play certain music files even if these are recorded in the WMA, MP3, MPEG-4 AAC, FLAC, or WAV format.	Play music recorded in a format that this unit is compatible with.	—
The Internet Radio cannot be played.	The firewall of the network device is activated. The Internet Radio can be played only when it passes through the port designated by each radio station. The port number is variable depending on radio station.	Check the firewall setting of the network device.	—
	Connection to the Internet is disconnected.	Check the configuration of the network device, and then contact the network connection provider.	—

Display	Cause	Remedy	See page
Connect error	There is a problem with the signal path from your network to this unit.	Check the connection between this unit and the LAN port on your router or hub.	34
		Make sure your router is properly connected and turned on. Also, make sure your modem is properly connected and turned on when you are attempting to listen to Internet Radio.	34
Disconnected	Your USB storage device or USB portable audio player has been disconnected from the USB port of this unit.	Check the connection between this unit and your USB storage device or USB portable audio player.	—
	The PC server previously connected to this unit no longer exists.	Connect this unit to the available PC server.	34
No Device	There is a problem with the signal path from your USB storage device or USB portable audio player to this unit.	Turn off this unit and reconnect your USB storage device or USB portable audio player to the USB port of this unit.	35
		Try resetting your USB storage device or USB portable audio player.	—

Display	Cause	Remedy	See page
Access error	This unit cannot access your USB storage device or USB portable audio player.	Try another USB storage device or USB portable audio player.	—
	There is a problem with the signal path from your USB storage device or USB portable audio player to this unit.	Turn off this unit and reconnect your USB storage device or USB portable audio player to the USB port of this unit.	35
		Try resetting your USB storage device or USB portable audio player.	—
Access denied	The PC you are attempting to connect has denied connection.	Configure the sharing setting of Window Media Player 11/12 and select this unit as a device to which music contents are shared.	62
Unable to play	This unit cannot play back the songs currently stored on your PC.	Make sure Windows Media Player is installed on your PC.	—
		Check that the songs currently stored on your PC are playable (MP3, WMA, MPEG-4 AAC, and WAV).	—
		Store some other playable music files (MP3, WMA, MPEG-4 AAC, and WAV) on your PC.	—
	The network may be overloaded with heavy traffic, and playback is interrupted.	Try preparing a network exclusively for use with this unit to separate it from general network traffic.	—
List updated	The list of the contents stored on your PC server has been updated.		—
Bookmark On	The desired Internet Radio station has been added to the Bookmarks list.		—
Bookmark Off	The stored Internet Radio station has been removed from the Bookmarks list.		—
USB Overloaded	Over current passes through the connected USB device.	Turn off this unit and then disconnect the USB device. If the message appears when you connect the USB device again, this unit may not compatible with the USB device.	—

iPod™/iPhone™

Display	Cause	Remedy	See page
Loading...	The unit is in the process of recognizing the connection with your iPod/iPhone.		—
	The unit is in the middle of acquiring song lists from your iPod/iPhone.		—
Connect error	There is a problem with the signal path from your iPod/iPhone to the unit.	Turn off the unit and reconnect the Universal Dock for iPod to the DOCK jack of the unit.	69
		Remove your iPod/iPhone from the Universal Dock for iPod and then place it back in the dock.	69
Unknown iPod	The iPod/iPhone being used is not supported by the unit.	Connect an iPod/iPhone supported by the unit.	—
iPod connected	Your iPod/iPhone is properly placed in the Universal Dock for iPod.		—
	Your iPod/iPhone is properly placed in the Wireless System for iPod and connected with this unit via wireless transmission.		71
Disconnected	Your iPod/iPhone is removed from the Universal Dock for iPod.		—
	Your iPod/iPhone is disconnected with this unit via wireless transmission.		—
Unable to play	The unit cannot playback the songs currently stored on your iPod/iPhone.	Check that songs are currently stored on your iPod/iPhone.	—

Bluetooth™

Display	Cause	Remedy	See page
Searching...	The Yamaha Bluetooth Wireless Audio Receiver and the Bluetooth component are in the process of pairing.		—
	The Yamaha Bluetooth Wireless Audio Receiver and the Bluetooth component are in the process of establishing a connection.		—
Completed	The pairing is completed.		—
Canceled	The pairing is canceled.		—
BT connected	The connection between the Yamaha Bluetooth Wireless Audio Receiver and the Bluetooth component is established.		—
Disconnected	The Bluetooth component is disconnected from the Yamaha Bluetooth Wireless Audio Receiver.		—
Not found	The Bluetooth component is not found.	During pairing: – pairing must be performed on the Bluetooth component and this unit simultaneously. Check if the Bluetooth component is in pairing mode. During connecting: – check if the Bluetooth component is turned on. – check if the Bluetooth component is within 10 m of the Yamaha Bluetooth Wireless Audio Receiver.	—
	Pairing may not have been achieved.	Try pairing again.	73

Remote control

Problem	Cause	Remedy	See page
The remote control does not work or function properly.	Wrong distance or angle.	The remote control will function within a maximum range of 6 m, and no more than 30 degrees off-axis from the front panel.	—
	Direct sunlight or lighting (from an inverter type of fluorescent lamp, strobe light, etc.) is striking the remote control sensor of this unit.	Adjust the lighting angle, or reposition this unit.	—
	The batteries are weak.	Replace all batteries.	12
	The remote control ID of the remote control and this unit do not match.	Match the remote control ID of this unit and the remote control.	106, 110
The battery of remote control runs out immediately.	The power of battery is not enough.	Replace the battery with alkaline battery.	—
External components cannot be controlled using the remote control.	The remote control code is not correctly set.	Set the remote control code correctly using "Remote control code search" on the CD-ROM.	—
		Try setting another code for the same manufacturer using "Remote control code search" on the CD-ROM.	—
		If this unit does not work when you press **Cursor △ / ▽ / ◁ / ▷**, do the following. When the key does not work during DVD disc menu operation: press the **Input selector** again. When there is no response with remote control operation of the Option menu/Setup menu: press **SOURCE/RECEIVER** (it should glow orange) and try operating the remote control again.	—
	Even if the remote control code is correctly set, there are some models that do not respond to the remote control.		—

Glossary

Audio information

Audio and video synchronization (Lipsync)

Lip sync, an abbreviation for lip synchronization, is a technical term that involves both a problem and a capability of maintaining audio and video signals synchronized during post-production and transmission. Whereas the audio and video latency requires complex end-user adjustments, HDMI version 1.3 incorporates an automatic audio and video syncing capability that allows devices to perform this synchronization automatically and accurately without user interaction.

Bi-amplification connection (Bi-amp)

A bi-amplification connection uses two amplifiers for a speaker. One amplifier is connected to the woofer section of a loudspeaker while the other is connected to the combined mid and tweeter section. With this arrangement each amplifier operates over a restricted frequency range. This restricted range presents each amplifier with a much simpler job and each amplifier is less likely to influence the sound in some way.

Dolby Digital

Dolby Digital is a digital surround sound system that gives you completely independent multi-channel audio. With 3 front channels (front L/R and center), and 2 surround stereo channels, Dolby Digital provides 5 full-range audio channels. With an additional channel especially for bass effects, called LFE (Low Frequency Effect), the system has a total of 5.1-channels (LFE is counted as 0.1 channel). By using 2-channel stereo for the surround speakers, more accurate moving sound effects and surround sound environment are possible than with Dolby Surround. The wide dynamic range from maximum to minimum volume reproduced by the 5 full-range channels and the precise sound orientation generated using digital sound processing provide listeners with unprecedented excitement and realism. With this unit, any sound environment from monaural up to a 5.1-channel configuration can be freely selected for your enjoyment.

Dolby Digital Surround EX

Dolby Digital EX creates 6 full-bandwidth output channels from 5.1-channel sources. For the best results, Dolby Digital EX should be used with movie sound tracks recorded with Dolby Digital Surround EX. With this additional channel, you can experience more dynamic and realistic moving sound especially with scenes with “fly-over” and “flyaround” effects.

Dolby Digital Plus

Dolby Digital Plus is an advanced audio technology developed for high-definition programming and media including HD broadcasts, and Blu-ray Disc. Selected as an optional audio standard for Blu-ray Disc, this technology delivers multichannel sound with discrete channel output. Supporting bitrates up to 6.0 Mbps, Dolby Digital Plus can carry up to 7.1 discreet audio channels simultaneously. Supported by HDMI version 1.3 and designed for the optical disc players and AV receivers/amplifiers of the future, Dolby Digital Plus also remains fully compatible with the existing multichannel audio systems that incorporate Dolby Digital.

Dolby Pro Logic II

Dolby Pro Logic II is an improved technique used to decode vast numbers of existing Dolby Surround sources. This new technology enables a discrete 5-channel playback with 2 front left and right channels, 1 center channel, and 2 surround left and right channels, instead of only 1 surround channel for conventional Pro Logic technology. There are three modes available: “Music mode” for music sources, “Movie mode” for movie sources, and “Game mode” for game sources.

Dolby Pro Logic IIx

Dolby Pro Logic IIx is a new technology enabling discrete multichannel playback from 2-channel or multi-channel sources. There are three modes available: “Music mode” for music sources, “Movie mode” for movie sources (for 2-channel sources only) and “Game mode” for game sources.

Dolby TrueHD

Dolby TrueHD is an advanced lossless audio technology developed for high-definition disc-based media including Blu-ray Disc. Selected as an optional audio standard for Blu-ray Disc, this technology delivers sound that is bit-for-bit identical to the studio master, offering a high-definition home theater experience. Supporting bitrates up to 18.0 Mbps, Dolby TrueHD can carry up to 8 discrete channels of 24-bit/96 kHz audio simultaneously. Dolby TrueHD also remains fully compatible with the existing multichannel audio systems and retains the metadata capability of Dolby Digital, allowing dialog normalization and dynamic range control.

DTS 96/24

DTS 96/24 offers an unprecedented level of audio quality for multichannel sound on DVD video, and is fully backward-compatible with all DTS decoders. “96” refers to a 96 kHz sampling rate compared to the typical 48 kHz sampling rate. “24” refers to 24-bit word length. DTS 96/24 offers sound quality transparent to the original 96/24 master, and 96/24 5.1-channel sound with full-quality full-motion video for music programs and motion picture soundtracks on DVD video.

DTS Digital Surround

DTS digital surround was developed to replace the analog soundtracks of movies with a 5.1-channel digital sound track, and is now rapidly gaining popularity in movie theaters around the world. DTS, Inc. has developed a home theater system so that you can enjoy the depth of sound and natural spatial representation of DTS digital surround in your home. This system produces practically distortion-free 6-channel sound (technically, front left and right, center, surround left and right, and LFE 0.1 (subwoofer) channels for a total of 5.1 channels). This unit incorporates a DTS-ES decoder that enables 6.1-channel reproduction by adding the surround back channel to the existing 5.1-channel format.

DTS Express

This is an audio format for next-generation optical discs such as Blu-ray discs. It uses optimized low bit rate signals for network streaming. In the case of a Blu-ray disc, this format is used with secondary audio, enabling you to enjoy the commentary of the movie producer via the Internet while playing the main program.

DTS-HD High Resolution Audio

DTS-HD High Resolution Audio is a high resolution audio technology developed for high-definition disc-based media including Blu-ray Disc. Selected as an optional audio standard for Blu-ray Disc, this technology delivers sound that is virtually indistinguishable from the original, offering a high-definition home theater experience.
Supporting bitrates up to 6.0 Mbps for Blu-ray Disc, DTS-HD High Resolution Audio can carry up to 7.1 discrete channels of 24-bit/96 kHz audio simultaneously.
DTS-HD High Resolution Audio also remains fully compatible with the existing multichannel audio systems that incorporate DTS Digital Surround.

DTS-HD Master Audio
DTS-HD Master Audio is an advanced lossless audio technology developed for high-definition disc-based media including Blu-ray Disc. Selected as an optional audio standard for Blu-ray Disc, this technology delivers sound that is bit-for-bit identical to the studio master, offering a high-definition home theater experience.
Supporting bitrates up to 24.5 Mbps for Blu-ray Disc, DTS-HD Master Audio can carry up to 7.1 discrete channels of 24-bit/96 kHz audio simultaneously. Supported by HDMI version 1.3 and designed for the optical disc players and AV receivers/amplifiers of the future, DTS-HD Master Audio also remains fully compatible with the existing multichannel audio systems that incorporate DTS Digital Surround.

DTS Neo:6
Neo:6 decodes the conventional 2-channel sources for 6-channel playback by the specific decoder. It enables playback with the fullrange channels with higher separation just like digital discrete signal playback. There are two modes available: “Music mode” for music sources and “Cinema mode” for movie sources.

DSD
Direct Stream Digital (DSD) technology stores audio signals on digital storage media, such as Super Audio CDs. Using DSD, signals are stored as single bit values at a high-frequency sampling rate of 2.8224 MHz, while noise shaping and oversampling are used to reduce distortion, a common occurrence with very high quantization of audio signals. Due to the high sampling rate, better audio quality can be achieved than that offered by the PCM format used for normal audio CDs. The frequency is equal to or higher than 100 kHz and the dynamic range is 120 dB. This unit can transmit or receive DSD signals input from the HDMI jack.

FLAC
This is a file format for lossless audio data compression. FLAC is inferior to lossy compression formats in compression rate but provides higher audio quality.

MP3
One of the audio compression methods used by MPEG. It employs the irreversible compression method, which achieves a high compression rate by thinning out the data of hardly audible part to the human ears. It is said to be capable of compressing the data quantity by about 1/11 (128 kbps) while maintaining a similar audio quality to music CD.

MPEG-4 AAC
An MPEG-4 audio standard. As it allows compression of data at a bit rate lower than that of MPEG-2 AAC, it is used among others for mobile telephones, portable audio players and other low-capacity devices requiring high sound quality. In addition to the above types of devices, MPEG-4 AAC is also used to distribute contents on the Internet, and as such is supported by computers, media servers and many other devices.

LFE 0.1 channel
This channel reproduces low-frequency bass signals, and has a frequency range from 20 Hz to 120 Hz. This channel is counted as 0.1, because it only enforces a low-frequency range compared to the full-range reproduced by the other 5-channels in Dolby Digital or DTS 5.1-channel systems.

PCM (Linear PCM)
Linear PCM is a signal format under which an analog audio signal is digitized, recorded and transmitted without using any compression. This is used as a method of recording CDs and DVD audio. The PCM system uses a technique for sampling the size of the analog signal per very small unit of time. Standing for “Pulse Code Modulation,” the analog signal is encoded as pulses and then modulated for recording.

Sampling frequency and number of quantized bits
When digitizing an analog audio signal, the number of times the signal is sampled per second is called the sampling frequency, while the degree of fineness when converting the sound level into a numeric value is called the number of quantized bits. The range of rates that can be played back is determined based on the sampling rate, while the dynamic range representing the sound level difference is determined by the number of quantized bits. In principle, the higher the sampling frequency, the wider the range of frequencies that can be played back, and the higher the number of quantized bits, the more finely the sound level can be reproduced.

WAV
Windows standard audio file format, which defines the method of recording the digital data obtained by converting audio signals. It does not specify the compression (coding) method so a desired compression method can be used with it. By default, it is compatible with the PCM method (no compression) and some compression methods including the ADPCM method.

WMA
An audio compression method developed by Microsoft Corporation. It employs the irreversible compression method, which achieves a high compression rate by thinning out the data of hardly audible part to the human ears. It is said to be capable of compressing the data quantity by about 1/22 (64 kbps) while maintaining a similar audio quality to music CD.

Sound program information

CINEMA DSP
Since the Dolby Surround and DTS systems were originally designed for use in movie theaters, their effect is best felt in a theater having many speakers designed for acoustic effects. Since home conditions, such as room size, wall material, number of speakers, and so on, can differ so widely, it is inevitable that there are differences in the sound that is heard. Based on a wealth of actually measured data, Yamaha CINEMA DSP uses Yamaha’s original DSP technology to combine Dolby Pro Logic, Dolby Digital, and DTS systems to provide the audiovisual experience of a movie theater in the listening room of your own home.

CINEMA DSP 3D
The actually measured sound field data contain the information of the height of the sound images. CINEMA DSP 3D feature achieves the reproduction of the accurate height of the sound images so that it creates the accurate and intensive stereoscopic sound fields in a listening room.

Compressed music enhancer
The Compressed music enhancer feature of this unit enhances your listening experience by regenerating the missing harmonics in compression artifacts. As a result, it compensates for flattened complexity due to the loss of high-frequency fidelity as well as lack of bass due to the loss of low-frequency bass, providing improved performance for the overall sound system.

SILENT CINEMA
Yamaha has developed a natural, realistic sound effect DSP algorithm for headphones. Parameters for headphones have been set for each sound program, so that accurate representations of all the sound programs can be enjoyed on headphones.

Virtual CINEMA DSP
Yamaha has developed a Virtual CINEMA DSP algorithm that allows you to enjoy DSP surround effects even without any surround speakers, by using virtual surround speakers. It is even possible to enjoy Virtual CINEMA DSP using a minimal two-speaker system that does not include a center speaker.

Video information

Component video signal

With the component video signal system, the video signal is separated into the Y signal for luminance and the PB and PR signals for chrominance. Color can be reproduced more faithfully with this system because each of these signals is independent. The component signal is also called the “color difference signal” because the luminance signal is subtracted from the color signal. A monitor with component input jacks is required in order to output component signals.

Composite video signal

With the composite video signal system, the video signal comprises the three basic elements of a video picture: color, brightness and synchronization data. A composite video jack on a video component transmits these three elements combined.

Deep Color

Deep Color refers to the use of various color depths in displays, up from the 24-bit depths in previous versions of the HDMI specification. This extra bit depth allows HDTVs and other displays go from millions of colors to billions of colors and eliminate on-screen color banding for smooth tonal transitions and subtle gradations between colors. The increased contrast ratio can represent many times more shades of gray between black and white. Also, Deep Color increases the number of available colors within the boundaries defined by the RGB or YCbCr color space.

HDMI

HDMI (High-Definition Multimedia Interface) is the first industry supported, uncompressed, all-digital audio/video interface. Providing an interface between any sources (such as set-top boxes or AV receivers) and audio/video monitor (such as digital television), HDMI supports standard, enhanced or high-definition video as well as multichannel digital audio using a single cable. HDMI transmits all ATSC HDTV standards and supports 8-channel digital audio, with bandwidth to spare to accommodate future enhancements and requirements.

When used in combination with HDCP (High-bandwidth Digital Content Protection), HDMI provides a secure audio/video interface that meets the security requirements of content providers and system operators. For further information on HDMI, visit the HDMI website at “http://www.hdmi.org/.”

S-video signal

With the S-video signal system, the video signal normally transmitted using a pin cable is separated and transmitted as the Y signal for the luminance and the C signal for the chrominance through the S-video cable. Using the S-VIDEO jack eliminates video signal transmission loss and allows recording and playback of even more beautiful images.

“x.v.Color”

A color space standard supported by HDMI version 1.3. It is a more extensive color space than sRGB, and allows the expression of colors that could not be expressed before. While remaining compatible with the color gamut of sRGB standards, “x.v.Color” expands the color space, and can thus produce more vivid, natural images. It is particularly effective for still pictures and computer graphics.

Compatibility of the input and output video signals

Analog-to-HDMI video conversion is performed according to resolution of video signals as shown below. Analog-to-analog video conversion is also possible when “Analog to Analog Conversion” is set to “On” (☞p. 95).

✓: available conversion

		HDMI output					COMPONENT VIDEO output				S-VIDEO output	VIDEO output
	Resolution	480i/576i	480p/576p	720p	1080i	1080p	480i/576i	480p/576p	720p	1080i	480i/576i	480i/576i
HDMI input	480i/576i	✓	✓	✓	✓	✓						
	480p/576p		✓	✓	✓	✓						
	720p			✓								
	1080i				✓							
	1080p					✓						
COMPONENT VIDEO input	480i/576i	✓	✓	✓	✓	✓	✓				✓	✓
	480p/576p		✓	✓	✓	✓		✓				
	720p			✓					✓			
	1080i				✓					✓		
S-VIDEO input	480i/576i	✓	✓	✓	✓	✓	✓				✓	✓
VIDEO input	480i/576i	✓	✓	✓	✓	✓	✓				✓	✓

Information on HDMI™

■ HDMI signal compatibility

Audio signals

Audio signal types	Audio signal formats	Compatible media
2ch Linear PCM	2ch, 32-192 kHz, 16/20/24 bit	CD, DVD-Video, DVD-Audio, etc.
Multi-ch Linear PCM	8ch, 32-192 kHz, 16/20/24 bit	DVD-Audio, Blu-ray Disc, HD DVD, etc.
DSD	2/5.1ch, 2.8224 MHz, 1 bit	SACD, etc.
Bitstream	Dolby Digital, DTS	DVD-Video, etc.
Bitstream (High definition audio)	Dolby TrueHD, Dolby Digital Plus, DTS-HD Master Audio, DTS-HD High Resolution Audio, DTS Express	Blu-ray Disc, HD DVD, etc.

- If the input source component can decode the bitstream audio signals of audio commentaries, you can playback the audio sources with the audio commentaries mixed down by using the digital audio input (optical or coaxial) connections.
- Refer to the supplied instruction manuals of the input source component, and set the component appropriately.

NOTES

- When CPPM copy-protected DVD-Audio is played back, video and audio signals may not be output, depending on the type of the DVD player.
- This unit is not compatible with HDCP-incompatible HDMI or DVI components.
- Refer to the supplied instruction manuals for details.
  To decode audio bitstream signals on this unit, set the input source component appropriately so that the component outputs the bitstream audio signals directly (does not decode the bitstream signals on the component).
- This unit is not compatible with the audio commentary features (for example, the special audio contents downloaded via Internet) of Blu-ray Disc or HD DVD. This unit does not playback the audio commentaries of the Blu-ray Disc or HD DVD content.

Video signals

This unit is compatible with the video signals of the following resolutions:

- 480i/60 Hz
- 576i/50 Hz
- 480p/60 Hz
- 576p/50 Hz
- 720p/60 Hz, 50 Hz
- 1080i/60 Hz, 50 Hz
- 1080p/60 Hz, 50 Hz, 24 Hz

About trademarks

Manufactured under license from Dolby Laboratories. Dolby, Pro Logic and the double-D symbol are trademarks of Dolby Laboratories.

Manufactured under license under U.S. Patent #'s:
5,451,942; 5,956,674; 5,974,380; 5,978,762; 6,226,616; 6,487,535; 7,212,872; 7,333,929; 7,392,195; 7,272,567 & other U.S. and worldwide patents issued & pending. DTS and the Symbol are registered trademarks, & DTS-HD, DTS-HD Master Audio, and the DTS logos are trademarks of DTS, Inc. Product includes software. © DTS, Inc. All Rights Reserved.

iPod™, iPhone™

"iPod" is a trademark of Apple Inc., registered in the U.S. and other countries. "iPhone" is a trademark of Apple Inc.

MPEG Layer-3 audio coding technology licensed from Fraunhofer IIS and Thomson.

This receiver supports network connections.

Bluetooth™

Bluetooth is a registered trademark of the Bluetooth SIG and is used by Yamaha in accordance with a license agreement.

"HDMI," the "HDMI" logo and "High-Definition Multimedia Interface" are trademarks, or registered trademarks of HDMI Licensing LLC.

x.v.Color™

"x.v.Color" is a trademark of Sony Corporation.

"SILENT CINEMA" is a trademark of Yamaha Corporation.

Windows XP, Windows Vista, Windows 7, Windows Media Audio, Windows Media Connect and Windows Media Player are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Specifications

■ Input

- Analog Audio
  - RCA 10
    - AV1-4, AUDIO1-4, PHONO, VIDEO AUX
  - MULTI CH INPUT 8ch
    - FRONT L/R, CENTER, SURROUND L/R, SURROUND BACK L/R, SUBWOOFER
- Digital Audio
  - Optical ..... 4 (AV3-4, AUDIO1, VIDEO AUX)
  - Coaxial 3 (AV1-2, AUDIO2)
- Analog Video
  - Composite ..... 5 (AV1-4, VIDEO AUX)
  - S-video ..... 5 (AV1-4, VIDEO AUX)
  - Component 4 (AV1-4)
- Other
  - DOCK ..... 1 (Audio L/R, Composite Video, S-video)

■ Output

- Analog Audio
  - SPEAKERS ..... 9ch (7ch + Extra 2ch)
    - FRONT L/R, CENTER, SURROUND L/R, SURROUND BACK/BI-AMP L/R, EXTRA SP (ZONE2/F.PRESENCE L/R)
  - PRE OUT 9ch
    - FRONT L/R, CENTER, SURROUND L/R, SURROUND BACK L/R, SUBWOOFER [Mono 2ch]
  - AV OUT 1
  - ZONE2 OUT 1
- Digital Audio
  - Optical ..... 1 (AV OUT)
- Analog Video
  - MONITOR OUT/ZONE OUT
    - Composite 1
    - S-video 1
    - Component 1
  - AV OUT
    - Composite 1
    - S-video 1

■ HDMI

- Input ..... 8 (AV1-7, VIDEO AUX)
- Output ..... 2 (HDMI OUT)
- HDMI Specification
  - Deep Color 30/36 bit, “x.v.Color,” Auto Lips Sync, HD Audio, ARC (Audio Return Channel), 3D
- Audio Format
  - Dolby Digital, DTS, DSD 6ch, Dolby Digital Plus, Dolby TrueHD, DTS-HD, PCM 2ch-8ch
- Content Protection ..... HDCP compatible

■ Tuner

- Analog Tuner
  - FM/AM ..... 1 (TUNER)
- [U.S.A. model] HD Radio with iTunes Tagging ..... 1 (TUNER)
- [U.S.A. model] Satellite Radio Ready
  - SIRIUS Radio ..... 1 (SIRIUS)

■ Network

- USB (USB1.1 Full Speed) 1
  - Device Type ..... USB Mass Storage Class, MTP
  - Audio Format ..... MP3, WMA, WAV, MPEG-4 AAC, FLAC
  - Max Audio Support fs ..... 48 kHz/24 bit
  - Cover Art Format ..... PNG, JPEG
- Ethernet (100Base-TX/10Base-TX) 1
  - Internet Radio
    - Audio Format ..... MP3, WMA
  - PC Server
    - Audio Format ..... MP3, WMA, WAV, MPEG-4 AAC, FLAC
    - Max Audio Support fs ..... 96 kHz/24 bit
    - Cover Art Format ..... PNG, JPEG
  - DLNA
    - Version ..... 1.5 (DMP & DMR support)
    - Audio Format ..... MP3, WMA, WAV, MPEG-4 AAC, FLAC
    - Max Audio Support fs ..... 96 kHz/24 bit
    - Cover Art Format ..... PNG, JPEG
  - [U.S.A. model] Internet Music Service
    - Rhapsody, Sirius Internet Radio
  - Network Control
    - Web Browse Control, MusicCAST2 Commander Support, Yamaha Network Control Support (YNC), Receiver Manager Support

■ Remote

- RS-232C 1
- REMOTE IN 1
- REMOTE OUT 1
- TRIGGER OUT ..... 2 (12 V/total 100 mA max.)

■ Compatible Decoding Format

- Decoding Format
  - Dolby TrueHD, Dolby Digital Plus, Dolby Digital, Dolby Digital EX, DTS-HD Master Audio, DTS-HD High Resolution Audio, DTS Express, DTS, DTS-ES Matrix 6.1, DTS-ES Discrete 6.1, DTS 96/24
- Post Decoding Format
  - Dolby Pro Logic, Dolby Pro Logic II Music, Dolby Pro Logic II Movie, Dolby Pro Logic II Game, Dolby Pro Logic IIx Music, Dolby Pro Logic IIx Movie, Dolby Pro Logic IIx Game, DTS Neo:6 Music, DTS Neo:6 Cinema

■ Audio Section

- Minimum RMS Output Power (20 Hz to 20 kHz, 0.06 % THD, 8 Ω)
  - FRONT L/R ..... 105 W + 105 W
  - CENTER ..... 105 W
  - SURROUND L/R ..... 105 W + 105 W
  - SURROUND BACK L/R ..... 105 W
- Dynamic Power (IHF)
  - FRONT L/R, 8/6/4/2 Ω ..... 135/165/210/280 W

- Dynamic Headroom
  8 Ω ..... 1.1 dB
- Damping Factor
  FRONT L/R, 1 kHz, 8 Ω ..... 150 or more
- Input Sensitivity/Input Impedance
  PHONO .....3.5 mV/47 kΩ
  AUDIO2 etc. .....200 mV/47 kΩ
  MULTI CH IN .....200 mV/47 kΩ
- Maximum Input Level
  PHONO (1 kHz, 0.1 % THD) ..... 60 mV or more
  AUDIO2 etc. (1 kHz, 0.5 % THD) ..... 2.4 V or more
- Output Level/Output Impedance
  AV OUT.....200 mV/1.2 kΩ
  HEADPHONE OUT .....150 mV/100 Ω
  PRE OUT.....1.0 V/1.2 kΩ
  ZONE2 OUT .....1.0 V/1.2 kΩ
- Frequency Response
  AUDIO2 etc. to FRONT L/R
  (Pure Direct, 10 Hz to 100 kHz).....+0/-3 dB
- Total Harmonic Distortion
  PHONO to AV OUT (20 Hz to 20 kHz, 1 V)..... 0.02 % or less
  AV1 to FRONT L/R (20 Hz to 20 kHz, 55 W/8 Ω).... 0.04 % or less
- Signal to Noise Ratio (IHF-A Network)
  PHONO (input shorted, 5 mV) to AV OUT
  [U.S.A and Canada models] .....86 dB or more
  [Australia models] .....81 dB or more
  AUDIO2 etc. (input shorted, 250 mV) to FRONT L/R
  .....100 dB or more
- Residual Noise (IHF-A Network)
  FRONT L/R .....150 µV or less
- Channel Separation (1 kHz/10 kHz)
  PHONO (input shorted).....60 dB/55 dB or more
  AV1 etc. (input 5.1 kΩ shorted).....60 dB/45 dB or more
- Volume Control
  Main Zone ..... MUTE/-80 to +16.5 dB
  Zone2 ..... MUTE/-80 to +16.5 dB
- Tone Control Characteristics
  Main Zone (FRONT)
  Bass Boost/Cut .....±6 dB/50 Hz
  Bass Turnover Frequency .....350 Hz
  Treble Boost/Cut.....±6 dB/20 kHz
  Treble Turnover Frequency .....3.5 kHz
  Zone2
  Bass Boost/Cut .....±10 dB/100 Hz
  Bass Turnover Frequency .....350 Hz
  Treble Boost/Cut.....±10 dB/10 kHz
  Treble Turnover Frequency .....3.5 kHz
- Filter Characteristics (fc=40/60/80/90/100/110/120/160/200 Hz)
  H.P.F. (FRONT, CENTER, SURROUND, SURROUND BACK: Small) .....12 dB/oct.
  L.P.F. (SUBWOOFER) .....24 dB/oct.

■ Video Section

- Video Format (MONITOR OUT/ZONE OUT, Wall Paper/OSD)
  [U.S.A. and Canada models].....NTSC/PAL
  [Australia model] .....PAL/NTSC
- Video Signal Type (Video Conversion) .....NTSC/PAL
- Signal Level
  Composite .....1 Vp-p/75 Ω
  S-video
  - NTSC.....1 Vp-p/75 Ω (Y), 0.286 Vp-p/75 Ω (C)
  - PAL.....1 Vp-p/75 Ω (Y), 0.3 Vp-p/75 Ω (C)
  Component ..... 1 Vp-p/75 Ω (Y), 0.7 Vp-p/75 Ω (PB/PR)
- Maximum Input Level (Video Conversion Off) .....1.5 Vp-p or more
- Signal to Noise Ratio (Video Conversion Off) ..... 60 dB or more
- Frequency Response (Video Conversion Off)
  Component (MONITOR OUT/ZONE OUT)
  ..... 5 Hz to 100 MHz, ±3 dB

■ FM Section

- Tuning Range
  [U.S.A. and Canada models] ..... 87.5 to 107.9 MHz
  [Australia model] ..... 87.50 to 108.00 MHz
- 50 dB Quieting Sensitivity (IHF)
  Mono..... 3.0 µV (20.8 dBf)
- Signal to Noise Ration (IHF)
  Mono/Stereo ..... 74 dB/70 dB
  [U.S.A. model] HD .....80 dB
- Harmonic Distortion (1 kHz)
  Mono/Stereo .....0.3 %/0.3 %
  [U.S.A. model] HD ..... 0.03 %
- Antenna Input .....75 Ω (unbalanced)

■ AM Section

- Tuning Range
  [U.S.A. and Canada models] .....530 to 1710 kHz
  [Australia model] .....531 to 1611 kHz

■ General

- Power Supply
  [U.S.A. and Canada models] ..... AC 120 V, 60 Hz
  [Australia model] ..... AC 240 V, 50 Hz
- Power Consumption
  [U.S.A. model].....490 W/620 VA
  [Canada model].....400 W/510 VA
  [Australia model] .....490 W
- Standby Power Consumption
  HDMI Control Off/Standby Through Off.....0.3 W or less
  HDMI Control On/Standby Through On..... 2.7 W (typical)
  NET Standby On..... 4.5 W (typical)
- Dimensions (W x H x D)
  ..... 435 x 182 x 430 mm (17-1/8 x 7-1/8 x 16-7/8 in)
- Weight..... 14.7 kg (32.4 lbs.)

Index

Numerics

2ch stereo playback 49
5 channel speaker layout 18
5.1-channel speaker layout 17
7.1-channel speaker connection 19
7.1-channel speaker layout 16

A

Adaptive DRC, Option menu 56
Adaptive DSP Level, Sound Setup 94
Advanced Setup menu 109
Advanced speaker configuration 22
AM antenna connection 36
AM tuning 59
Analog to Analog Conversion, Video setup 95
ARC (Audio Return Channel), HDMI setup 96
Aspect, Processing, Video setup 95
AUDIO jack 23
Audio Output, HDMI setup 97
Audio Return Channel function 115
Audio Select, Option menu 57
Audio Signal, Information menu 104
Auto Power Down, Function setup 101
Auto Preset 61
Auto Setup, Speaker setup 89

B

Basic playback 44
BD player connection 27
Bi-amp connection, speaker 20
Bluetooth™ component playback 73
Bookmark Off, Internet Radio 66
Bookmark On, Internet Radio 66
Browse view 58

C

Cable plug 23
Center Image, Sound Program menu 87
Center Level, Sound Program menu 86
Center speaker 15
Center Width, Sound Program menu 87
Changing speaker impedance 20
CINEMA DSP 3D mode 48
CINEMA DSP 3D Mode, Option menu 56
CINEMA DSP indicator 11
CINEMA DSP parameters 84
Clear All Preset 61
Clear Preset 61
Close, DOCK (iPod) 70
COAXIAL jack 23
COMPONENT VIDEO jack 23
Compressed Music Enhancer 49
Configuration, Manual Setup, Speaker setup 90
Connect, Option menu 57
Connecting speakers 19
Connecting to network 34
Connecting USB storage device 35
Connections 15
Content window 58
Control Select, HDMI setup 96
Controlling Zone2 119
Cursor indicators 11

D

Decode Type, Sound Program menu 86, 87
Decoder Mode, Input menu 79
Dialogue Lift, Option menu 56
Dimension, Sound Program menu 87
Direct, Sound Program menu 86
Disconnect, Option menu 57
Display Set, Function setup 102
Distance, Speaker setup 92
DMC Control, Input menu 79
DSP Level, Sound Program menu 84
DVD player connection 27
Dynamic Range, Sound setup 94

E

Enhancer, Input menu 79
Extended Surround, Option menu 56
External component connection 23
External decoder connection 32

F

Features of Web Control Center 75
FIRM UPDATE, Advanced Setup menu 112
FM antenna connection 36
FM Mode 61
FM tuning 59
Front panel 8
Front panel display 11
Front Presence L Level, Sound Program menu 86
Front Presence R Level, Sound Program menu 87
Front speaker 15
Function setup 100

G

Game connection 32

H

HDMI Control function 113
HDMI Control, HDMI setup 96
HDMI indicator 11
HDMI jack 23
HDMI Monitor, Information menu 104
HDMI setup 96
High-frequency sound adjustment 45

I

Information menu 104
Initial Delay, Sound Program menu 84
Initial Volume, Sound setup 94
INITIALIZE, Advanced Setup menu 111
Input Assignment, Function setup 101

Input menu 77
Input menu list 78
Internet Radio 66
IP Address, Network setup 98
iPhone™ playback 69
iPod Interlock, Input menu 79
iPod™ playback 69

J

Jack 23

L

Language 103
Level, Speaker setup 92
Lipsync, Sound setup 93
Liveness, Sound Program menu 85
Load, Scene menu 81
Low-frequency sound adjustment 45

M

MAC Address Filter, Network setup 98
Manual Preset 59
Manual Setup, Speaker setup 89
Manual Tuning, TUNER 60
Max Volume, Sound setup 94
Memory Guard, Function setup 103
Menu browse control 70
MONITOR CHECK, Advanced Setup menu 111
Monitor Out Assign, Multi Zone setup 99
Multi information display 11
Multi Zone setup 99
Multi-format player connection 32
Multi-zone function 117
MUTE indicator 11

N

Network connection 34
NETWORK port 34
Network setup 98
Network Standby, Network setup 98
Network, Information menu 105
Normal tuning 59
Now Playing view 58

O

ON SCREEN menu 52
On-screen display 14
OPTICAL jack 23
Option menu 54
Option menu list 55

P

Pairing, Option menu 57
Panorama, Sound Program menu 87
Parametric EQ, Speaker setup 92
Party mode 119
Party Mode Set, Multi Zone setup 99
PC 62
PHONES jack 9
Play Control, DOCK (iPod) 71
Play Control, PC 63
Play Control, USB 65
Power Amp Assign, Manual Setup, Speaker setup 90
PREOUT connection 22
Presence speaker 15
Presence speaker connection 19
Presence speaker layout 17
Preset Select, TUNER 61
Pure Direct Mode 49
Pure Direct Mode, Sound Setup 94

R

Rear panel 10
Recording device connection 34
RECOV./BACKUP, Advanced Setup menu 111
Registering remote control codes 107
REMOTE CON AMP, Advanced Setup menu 110
Remote control 12
Remote control battery installation 12
Remote control connection 33
Remote control, Controlling other components 106
REMOTE SENSOR, Advanced Setup menu 110
Rename/Icon Select, Input menu 78
Rename/Icon Select, Scene menu 82
Repeat, Option menu 57
Reset, Scene menu 82
Resetting all remote control codes 108
Resolution, Processing, Video setup 95
Reverb Delay, Sound Program menu 85
Reverb Level, Sound Program menu 86
Reverb Time, Sound Program menu 85
Room Size, Sound Program menu 84

S

Save, Scene menu 81
SCENE function 46
Scene menu 80
Setting Data Copy, Manual Setup, Speaker setup 89
Setting Pattern, Manual Setup, Speaker setup 89
Setup menu 88
Setup menu list 89
Shortcut function 68
Shuffle, Option menu 57
SILENT CINEMA mode 47
Simple remote control 71
Sound program 47
Sound program list 50
Sound Program menu 83
Sound setup 93
Speaker connection 15
SPEAKER IMP., Advanced Setup menu 109
Speaker indicators 11
Speaker layout 16, 22
Speaker setting 37
Speaker setup 89
Standby Charge, Input menu 79
Standby Through, HDMI setup 97
Straight decoding mode 48
Subwoofer 15

Supplied accessories 2
Surround Back Initial Delay, Sound Program menu 84
Surround Back L Level, Sound Program menu 86
Surround Back Liveness, Sound Program menu 85
Surround Back R Level, Sound Program menu 86
Surround Back Room Size, Sound Program menu 84
Surround back speaker 15
Surround Initial Delay, Sound Program menu 84
Surround L Level, Sound Program menu 86
Surround Liveness, Sound Program menu 85
Surround R Level, Sound Program menu 86
Surround Room Size, Sound Program menu 84
Surround speaker 15
S-VIDEO jack 23
System, Information menu 105

T

Test Tone, Speaker setup 93
Tone control 45
Tone Control, Option menu 56
Transmitter of the Wireless System for iPod 71
Trigger connection 33
Trigger Output, Function setup 102
Tuner indicator 11
TV Audio Input, HDMI setup 97
TV FORMAT, Advanced Setup menu 111
TV monitor connection 24

U

USB port 35
USB storage device connection 35
USB storage devices 64
Utility, TUNER 61

V

VERSION, Advanced Setup menu 112
VIDEO jack 23
Video Out, Input menu 79
Video setup 95
Video Signal, Information menu 104
Virtual CINEMA DSP 3D mode 48
Virtual CINEMA DSP mode 47
VOLUME 8
VOLUME indicator 11
Volume Trim, Option menu 57

W

Web Control Center 75

Y

YPAO 37

Z

ZONE OUT connection 22
Zone Rename, Multi Zone setup 100
Zone Scene Rename, Multi Zone setup 100
Zone, Information menu 105
Zone2 Set, Multi Zone setup 99

© 2010 Yamaha Corporation

YAMAHA CORPORATION
@ YC711C0/OMEN3